

4. Average performance sheeting is identified as Types I and II sheeting and high performance sheeting is identified as Types III and IV sheeting in Standard Specifications for Construction of Roads and Bridges on Federal Highway Projects<sup>3</sup> (FP-79, Section 633).

TABLE I—COLOR SPECIFICATION LIMITS AND REFERENCE STANDARDS, TYPES I AND II SHEETING

Color	Chromaticity coordinates <sup>1</sup> (corner points)								Reflectance limits (percent Y) Y		Reference <sup>3</sup> standard (munsell papers)
	1		2		3		4		Minium	Max-imum	
	x	y	x	y	x	y	x	y			
White <sup>2</sup> .....	.305	.290	.350	.342	.321	.361	.276	.308	35	—	6.3Gy 6.77/0.8.
Red .....	.602	.317	.664	.336	.644	.356	.575	.356	8	12	8.2R 3.78/14.0.
Orange .....	.535	.375	.607	.393	.582	.417	.535	.399	18	30	2.5YR 5.5/14.0
Brown .....	.445	.353	.604	.396	.556	.443	.445	.386	4	9	5.OYR 3/6.
Yellow .....	.482	.450	.532	.465	.505	.494	.475	.485	29	45	1.25Y 6/12.
Green .....	.130	.369	.180	.391	.155	.460	.107	.439	3.5	9	0.65BG 2.84/8.45.
Blue .....	.147	.075	.176	.091	.176	.151	.106	.113	1.0	4	5.8PB 1.32/6.8.

<sup>1</sup> The four pairs of chromaticity coordinates determine the acceptable color in terms of the CIE 1931 standard colorimetric system measured with standard illumination source C.

<sup>2</sup> Silver white is an acceptable color designation.

<sup>3</sup> Available from Munsell Color Company, 2441 Calvert Street, Baltimore, Maryland 21218.

TABLE II—COLOR SPECIFICATION LIMITS AND REFERENCE STANDARDS, TYPES III AND IV SHEETING

Color	Chromaticity Coordinates <sup>1</sup> (corner points)								Reflectance limits (percent Y) Y		Reference <sup>3</sup> standard (munsell papers)
	1		2		3		4		Min.	Max.	
	x	y	x	y	x	y	x	y			
White <sup>2</sup> .....	.303	.287	.368	.353	.340	.380	.274	.316	27	.....	5.0PB 7/1.
Red .....	.613	.297	.708	.292	.636	.364	.558	.352	2.5	11	7.5R 3/12.
Orange .....	.550	.360	.630	.370	.581	.418	.516	.394	14	30	2.5YR 5.5/14.
Yellow .....	.498	.412	.557	.442	.479	.520	.438	.472	15	40	1.25Y 6/12.
Green .....	.030	.380	.166	.346	.286	.428	.201	.776	3	8	10G 3/8
Blue .....	.144	.030	.244	.202	.190	.247	.066	.208	1	10	5.8PB 1.32/6.8.

<sup>1</sup> The four pairs of chromaticity coordinates determine the acceptable color in terms of the CIE 1931 standard colorimetric system measured with standard illumination source C.

<sup>2</sup> Silver white is an acceptable color designation.

<sup>3</sup> Available from Munsell Color Company, 2441 Calvert Street, Baltimore, Maryland 21218.

**Subpart G [Reserved]**

**PART 656—CARPOOL AND VANPOOL PROJECTS**

Sec.

656.1 Purpose.

656.3 Policy.

656.5 Eligibility.

656.7 Determination of an exception.

AUTHORITY: 23 U.S.C. 146 and 315; sec. 126 of the Surface Transportation Assistance Act of 1978, Pub. L. 95-599, 92 Stat. 2689; 49 CFR 1.48(b).

SOURCE: 47 FR 43024, Sept. 30, 1982, unless otherwise noted.

**§ 656.1 Purpose.**

The purpose of this regulation is to prescribe policies and general procedures for administering a program of ridesharing projects using Federal-aid primary, secondary, and urban system funds.

**§ 656.3 Policy.**

Section 126(d) of the Surface Transportation Assistance Act of 1978 declares that special effort should be made to promote commuter modes of transportation which conserve energy, reduce pollution, and reduce traffic congestion.

<sup>3</sup>This document is available for inspection and copying as prescribed in 49 CFR part 7, appendix D.