

Department of Energy

§ 835.402

skin receiving the maximum dose. This dose equivalent shall:

(i) Be recorded in the individual's occupational exposure history as a special entry; and

(ii) Not be added to any other shallow dose equivalent to any extremity or skin recorded as the dose equivalent for the year.

§ 835.206 Limits for the embryo/fetus.

(a) The dose equivalent limit for the embryo/fetus from the period of conception to birth, as a result of occupational exposure of a declared pregnant worker, is 0.5 rem (0.005 sievert).

(b) Substantial variation above a uniform exposure rate that would satisfy the limits provided in § 835.206(a) shall be avoided.

(c) If the dose equivalent to the embryo/fetus is determined to have already exceeded 0.5 rem (0.005 sievert) by the time a worker declares her pregnancy, the declared pregnant worker shall not be assigned to tasks where additional occupational exposure is likely during the remaining gestation period.

§ 835.207 Occupational dose limits for minors.

The dose equivalent limits for minors occupationally exposed to radiation and/or radioactive materials at a DOE activity are 0.1 rem (0.001 sievert) total effective dose equivalent in a year and 10% of the occupational dose limits specified at § 835.202(a)(3) and (a)(4).

[63 FR 59682, Nov. 4, 1998]

§ 835.208 Limits for members of the public entering a controlled area.

The total effective dose equivalent limit for members of the public exposed to radiation and/or radioactive material during access to a controlled area is 0.1 rem (0.001 sievert) in a year.

[63 FR 59682, Nov. 4, 1998]

§ 835.209 Concentrations of radioactive material in air.

(a) The derived air concentration (DAC) values given in appendices A and C of this part shall be used in the control of occupational exposures to airborne radioactive material.

(b) The estimation of internal dose shall be based on bioassay data rather than air concentration values unless bioassay data are:

(1) Unavailable;

(2) Inadequate; or

(3) Internal dose estimates based on air concentration values are demonstrated to be as or more accurate.

[58 FR 65485, Dec. 14, 1993, as amended at 63 FR 59682, Nov. 4, 1998]

Subpart D [Reserved]

Subpart E—Monitoring of Individuals and Areas

§ 835.401 General requirements.

(a) Monitoring of individuals and areas shall be performed to:

(1) Demonstrate compliance with the regulations in this part;

(2) Document radiological conditions;

(3) Detect changes in radiological conditions;

(4) Detect the gradual buildup of radioactive material;

(5) Verify the effectiveness of engineering and process controls in containing radioactive material and reducing radiation exposure; and

(6) Identify and control potential sources of individual exposure to radiation and/or radioactive material.

(b) Instruments and equipment used for monitoring shall be:

(1) Periodically maintained and calibrated on an established frequency;

(2) Appropriate for the type(s), levels, and energies of the radiation(s) encountered;

(3) Appropriate for existing environmental conditions; and

(4) Routinely tested for operability.

[58 FR 65485, Dec. 14, 1993, as amended at 63 FR 59682, Nov. 4, 1998]

§ 835.402 Individual monitoring.

(a) For the purpose of monitoring individual exposures to external radiation, personnel dosimeters shall be provided to and used by:

(1) Radiological workers who, under typical conditions, are likely to receive one or more of the following:

(i) An effective dose equivalent to the whole body of 0.1 rem (0.001 sievert) or more in a year;