

§ 58.647

have been officially inspected in process and found to be in compliance with these requirements may be identified with the official USDA Quality Approved Inspection Shield.

(b) Dairy products used in the manufacture of frozen desserts for which there are U.S. grades established (non-fat dry milk, whole milk, buttermilk and whey) shall be U.S. Extra Grade or better, and in the case of unsalted butter, shall be no lower than U.S. Grade A. Dairy products for which there are not USDA grade shall meet the applicable requirements of this part which permit such product to bear the USDA Quality Approved Inspection Shield.

§ 58.647 Composition requirements for ice cream.

See § 58.605(a).

§ 58.648 Microbiological requirements for ice cream.

The finished product shall contain not more than 50,000 bacteria per gram as determined by the standard plate count, and shall contain not more than 10 coliform organisms per gram for plain and not more than 20 coliform per gram in chocolate, fruit, nut or other flavors in three out of five samples.

§ 58.649 Physical requirements for ice cream.

(a) *Flavor.* The flavor of the finished ice cream shall be pleasing and desirable, and characteristic of the fresh milk and cream and the particular flavoring used.

(b) *Body and texture.* The body shall be firm, have substance and readily melt to a creamy consistency when exposed to room temperatures; the texture shall be fine, smooth, and have the appearance of creaminess throughout.

(c) *Color.* The color shall be attractive, pleasing, uniform and characteristic of the flavor represented.

§ 58.650 Requirements for frozen custard.

The same requirements apply as for ice cream except plain frozen custard shall have a minimum egg yolk solids content of 1.4 percent, and 1.12 percent when fruits, nuts and other such ingredients are used for flavoring.

7 CFR Ch. I (1-1-01 Edition)

§ 58.651 Requirements for ice milk.

The requirements are the same as for ice cream except: (a) The minimum milk fat content shall be 2 percent by weight and the maximum milk fat content 7 percent by weight, (b) the total milk solids content shall be no less than 11 percent by weight, (c) the minimum total food solids weight per gallon shall be 1.3 pounds, (d) no reduction in the standards are permitted when fruits, nuts and other such ingredients are used for flavoring.

§ 58.652 Composition requirements for sherbet.

See § 58.605(d).

§ 58.653 Microbiological requirements for sherbet.

The finished product shall contain not more than 50,000 bacteria per gram as determined by the standard plate count and shall contain not more than 10 coliform organisms per gram in three out of five samples.

§ 58.654 Physical requirements for sherbet.

(a) *Flavor.* The flavor of the finished sherbet shall be pleasing and desirable and characteristic of the particular flavoring used and shall impart a sweet yet tart sensation.

(b) *Body and texture.* The body shall be firm, compact, somewhat chewy and readily melt to an even syrupy consistency at room temperatures; the texture shall be smooth but not as fine as in ice cream and shall be even throughout.

(c) *Color.* The color shall be attractive, pleasing, uniform and characteristic of the flavor represented.

SUPPLEMENTAL SPECIFICATIONS FOR PLANTS MANUFACTURING, PROCESSING AND PACKAGING PASTEURIZED PROCESS CHEESE AND RELATED PRODUCTS

DEFINITIONS

§ 58.705 Meaning of words.

(a) *Pasteurized process cheese and related products.* Pasteurized process cheese and related products are the foods which conform to the applicable provisions of part 19, title 21, §§ 19.750

through 19.790,¹ "Definitions and Standards of Identity for Cheese and Cheese Products," Food and Drug Administration.

(b) *Blend set up.* The trade term for a particular group of vat lots of cheese selected to form a blend based upon their combined ability to impart the desired characteristics to a pasteurized process cheese product.

(c) *Cooker batch.* The amount of cheese and added optional ingredients placed into a cooker at one time, heated to pasteurization temperature, and held for the required length of time.

EQUIPMENT AND UTENSILS

§ 58.706 General construction, repair and installation.

The equipment and utensils used for the handling and processing of cheese products shall be as specified in § 58.128 of this subpart. In addition, for certain other equipment the following requirements shall be met.

§ 58.707 Conveyors.

Conveyors shall be constructed of material which can be properly cleaned, will not rust, or otherwise contaminate the cheese, and shall be maintained in good repair.

§ 58.708 Grinders or shredders.

The grinders or shredders used in the preparation of the trimmed and cleaned cheese shall be of corrosion-resistant material, and of such construction as to prevent contamination of the cheese and to allow thorough cleaning of all parts and product contact surfaces.

§ 58.709 Cookers.

The cookers shall be the steam jacketed or direct steam type. They shall be constructed of stainless steel or other equally corrosion-resistant material. All product contact surfaces shall be readily accessible for cleaning. Each cooker shall be equipped with an indicating thermometer, and shall be equipped with a temperature recording device. The recording thermometer stem may be placed in the cooker if

satisfactory time charts are obtained, if not, the stem shall be placed in the hotwell or filler hopper. Steam check valves on direct steam type cookers shall be mounted flush with cooker wall, be constructed of stainless steel and designed to prevent the backup of product into the steam line, or the steam line shall be constructed of stainless steel pipes and fittings which can be readily cleaned. If direct steam is applied to the product only culinary steam shall be used (see § 58.127(d)).

§ 58.710 Fillers.

A strainer should be installed between the cooker and the filler. The hoppers of all filters shall be covered but the cover may have sight ports. If necessary, the hopper may have an agitator to prevent buildup on side wall. The filler valves and head shall be kept in good repair and capable of accurate measurements. Product contact surfaces shall be of stainless steel or other corrosion resistant material.

QUALITY SPECIFICATIONS FOR RAW MATERIAL

§ 58.711 Cheddar, colby, washed or soaked curd, granular or stirred curd cheese.

Cheese, used in the manufacture of pasteurized process cheese products should possess a pleasing and desirable taste and odor consistent with the age of the cheese; should have body and texture characteristics which will impart the desired body and texture characteristics in the finished product; and should possess finish and appearance characteristics which will permit removal of all packaging material and surface defects. The cheese should at least meet the requirements equivalent to U.S. Standard Grade for Bulk American Cheese for Manufacturing provided the quantity of the cheese with any one defect as listed for U.S. Standard Grade is limited to assure a satisfactory finished product.

§ 58.712 Swiss.

Swiss cheese used in the manufacture of pasteurized process cheese and related products should be equivalent to U.S. Grade B or better, except that the cheese may be blind or possess finish

¹21 CFR Part 18 was redesignated as Part 131 at 42 FR 14302, Mar. 15, 1977.