

§ 318.302

9 CFR Ch. III (1–1–01 Edition)

the hermetic condition of the containers. The accumulation of stationary containers on moving conveyors should be minimized to avoid damage to the containers.

(2) The maximum time lapse between closing and initiation of thermal processing shall be 2 hours. However, the Administrator may specify a shorter period of time when considered necessary to ensure product safety and stability. A longer period of time between closing and the initiation of thermal processing may be permitted by the Administrator.

(Approved by the Office of Management and Budget under control number 0583–0015)

§ 318.302 Thermal processing.

(a) *Process schedules.* Prior to the processing of canned product for distribution in commerce, an establishment shall have a process schedule (as defined in § 318.300(n) of this subpart) for each canned meat product to be packed by the establishment.

(b) *Source of process schedules.* (1) Process schedules used by an establishment shall be developed or determined by a processing authority.

(2) Any change in product formulation, ingredients, or treatments that are not already incorporated in a process schedule and that may adversely affect either the product heat penetration profile or sterilization value requirements shall be evaluated by the establishment's processing authority. If it is determined that any such change adversely affects the adequacy of the process schedule, the processing authority shall amend the process schedule accordingly.

(3) Complete records concerning all aspects of the development or determination of a process schedule, including any associated incubation tests, shall be made available by the establishment to the Program employee upon request.

(c) *Submittal of process information.* (1) Prior to the processing of canned product for distribution in commerce, the establishment shall provide the inspector at the establishment with a list of the process schedules (including alternate schedules) along with any additional applicable information, such as

the retort come-up operating procedures and critical factors.

(2) Letters or other written communications from a processing authority recommending all process schedules shall be maintained on file by the establishment. Upon request by Program employees, the establishment shall make available such letters or written communications (or copies thereof). If critical factors are identified in the process schedule, the establishment shall provide the inspector with a copy of the procedures for measuring, controlling, and recording these factors, along with the frequency of such measurements, to ensure that the critical factors remain within the limits used to establish the process schedule. Once submitted, the process schedules and associated critical factors and the procedures for measuring (including the frequency), controlling, and recording of critical factors shall not be changed without the prior written submittal of the revised procedures (including supporting documentation) to the inspector at the establishment.

(Approved by the Office of Management and Budget under control number 0583–0015)

§ 318.303 Critical factors and the application of the process schedule.

Critical factors specified in the process schedule shall be measured, controlled and recorded by the establishment to ensure that these factors remain within the limits used to establish the process schedule. Examples of factors that are often critical to process schedule adequacy may include:

(a) *General.* (1) Maximum fill-in weight or drained weight;

(2) Arrangement of pieces in the container;

(3) Container orientation during thermal processing;

(4) Product formulation;

(5) Particle size;

(6) Maximum thickness for flexible, and to some extent semirigid containers during thermal processing;

(7) Maximum pH;

(8) Percent salt;

(9) Ingoing (or formulated) nitrite level (ppm);

(10) Maximum water activity; and

(11) Product consistency or viscosity.

(b) *Continuous rotary and batch agitating retorts.* (1) Minimum headspace; and

(2) Retort reel speed.

(c) *Hydrostatic retorts.* (1) Chain or conveyor speed.

(d) *Steam/air retorts.* (1) Steam/air ratio; and

(2) Heating medium flow rate.

§ 318.304 Operations in the thermal processing area.

(a) *Posting of processes.* Process schedules (or operating process schedules) for daily production, including minimum initial temperatures and operating procedures for thermal processing equipment, shall be posted in a conspicuous place near the thermal processing equipment. Alternatively, such information shall be available to the thermal processing system operator and the inspector.

(b) *Process indicators and retort traffic control.* A system for product traffic control shall be established to prevent product from bypassing the thermal processing operation. Each basket, crate or similar vehicle containing unprocessed product, or at least one visible container in each vehicle, shall be plainly and conspicuously marked with a heat sensitive indicator that will visually indicate whether such unit has been thermally processed. Exposed heat sensitive indicators attached to container vehicles shall be removed before such vehicles are refilled with unprocessed product. Container loading systems for crateless retorts shall be designed to prevent unprocessed product from bypassing the thermal processing operation.

(c) *Initial temperature.* The initial temperature of the contents of the coldest container to be processed shall be determined and recorded by the establishment at the time the processing cycle begins to assure that the temperature of the contents of every container to be processed is not lower than the minimum initial temperature specified in the process schedule. Thermal processing systems which subject the filled and sealed containers to water at any time before process timing begins shall be operated to assure that such water will not lower the temperature of the product below the minimum ini-

tial temperature specified in the process schedule.

(d) *Timing devices.* Devices used to time applicable thermal processing operation functions or events, such as process schedule time, come-up time and retort venting, shall be accurate to assure that all such functions or events are achieved. Pocket watches and wrist watches are not considered acceptable timing devices. Analog and digital clocks are considered acceptable. If such clocks do not display seconds, all required timed functions or events shall have at least a 1-minute safety factor over the specified thermal processing operation times. Temperature/time recording devices shall correspond within 15 minutes to the time of the day recorded on written records required by § 318.306.

(e) *Measurement of pH.* Unless other methods are approved by the Administrator, potentiometric methods using electronic instruments (pH meters) shall be used for making pH determinations when a maximum pH value is specified as a critical factor in a process schedule.

(Approved by Office of Management and Budget under control number 0583-0015)

§ 318.305 Equipment and procedures for heat processing systems.

(a) *Instruments and controls common to different thermal processing systems—*(1) *Indicating temperature devices.* Each retort shall be equipped with at least one indicating temperature device that measures the actual temperature within the retort. The indicating temperature device, not the temperature/time recording device, shall be used as the reference instrument for indicating the process temperature.

(i) *Mercury-in-glass thermometers.* A mercury-in-glass thermometer shall have divisions that are readable to 1F° (or 0.5C°) and whose scale contains not more than 17F°/inch (or 4.0C°/cm) of graduated scale. Each mercury-in-glass thermometer shall be tested for accuracy against a known accurate standard upon installation and at least once a year to ensure its accuracy. Records that specify the date, standard used, test method, and the person or testing authority performing the test shall be