

§ 110.233

33 CFR Ch. I (7-1-01 Edition)

(7) Each vessel moored, anchored, or remaining within the anchorage during the night shall display:

- (i) Anchor lights; and
- (ii) A 32 point red light located from the mast or highest part of the vessel to be visible all around the horizon for a distance of 2 miles.

[CGFR 71-86A, 36 FR 20603, Oct. 27, 1971, as amended by CGD 77-020, 42 FR 30618, June 16, 1977]

§ 110.233 Prince William Sound, Alaska.

(a) *The anchorage grounds.* In Prince William Sound, Alaska, beginning at a point at latitude 60°40'00" N., longitude 146°40'00" W.; thence south to latitude 60°38'00" N., longitude 146°40'00" W.; thence east to latitude 60°38'00" N., longitude 146°30'00" W.; thence north to latitude 60°39'00" N., longitude 146°30'00" W.; thence northwesterly to the beginning point.

(b) *The regulations.* (1) This anchorage area is for the temporary use of vessels during:

- (i) Adverse weather or tidal conditions;
 - (ii) Vessel equipment failure; or
 - (iii) Delays at Port Valdez;
- (2) No vessel may anchor in this anchorage without notifying the vessel traffic center in Valdez; and
- (3) Each vessel anchored shall notify the vessel traffic center in Valdez when it weighs anchor.

[CGD 77-144, 43 FR 21459, May 18, 1978]

§ 110.235 Pacific Ocean (Mamala Bay), Honolulu Harbor, Hawaii (Datum: NAD 83).

(a) *The anchorage grounds*—(1) Anchorage A. The waters bounded by the arc of a circle with a radius of 350 yards with the center located at:

| <i>Latitude</i> | <i>Longitude</i> |
|-----------------|------------------|
| 21°16'57" N | 157°53'12" W |

(2) Anchorage B. The waters bounded by a line connecting the following coordinates:

| <i>Latitude</i> | <i>Longitude</i> |
|-----------------|-------------------|
| 21°17'06" N | 157°54'40" W; to |
| 21°17'22" N | 157°54'40" W; to |
| 21°17'22" N | 157°54'19" W; to |
| 21°17'06" N | 157°54'19" W; and |
| | thence to |
| 21°17'06" N | 157°54'40" W |

(3) Anchorage C. The waters bounded by the arc of a circle with a radius of 450 yards with the center located at:

| <i>Latitude</i> | <i>Longitude</i> |
|-----------------|------------------|
| 21°17'09" N | 157°54'55" W |

(4) Anchorage D. The waters bounded by the arc of a circle with a radius of 450 yards with the center located at:

| <i>Latitude</i> | <i>Longitude</i> |
|-----------------|------------------|
| 21°17'21" N | 157°55'20" W |

(b) *The regulations.* (1) Anchors must be placed inside the anchorage areas.

(2) The anchorages are general anchorages for commercial vessels. Anchorage A should be used only if anchorages B, C, and D are full.

(3) No bunkering operations or vessel to vessel transfer of oil in bulk of any kind is permitted within Anchorage A.

(4) Nothing in this section shall be construed as relieving the owner or person in charge of any vessel from complying with the rules of navigation and with safe navigation practice.

[CGD14-93-003, 59 FR 40820, Aug. 10, 1994]

§ 110.236 Pacific Ocean off Barbers Point, Island of Oahu, Hawaii: Off-shore pipeline terminal anchorages.

(a) *The anchorage grounds*—(1) *Anchorage A.* The waters within an area described as follows: A circle of 1,000 feet radius centered at latitude 21°17'55"N., longitude 158°07'46"W. (Datum: OHD)

(2) *Nonanchorage area A.* The waters extending 300 feet on either side of a line bearing 059° from anchorage A to the shoreline at latitude 21°18'22" N., longitude 158°06'57"W. (Datum: OHD)

(3) *Anchorage B.* The waters enclosed by a line beginning at latitude 21°16'31.5" N., longitude 158°05'09.0" W.; thence to latitude 21°16'03.9" N., longitude 158°05'16.9" W.; thence to latitude 21°16'11.1" N., longitude 158°05'45.8" W.; thence to latitude 21°16'38.8" N., longitude 158°05'37.9" W.; thence to the point of beginning. (Datum: OHD)

(4) *Nonanchorage area B.* The waters extending 300 feet on either side of a line bearing 334.5° from anchorage B to the shoreline at latitude 21°17'50.5" N., longitude 158°06'13.1" W. (Datum: OHD)

(5) *Anchorage C.* The waters enclosed by a line beginning at latitude 21°16'58" N., longitude 158°04'39" W.; thence to

latitude 21°16'58" N., longitude 158°04'12" W.; thence to latitude 21°16'44" N., longitude 158°04'12" W.; thence to latitude 21°16'44" N., longitude 158°04'39" W.; thence to the point of beginning. (Datum: OHD)

(6) *Nonanchorage area C.* The waters extending 300 feet on either side of a line bearing 306° from anchorage C to the shoreline at latitude 21°17'54.9" N., longitude 158°06'07.8" W. (Datum: OHD)

(7) *Anchorage D.* The waters enclosed by a line beginning at latitude 21°18'00" N., longitude 158°07'20" W.; thence to latitude 21°17'56" N., longitude 158°07'16" W.; thence to latitude 21°17'49" N., longitude 158°07'24" W.; thence to latitude 21°17'53" N., longitude 158°07'28" W.; thence to the point of beginning. (Datum: OHD)

(b) *The regulations.* (1) No vessels may anchor, moor, or navigate in anchorages A, B, C, or D except:

(i) Vessels using the anchorages and their related pipelines for loading or unloading;

(ii) Commercial tugs, lighters, barges, launches, or other vessels engaged in servicing the anchorage facilities or vessels using them;

(iii) Public vessels of the United States.

(2) When vessels are conducting loading or unloading operations as indicated by the display of a red flag (international code flag B) at the masthead, passing vessels of over 100 gross tons shall not approach within 1,000 yards at a speed in excess of 6 knots.

(3) The owner of any vessel wanting to use an anchorage ground and use of the related pipeline facilities shall notify the Captain of the Port, Honolulu, Hawaii, and the Commanding Officer, U.S. Naval Air Station, Barbers Point, Hawaii, at least 24 hours in advance of desired occupancy of the anchorage ground by the vessel. Such notification must include the maximum height above the waterline of the uppermost portion of the vessel's mast and a description of the masts' lighting including height of the highest anchor light and any aircraft warning lights to be displayed by the vessel at night.

(4) When, in the opinion of the Captain of the Port, or his authorized representative, oil transfer operations within these anchorages could jeop-

ardize the safety of vessels or facilities in the area, or cause an undue risk of oil pollution, such oil transfer operations shall be immediately terminated until such time as the cognizant Coast Guard officer determines that the danger has subsided.

(5) Nonanchorage areas A, B, and C are established for the protection of submerged pipelines. Except for vessels servicing pipeline facilities, no anchoring, dragging, seining or other potential pipeline fouling activities are permitted within these areas.

(6) Nothing in this section shall be construed as relieving the owner or person in charge of any vessel from complying with the rules of the road and safe navigation practice.

(7) The regulations of this section are enforced by the Captain of the Port or his duly authorized representative.

[CGD 73-59R, 38 FR 16777, June 26, 1973, as amended by CGD 96-026, 61 FR 33663, June 28, 1996]

§ 110.237 Pacific Ocean at Waimea, Hawaii, Naval Anchorage.

(a) *The Anchorage grounds.* All the waters within a circle having a radius of 300 yards centered at latitude 21°57'02" N., longitude 159°41'33" W. (Datum: OHD)

(b) *The regulation.* Except in an emergency, no vessel except a Naval vessel may anchor or moor in this anchorage without permission of the Captain of the Port, Honolulu, Hawaii.

[CGD 74-187, 41 FR 54176, Dec. 13, 1976, as amended by CGD 96-026, 61 FR 33663, June 28, 1996]

§ 110.238 Apra Harbor, Guam.

(a) The anchorage grounds (Datum: WGS 84). (1) General Anchorage. The waters bounded by a line connecting the following points:

| Latitude | Longitude |
|--------------------|---------------|
| 13°27'32.0"N | 144°39'36.8"E |
| 13°27'21.0"N | 144°39'22.8"E |
| 13°27'12.5"N | 144°37'25.4"E |

and thence along the shoreline to

| Latitude | Longitude |
|--------------------|---------------|
| 13°27'45.5"N | 144°39'34.8"E |

and thence to the point of beginning.