

sampling scheme and the guidance document are available from the Director, Environmental Assistance Division (7408), Office of Pollution Prevention and Toxics, U.S. Environmental Protection Agency, Room E-543B, 1200 Pennsylvania Ave., NW., Washington, DC 20460, Telephone: (202) 554-1404, TDD: (202) 544-0551. The major advantage of this sampling scheme is that it is designed to characterize the degree of contamination within the entire sampling area with a high degree of confidence while using fewer samples than any other grid or random sampling scheme. This sampling scheme also allows some sites to be characterized on the basis of composite samples.

(f) EPA may, at its discretion, take samples from any spill site. If EPA's sampling indicates that the remaining concentration level exceeds the required level, EPA will require further cleanup. For this purpose, the numerical level of cleanup required for spills cleaned in accordance with § 761.125(b) is deemed to be the equivalent of numerical cleanup requirements required for cleanups under § 761.125(c) (2) through (4). Using its best engineering judgment, EPA may sample a statistically valid random or grid sampling technique, or both. When using engineering judgment or random "grab" samples, EPA will take into account that there are limits on the power of a grab sample to dispute statistically based sampling of the type required of the responsible party. EPA headquarters will provide guidance to the EPA regions on the degree of certainty associated with various grab sample results.

[52 FR 10705, Apr. 2, 1987, as amended at 60 FR 34465, July 3, 1995]

§ 761.135 Effect of compliance with this policy and enforcement.

(a) Although a spill of material containing 50 ppm or greater PCBs is considered improper PCB disposal, this policy establishes requirements that EPA considers to be adequate cleanup of the spilled PCBs. Cleanup in accordance with this policy means compliance with the procedural as well as the numerical requirements of this policy. Compliance with this policy creates a presumption against both enforcement

action for penalties and the need for further cleanup under TSCA. The Agency reserves the right, however, to initiate appropriate action to compel cleanup where, upon review of the records of cleanup or EPA sampling following cleanup, EPA finds that the decontamination levels in the policy have not been achieved. The Agency also reserves the right to seek penalties where the Agency believes that the responsible party has not made a good faith effort to comply with all provisions of this policy, such as prompt notification of EPA of a spill, recordkeeping, etc.

(b) EPA's exercise of enforcement discretion does not preclude enforcement action under other provisions of TSCA or any other Federal statute. This includes, even in cases where the numerical decontamination levels set forth in this policy have been met, civil or criminal action for penalties where EPA believes the spill to have been the result of gross negligence or knowing violation.

Subparts H-I [Reserved]

Subpart J—General Records and Reports

§ 761.180 Records and monitoring.

This section contains recordkeeping and reporting requirements that apply to PCBs, PCB Items, and PCB storage and disposal facilities that are subject to the requirements of the part.

(a) *PCBs and PCB Items in service or projected for disposal.* Beginning February 5, 1990, each owner or operator of a facility, other than a commercial storer or a disposer of PCB waste, using or storing at any one time at least 45 kilograms (99.4 pounds) of PCBs contained in PCB Container(s), or one or more PCB Transformers, or 50 or more PCB Large High or Low Voltage Capacitors shall develop and maintain at the facility, or a central facility provided they are maintained at that facility, all annual records and the written annual document log of the disposition of PCBs and PCB Items. The written annual document log must be prepared for each facility by July 1 covering the previous calendar year (January through December). The annual

Environmental Protection Agency

§ 761.180

document log shall be maintained for at least 3 years after the facility ceases using or storing PCBs and PCB Items in the quantities prescribed in this paragraph. Annual records (manifests and certificates of disposal) shall be maintained for the same period. The annual records and the annual document log shall be available for inspection at the facility where they are maintained by authorized representatives of EPA during normal business hours, and each owner or operator of a facility subject to these requirements shall know the location of these records. All records and annual documents required to be prepared and maintained by this section prior to February 5, 1990 shall continue to be maintained at the facility for the same time as the annual records and the annual document log. The annual document required for 1989 shall cover the period from January 1, 1989 to February 5, 1990.

(1) The annual records shall include the following:

(i) All signed manifests generated by the facility during the calendar year.

(ii) All Certificates of Disposal that have been received by the facility during the calendar year.

(iii) Records of inspections and cleanups performed in accordance with § 761.65(c)(5).

(2) The written annual document log shall include the following:

(i) The name, address, and EPA identification number of the facility covered by the annual document log and the calendar year covered by the annual document log.

(ii) The unique manifest number of every manifest generated by the facility during the calendar year, and from each manifest and for unmanifested waste that may be stored at the facility, the following information:

(A) For bulk PCB waste (*e.g.*, in a tanker or truck), its weight in kilograms, the first date it was removed from service for disposal, the date it was placed into transport for off-site storage or disposal, and the date of disposal, if known.

(B) The serial number (if available) or other means of identifying each PCB Article (*e.g.*, transformer or capacitor), the weight in kilograms of the PCB

waste in each transformer or capacitor, the date it was removed from service for disposal, the date it was placed in transport for off-site storage or disposal, and the date of disposal, if known.

(C) A unique number identifying each PCB Container, a description of the contents of each PCB Container, such as liquid, soil, cleanup debris, etc., including the total weight of the material in kilograms in each PCB Container, the first date material placed in each PCB Container was removed from service for disposal, and the date each PCB Container was placed in transport for off-site storage or disposal, and the date of disposal (if known).

(D) A unique number identifying each PCB Article Container, a description of the contents of each PCB Article Container, such as pipes, capacitors, electric motors, pumps, etc., including the total weight in kilograms of the content of each PCB Article Container, the first date a PCB Article placed in each PCB Article Container was removed from service for disposal, and the date the PCB Article Container was placed in transport for off-site storage or disposal, and the date of disposal (if known.)

(iii) The total number by specific type of PCB Articles and the total weight in kilograms of PCBs in PCB Articles, the total number of PCB Article Containers and total weight in kilograms of the contents of PCB Article Containers, the total number of PCB Containers and the total weight in kilograms of the contents of PCB Containers, and the total weight in kilograms of bulk PCB waste that was placed into storage for disposal or disposed during the calendar year.

(iv) The total number of PCB Transformers and total weight in kilograms of PCBs contained in the transformers remaining in service at the end of the calendar year.

(v) The total number of Large High or Low Voltage PCB Capacitors remaining in service at the end of the calendar year.

(vi) The total weight in kilograms of any PCBs and PCB Items in PCB Containers, including the identification of

container contents, remaining in service at the facility at the end of the calendar year.

(vii) For any PCBs or PCB item received from or shipped to another facility owned or operated by the same generator, the information required under paragraph (a)(2)(ii)(A) through (a)(2)(ii)(D) of this section.

(viii) A record of each telephone call, or other means of verification agreed upon by both parties, made to each designated commercial storer or designated disposer to confirm receipt of PCB waste transported by an independent transporter, as required by §761.208.

(ix) Whenever a PCB Item, excluding small capacitors, with a concentration of ≥ 50 ppm is distributed in commerce for reuse pursuant to §761.20(c)(1), the name, address, and telephone number of the person to whom the item was transferred, date of transfer, and the serial number of the item or the internal identification number, if a serial number is not available, must be recorded in the annual document log. The serial number or internal identification number shall be permanently marked on the equipment.

(3) [Reserved]

(4) For purposes of this paragraph, PCB Voltage Regulators shall be recorded as PCB Transformers.

(b) *Disposers and commercial storers of PCB waste.* Beginning February 5, 1990, each owner or operator of a facility (including high efficiency boiler operations) used for the commercial storage or disposal of PCBs and PCB Items shall maintain annual records on the disposition of all PCBs and PCB items at the facility and prepare and maintain a written annual document log that includes the information required by paragraphs (b)(2) of this section for PCBs and PCB Items that were handled as PCB waste at the facility. The written annual document log shall be prepared by July 1 for the previous calendar year (January through December). The written annual document log shall be maintained at each facility for at least 3 years after the facility is no longer used for the storage or disposal of PCBs and PCB Items except that, in the case of chemical waste landfills,

the annual document log shall be maintained at least 20 years after the chemical waste landfill is no longer used for the disposal of PCBs and PCB Items. The annual records shall be maintained for the same period. The annual records and written annual document log shall be available at the facility for inspection by authorized representatives of the EPA. All records and annual documents required to be prepared and maintained by this section prior to February 5, 1990 shall continue to be maintained at the facility for the same time as the annual records and the annual document log. The annual document for 1989 shall cover the period from January 1, 1989 to February 5, 1990. From the written annual document log the owner or operator of a facility must prepare the annual report containing the information required by paragraphs (b)(3)(i) through (b)(3)(vi) of this section for PCBs and PCB Items that were handled as PCB waste at the facility during the previous calendar year (January through December). The annual report must be submitted by July 15 of each year for the preceding calendar year. If the facility ceases commercial PCB storage or disposal operations, the owner or operator of the facility shall provide at least 60 days advance written notice to the Regional Administrator for the region in which the facility is located of the date the facility intends to begin closure. d

(1) The annual records shall include the following:

(i) All signed manifests generated or received at the facility during the calendar year.

(ii) All Certificates of Disposal that have been generated or received by the facility during the calendar year.

(iii) Records of inspections and cleanups performed in accordance with §761.65(c)(5).

(2) The written annual document log shall include the following:

(i) The name, address, and EPA identification number of the storage or disposal facility covered by the annual document log and the calendar year covered by the annual document log.

(ii) For each manifest generated or received by the facility during the calendar year, the unique manifest number and the name and address of the facility that generated the manifest and the following information:

(A) For bulk PCB waste (*e.g.*, in a tanker or truck), its weight in kilograms, the first date PCB waste placed in the tanker or truck was removed from service for disposal, the date it was received at the facility, the date it was placed in transport for off-site disposal (if applicable), and the date of disposal, (if known).

(B) The serial number or other means of identifying each PCB Article, not in a PCB Container or PCB Article Container, the weight in kilograms of the PCB waste in the PCB Article, the date it was removed from service for disposal, the date it was received at the facility, the date it was placed in transport for off-site disposal (if applicable), and the date of disposal (if known).

(C) The unique number assigned by the generator identifying each PCB Container, a description of the contents of each PCB Container, such as liquid, soil, cleanup debris, etc., including the total weight of the PCB waste in kilograms in each PCB Container, the first date PCB waste placed in each PCB Container was removed from service for disposal, the date it was received at the facility, the date each PCB Container was placed in transport for off-site storage or disposal (as applicable), and the date the PCB Container was disposed of (if known).

(D) The unique number assigned by the generator identifying each PCB Article Container, a description of the contents of each PCB Article Container, such as pipes, capacitors, electric motors, pumps, etc., including the total weight in kilograms of the PCB waste in each PCB Article Container, the first date a PCB Article placed in each PCB Article Container was removed from service for disposal, the date it was received at the facility, the date each PCB Article Container was placed in transport for off-site storage or disposal (as applicable), and the date the PCB Article Container was disposed of (if known).

(E) Disposers of PCB waste shall include the confirmed date of disposal for items in paragraphs (b)(2)(ii)(A) through (b)(2)(ii)(D) of this section.

(iii) For any PCB waste disposed at a facility that generated the PCB waste or any PCB waste that was not manifested to the facility, the information required under paragraph (b)(2)(ii)(A) through (b)(2)(ii)(E) of this section.

(3) The owner or operator of a PCB disposal facility (including an owner or operator who disposes of his/her own waste and does not receive or generate manifests) or a commercial storage facility shall submit an annual report, which briefly summarizes the records and annual document log required to be maintained and prepared under paragraphs (b)(1) and (b)(2) of this section to the EPA Regional Administrator of the Region in which the facility is located by July 15 of each year, beginning with July 15, 1991. The first annual report submitted on July 15, 1991, shall be for the period starting February 5, 1990, and ending December 31, 1990. The annual report shall contain no confidential business information. The annual report shall consist of the information listed in paragraphs (b)(3)(i) through (b)(3)(vi) of this section.

(i) The name, address, and EPA identification number of the facility covered by the annual report for the calendar year.

(ii) A list of the numbers of all signed manifests of PCB waste initiated or received by the facility during that year.

(iii) The total weight in kilograms of bulk PCB waste, PCB waste in PCB Transformers, PCB waste in PCB Large High or Low Voltage Capacitors, PCB waste in PCB Article Containers, and PCB waste in PCB Containers in storage at the facility at the beginning of the calendar year, received or generated at the facility, transferred to another facility, or disposed of at the facility during the calendar year. The information must be provided for each of these categories, as appropriate.

(iv) The total number of PCB Transformers, the total number of PCB Large High or Low Voltage Capacitors, the total number of PCB Article Containers, and the total number of PCB Containers in storage at the facility at

the beginning of the calendar year, received or generated at the facility, transferred to another facility, or disposed of at the facility during the calendar year. The information must be provided for each of these categories, as appropriate.

(v) The total weight in kilograms of each of the following PCB categories: bulk PCB waste, PCB waste in PCB Transformers, PCB waste in PCB Large High or Low Voltage Capacitors, PCB waste in PCB Article Containers, and PCB waste in PCB Containers remaining in storage for disposal at the facility at the end of the calendar year.

(vi) The total number of PCB Transformers, the total number of PCB Large High or Low Voltage Capacitors, the total number of PCB Article Containers, and the total number of PCB Containers remaining in storage for disposal at the facility at the end of the calendar year.

(vii) The requirement to submit annual reports to the Regional Administrator continues until the submission of the annual report for the calendar year during which the facility ceases PCB storage or disposal operations. Storage operations have not ceased until all PCB waste, including any PCB waste generated during closure, has been removed from the facility.

(4) Whenever a commercial storer of PCB waste accepts PCBs or PCB Items at his storage facility and transfers the PCB waste off-site to another facility for storage or disposal, the commercial storer of PCB waste shall initiate a manifest under subpart K of this part for the transfer of PCBs or PCB Items to the next storage or disposal facility.

NOTE: Any requirements for weights in kilograms of PCBs may be calculated values if the internal volume of PCBs in containers and transformers is known and included in the reports, together with any assumptions on the density of the PCBs contained in the containers or transformers. If the internal volume of PCBs is not known, a best estimate may be used.

(5) For purposes of this paragraph, PCB Voltage Regulators shall be recorded and reported as PCB Transformers.

(c) *Incineration facilities.* Each owner or operator of a PCB incinerator facility shall collect and maintain for a period of 5 years from the date of collec-

tion the following information, in addition to the information required in paragraph (b) of this section:

(1) When PCBs are being incinerated, the following continuous and short-interval data:

(i) Rate and quantity of PCBs fed to the combustion system as required in § 761.70(a)(3);

(ii) Temperature of the combustion process as required in § 761.70(a)(4); and

(iii) Stack emission product to include O₂, CO, and CO₂ as required in § 761.70(a)(7).

(2) When PCBs are being incinerated, data and records on the monitoring of stack emissions as required in § 761.70(a)(6).

(3) Total weight in kilograms of any solid residues generated by the incineration of PCBs and PCB Items during the calendar year, the total weight in kilograms of any solid residues disposed of by the facility in chemical waste landfills, and the total weight in kilograms of any solid residues remaining on the facility site.

(4) When PCBs and PCB Items are being incinerated, additional periodic data shall be collected and maintained as specified by the Regional Administrator pursuant to § 761.70(d)(4).

(5) Upon any suspension of the operation of any incinerator pursuant to § 761.70(a)(8), the owner or operator of such an incinerator shall prepare a document. The document shall, at a minimum, include the date and time of the suspension and an explanation of the circumstances causing the suspension of operation. The document shall be sent to the appropriate Regional Administrator within 30 days of any such suspension.

(d) *Chemical waste landfill facilities.* Each owner or operator of a PCB chemical waste landfill facility shall collect and maintain until at least 20 years after the chemical waste landfill is no longer used for the disposal of PCBs the following information in addition to the information required in paragraph (b) of this section:

(1) Any water analysis obtained in compliance with § 761.75(b)(6)(iii); and

(2) Any operations records including burial coordinates of wastes obtained in compliance with § 761.75(b)(8)(ii).

Environmental Protection Agency

§ 761.185

(e) *High efficiency boiler facilities.* Each owner or operator of a high efficiency boiler used for the disposal of liquids between 50 and 500 ppm PCB shall collect and maintain for a period of 5 years the following information, in addition to the information required in paragraph (b) of this section:

(1) For each month PCBs are burned in the boiler the carbon monoxide and excess oxygen data required in § 761.71(a)(1)(viii) and § 761.71(b)(1)(viii);

(2) The quantity of PCBs burned each month as required in § 761.71(a)(1)(vii) and § 761.71(b)(1)(vii); and

(3) For each month PCBs (other than mineral oil dielectric fluid) are burned, chemical analysis data of the waste as required in § 761.71(b)(2)(vi).

(f) *Retention of special records by storage and disposal facilities.* In addition to the information required to be maintained under paragraphs (b), (c), (d) and (e) of this section, each owner or operator of a PCB storage or disposal facility (including high efficiency boiler operations) shall collect and maintain for the time period specified in paragraph (b) of this section the following data:

(1) All documents, correspondence, and data that have been provided to the owner or operator of the facility by any State or local government agency and that pertain to the storage or disposal of PCBs and PCB Items at the facility.

(2) All documents, correspondence, and data that have been provided by the owner or operator of the facility to any State or local government agency and that pertain to the storage or disposal of PCBs and PCB Items at the facility.

(3) Any applications and related correspondence sent by the owner or operator of the facility to any local, State, or Federal authorities in regard to waste water discharge permits, solid waste permits, building permits, or other permits or authorizations such as those required by §§ 761.70(d) and 761.75(c).

(g) *Reclassification records.* If you reclassify electrical equipment using the procedures in § 761.30(a)(2)(v) or § 761.30(h)(2)(v), you must keep records showing that you followed the required reclassification procedures. Where these procedures require testing, the

records must include copies of pre- and post-reclassification PCB concentration measurements from a laboratory using quality control and quality assurance procedures. You must make these records available promptly to EPA or to any party possessing the equipment through sale, loan, lease, or for servicing. You must retain the records for at least 3 years after you sell or dispose of the equipment.

(Sec. 6, Pub. L. 94-469, 90 Stat. 2020 (15 U.S.C. 2605)

[44 FR 31542, May 31, 1979. Redesignated at 47 FR 19527, May 6, 1982, and further redesignated at 47 FR 37360, Aug. 25, 1982; 49 FR 28191, July 10, 1984; 53 FR 12524, Apr. 15, 1988; 54 FR 52750, Dec. 21, 1989; 55 FR 26205, June 27, 1990; 58 FR 34205, June 23, 1993; 63 FR 35461, June 29, 1998; 66 FR 17619, Apr. 2, 2001]

§ 761.185 Certification program and retention of records by importers and persons generating PCBs in excluded manufacturing processes.

(a) In addition to meeting the basic requirements of § 761.1(f) and the definition of excluded manufacturing processes at § 761.3, manufacturers with processes inadvertently generating PCBs and importers of products containing inadvertently generated PCBs must report to EPA any excluded manufacturing process or imports for which the concentration of PCBs in products leaving the manufacturing site or imported is greater than 2 micrograms per gram (2 µg/g, roughly 2 ppm) for any resolvable gas chromatographic peak. Such reports must be filed by October 1, 1984 or, if no processes or imports require reports at the time, within 90 days of having processes or imports for which such reports are required.

(b) Manufacturers required to report by paragraph (a) of this section must transmit a letter notifying EPA of the number, the type, and the location of excluded manufacturing processes in which PCBs are generated when the PCB level in products leaving any manufacturing site is greater than 2 µg/g for any resolvable gas chromatographic peak. Importers required to report by paragraph (a) of this section must transmit a letter notifying EPA of the concentration of PCBs in imported products when the PCB concentration