

§ 761.19

40 CFR Ch. I (7–1–02 Edition)

Wet weight means reporting chemical analysis results by including either the weight, or the volume and density, of all liquids.

(Sec. 6, Pub. L. 94–469, 90 Stat. 2020 (15 U.S.C. 2605)

[49 FR 25239, June 20, 1984, as amended at 49 FR 28189, July 10, 1984; 49 FR 29066, July 18, 1984; 49 FR 44638, Nov. 8, 1984; 50 FR 29199, July 17, 1985; 50 FR 32176, Aug. 9, 1985; 53 FR 24220, June 27, 1988; 53 FR 27327, July 19, 1988; 54 FR 52745, Dec. 21, 1989; 55 FR 26205, June 27, 1990; 58 FR 32061, June 8, 1993; 61 FR 11106, Mar. 18, 1996; 63 FR 35437, June 29, 1998; 64 FR 33759, June 24, 1999]

§ 761.19 References.

(a) [Reserved]

(b) *Incorporation by reference.* The following material is incorporated by reference, and is available for inspection at the Office of the Federal Register, 800 North Capitol St., NW., Suite 700, Washington, DC. These incorporations by reference were approved by the Director of the Office of the Federal Register. These materials are incorporated as they exist on the date of approval and a notice of any change in these materials will be published in the FEDERAL REGISTER. Copies of the incorporated material are available for inspection at the TSCA Nonconfidential Information Center (7407), Rm. B607, Northeast Mall, Office of Pollution Prevention and Toxics, Environmental Protection Agency, 401 M St., SW., Washington, DC 20460. Copies of the incorporated material may be obtained from the American Society for Testing and Materials (ASTM), 100 Barr Harbor Drive, West Conshohocken, PA 19428–2959.

References	CFR Citation
ASTM D 93 – 90 Standard Test Methods for Flash Point by Pensky-Martens Closed Tester.	§ 761.71(b)(2)(vi); § 761.75(b)(8)(iii)
ASTM D 129–64 (Re-approved 1978) Standard Test Method for Sulfur in Petroleum Products (General Bomb Method).	§ 761.71(b)(2)(vi)
ASTM D 240–87 Standard Test Method for Heat of Combustion of Liquid Hydrocarbon Fuel by Bomb Calorimeter.	§ 761.71(b)(2)(vi)

References	CFR Citation
ASTM D 482–87 Standard Test Method for Ash from Petroleum Products.	§ 761.71(b)(2)(vi)
ASTM D 524–88 Standard Test Method for Ramsbottom Carbon Residue of Petroleum Products.	§ 761.71(b)(2)(vi)
ASTM D 808–87 Standard Test Method for Chlorine in New and Used Petroleum Products (Bomb Method).	§ 761.71(b)(2)(vi)
ASTM D 923–86 Standard Test Method for Sampling Electrical Insulating Liquids.	§ 761.60(g)(1)(ii); (g)(2)(ii)
ASTM D 923–89 Standard Methods of Sampling Electrical Insulating Liquids.	§ 761.60(g)(1)(ii); (g)(2)(ii)
ASTM D 1266–87 Standard Test Method for Sulfur in Petroleum Products (Lamp Method).	§ 761.71(b)(2)(vi)
ASTM D 1796–83 (Re-approved 1990) Standard Test Method for Water and Sediment in Fuel Oils by the Centrifuge Method (Laboratory Procedure).	§ 761.71(b)(2)(vi)
ASTM D 2158–89 Standard Test Method for Residues in Liquefied Petroleum (LP) Gases.	§ 761.71(b)(2)(vi)
ASTM D 2709–88 Standard Test Method for Water and Sediment in Distillate Fuels by Centrifuge.	§ 761.71(b)(2)(vi)
ASTM D 2784–89 Standard Test Method for Sulfur in Liquefied Petroleum Gases (Oxy-hydrogen Burner or Lamp).	§ 761.71(b)(2)(vi)
ASTM D 3178–84 Standard Test Methods for Carbon and Hydrogen in the Analysis Sample of Coke and Coal.	§ 761.71(b)(2)(vi)
ASTM D 3278–89 Standard Test Methods for Flash Point of Liquids by Setaflash Closed-Cup Apparatus.	§ 761.75(b)(8)(iii)
ASTM E 258–67 (Re-approved 1987) Standard Test Method for Total Nitrogen Inorganic Material by Modified KJELDAHL Method.	§ 761.71(b)(2)(vi)

[47 FR 22098, May 21, 1982, as amended at 49 FR 29067, July 18, 1984; 49 FR 36648, Sept. 19, 1984; 53 FR 10391, Mar. 31, 1988; 53 FR 12524, Apr. 15, 1988; 53 FR 21641, June 9, 1988; 57 FR 13323, Apr. 16, 1992; 59 FR 33697, June 30, 1994; 60 FR 34465, July 3, 1995; 63 FR 35439, June 29, 1998; 64 FR 33759, June 24, 1999]