

## Environmental Protection Agency

## § 761.218

explaining the efforts taken to locate the PCB waste and the results of those efforts.

(c) A disposer of PCB waste shall submit a One-year Exception Report to the EPA Regional Administrator for the Region in which the disposal facility is located no later than 45 days from the end of the 1-year storage for disposal date when the following occurs:

(1) The disposal facility receives PCBs or PCB Items on a date more than 9 months from the date the PCBs or PCB Items were removed from service for disposal, as indicated on the manifest or continuation sheet; and

(2) Because of contractual commitments or other factors affecting the facility's disposal capacity, the disposer of PCB waste could not dispose of the affected PCBs or PCB Items within 1 year of the date of removal from service for disposal.

(d) A generator or commercial storer of PCB waste who manifests PCBs or PCB Items to a disposer of PCB waste shall submit a One-year Exception Report to the EPA Regional Administrator for the Region in which the generator or commercial storer is located no later than 45 days from the date the following occurs:

(1) The generator or commercial storer transferred the PCBs or PCB Items to the disposer of PCB waste on a date within 9 months from the date of removal from service for disposal of the affected PCBs or PCB Items, as indicated on the manifest or continuation sheet; and

(2) The generator or commercial storer either has not received within 13 months from the date of removal from service for disposal a Certificate of Disposal confirming the disposal of the affected PCBs or PCB Items, or the generator or commercial storer receives a Certificate of Disposal confirming disposal of the affected PCBs or PCB Items on a date more than 1 year after the date of removal from service.

(e) The One-year Exception Report shall include:

(1) A legible copy of any manifest or other written communication relevant to the transfer and disposal of the affected PCBs or PCB Items.

(2) A cover letter signed by the submitter or an authorized representative explaining:

(i) The date(s) when the PCBs or PCB Items were removed from service for disposal.

(ii) The date(s) when the PCBs or PCB Items were received by the submitter of the report, if applicable.

(iii) The date(s) when the affected PCBs or PCB Items were transferred to a designated disposal facility.

(iv) The identity of the transporters, commercial storers, or disposers known to be involved with the transaction.

(v) The reason, if known, for the delay in bringing about the disposal of the affected PCBs or PCB Items within 1 year from the date of removal from service for disposal.

(f) PCB/radioactive waste that is exempt from the 1-year storage for disposal time limit pursuant to § 761.65(a)(1) is also exempt from the exception reporting requirements of paragraphs (c), (d), and (e) of this section.

[54 FR 52752, Dec. 21, 1989, as amended at 55 FR 26205, June 27, 1990; 58 FR 34205, June 23, 1993; 63 FR 35461, June 29, 1998]

### § 761.218 Certificate of disposal.

(a) For each shipment of manifested PCB waste that the owner or operator of a disposal facility accepts by signing the manifest, the owner or operator of the disposal facility shall prepare a Certificate of Disposal for the PCBs and PCB Items disposed of at the facility, which shall include:

(1) The identity of the disposal facility, by name, address, and EPA identification number.

(2) The identity of the PCB waste affected by the Certificate of Disposal including reference to the manifest number for the shipment.

(3) A statement certifying the fact of disposal of the identified PCB waste, including the date(s) of disposal, and identifying the disposal process used.

(4) A certification as defined in § 761.3.

(b) The owner or operator of the disposal facility shall send the Certificate of Disposal to the generator identified on the manifest which accompanied the shipment of PCB waste within 30 days of the date that disposal of each item

## § 761.240

of PCB waste identified on the manifest was completed unless the generator and the disposer contractually agree to another time frame.

(c) The disposal facility shall keep a copy of each Certificate of Disposal among the records that it retains under § 761.180(b).

(d)(1) Generators of PCB waste shall keep a copy of each Certificate of Disposal that they receive from disposers of PCB waste among the records they retain under § 761.180(a).

(2) Commercial storers of PCB waste shall keep a copy of each Certificate of Disposal that they receive from disposers of PCB waste among the records they retain under § 761.180(b).

[54 FR 52752, Dec. 21, 1984, as amended at 63 FR 35462, June 29, 1998]

### Subpart L [Reserved]

### Subpart M—Determining a PCB Concentration for Purposes of Abandonment or Disposal of Natural Gas Pipeline: Selecting Sample Sites, Collecting Surface Samples, and Analyzing Standard PCB Wipe Samples

SOURCE: 63 FR 35462, June 29, 1998, unless otherwise noted.

#### § 761.240 Scope and definitions.

(a) Use these procedures to select surface sampling sites for natural gas pipe to determine its PCB surface concentration for abandonment-in-place or removal and disposal off-site in accordance with § 761.60(b)(5).

(b) "Pipe segment" means a length of natural gas pipe that has been removed from the pipeline system to be disposed of or reused, and that is usually approximately 12.2 meters (40 feet) or shorter in length. Pipe segments are usually linear.

(c) "Pipeline section" means a length of natural gas pipe that has been cut or otherwise separated from the active pipeline, usually for purposes of abandonment, and that is usually longer than 12.2 meters in length. Pipeline sections may be branched.

## 40 CFR Ch. I (7-1-02 Edition)

#### § 761.243 Standard wipe sample method and size.

(a) Collect a surface sample from a natural gas pipe segment or pipeline section using a standard wipe test as defined in § 761.123. Detailed guidance for the entire wipe sampling process appears in the document entitled "Wipe Sampling and Double Wash/Rinse Cleanup as Recommended by the Environmental Protection Agency PCB Spill Cleanup Policy," dated June 23, 1987 and revised on April 18, 1991. This document is available from the TSCA Assistance Information Service, Environmental Protection Agency, 1200 Pennsylvania Ave., NW., Washington, DC 20460.

(b) Collect a surface sample from a minimum surface area of 100 cm<sup>2</sup> at each sampling site selected. The EPA Regional Administrator may approve, in writing, requests to collect a sample from smaller surface areas, when <100 cm<sup>2</sup> of surface eligible for sampling is present; e.g., when sampling a small diameter pipe, a small valve, or a small regulator. When smaller surfaces are sampled, convert the measurement to the equivalent measurement for 100 cm<sup>2</sup> for purposes of comparison to standards based on 100 cm<sup>2</sup>.

#### § 761.247 Sample site selection for pipe segment removal.

(a) *General.* (1) Select the pipe segments to be sampled by following the directions in paragraph (b) of this section.

(2) Locate the proper position along the length of the pipe segment that you have selected for sampling, by following the directions in paragraph (c) of this section.

(3) Select the proper sampling position around the circumference of the pipe segment that you have selected for sampling, by following the directions in paragraph (d) of this section.

(4) Prior to removing pipe from the ground or lifting the pipe from its location during former operations, mark the top side of the pipe.

(5) Do not sample if there are free-flowing liquids in the pipe segment. Free-flowing liquids must be removed prior to sampling.

(b) *Selecting pipe segments to sample.* Select the pipe segment(s) that you