

cable systems and wireless cable systems may change back and forth between automatic and manual operation.

[59 FR 67092, Dec. 28, 1994, as amended at 60 FR 56000, Nov. 6, 1995; 63 FR 29664, June 1, 1998; 65 FR 7639, Feb. 15, 2000; 67 FR 18510, Apr. 16, 2002]

§ 11.52 EAS code and Attention Signal Monitoring requirements.

(a) Before January 1, 1998, broadcast stations must be capable to receiving the Attention Signal required by § 11.32(a)(9) and emergency messages of other broadcast stations during their hours of operation. Effective January 1, 1997, all broadcast stations must install and operate during their hours of operation, equipment capable of receiving and decoding, either automatically or manually, the EAS header codes, emergency messages and EOM code. The effective dates for cable and wireless cable systems to install and operate EAS equipment are set forth in § 11.11.

NOTE TO PARAGRAPH (a): After January 1, 1998, the two-tone Attention Signal will not be used to actuate two-tone decoders but will be used as an aural alert signal.

(b) If manual interrupt is used as authorized in § 11.51(j)(2), decoders must be located so that operators at their normal duty stations at broadcast stations and cable systems and wireless cable systems can be alerted immediately when EAS messages are received.

(c) Broadcast stations and cable systems and wireless cable systems that are co-owned and co-located with a combined studio or control facility (such as an AM and FM licensed to the same entity and at the same location or a cable headend serving more than one system) may comply with the EAS monitoring requirements contained in this section for the combined station or system with one EAS Decoder. The requirements of § 11.33 must be met by the combined facility.

(d) Broadcast stations and cable systems and wireless cable systems must monitor two EAS sources. The monitoring assignments of each broadcast station and cable system and wireless cable system are specified in the State EAS Plan and FCC Mapbook. They are

developed in accordance with FCC monitoring priorities.

(1) If the required EAS sources cannot be received, alternate arrangements or a waiver may be obtained by written request to the FCC's EAS office. In an emergency, a waiver may be issued over the telephone with a follow up letter to confirm temporary or permanent reassignment.

(2) Broadcast station and cable system and wireless cable system management shall determine which header codes will automatically interrupt their programming for State and Local Area emergency situations affecting their audiences.

(e) Broadcast stations and cable systems and wireless cable systems are required to interrupt normal programming either automatically or manually when they receive an EAS message in which the header code contains the Event codes for Emergency Action Notification (EAN), Emergency Action Termination (EAT), and Required Monthly Test (RMT) for their State or State/county location.

(1) *Automatic* interrupt of programming is required when facilities are unattended. Automatic operation must provide a permanent record of the EAS message that contains at a minimum the following information: Originator, Event, Location and valid time period of the message.

(2) *Manual* interrupt of programming and transmission of EAS messages may be used. EAS messages with the EAN Event code must be transmitted immediately and Monthly EAS test messages within 60 minutes. All actions must be logged and recorded. Decoders must be programmed for the EAN and EAT Event header codes for National level emergencies and the RMT and RWT Event header codes for required monthly and weekly tests, with the appropriate accompanying State and State/county location codes.

[59 FR 67092, Dec. 28, 1994, as amended at 60 FR 56000, Nov. 6, 1995; 63 FR 29665, June 1, 1998; 67 FR 18510, Apr. 16, 2002]

§ 11.53 Dissemination of Emergency Action Notification.

Initiation of the EAN by any one of the following sources is sufficient to begin the emergency actions in § 11.54.