

§ 2.202

be preceded by the necessary bandwidth of the emission as indicated in § 2.202(b)(1).

[49 FR 48697, Dec. 14, 1984]

§ 2.202 Bandwidths.

(a) Occupied bandwidth. The frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission. In some cases, for example multi-channel frequency-division systems, the percentage of 0.5 percent may lead to certain difficulties in the practical application of the definitions of occupied and necessary bandwidth; in such cases a different percentage may prove useful.

(b) Necessary bandwidth. For a given class of emission, the minimum value of the occupied bandwidth sufficient to ensure the transmission of information at the rate and with the quality required for the system employed, under specified conditions. Emissions useful for the good functioning of the receiving equipment as, for example, the emission corresponding to the carrier of reduced carrier systems, shall be included in the necessary bandwidth.

(1) The necessary bandwidth shall be expressed by three numerals and one letter. The letter occupies the position of the decimal point and represents the unit of bandwidth. The first character shall be neither zero nor K, M or G.

(2) Necessary bandwidths:

- between 0.001 and 999 Hz shall be expressed in Hz (letter H);
between 1.00 and 999 kHz shall be expressed in kHz (letter K);
between 1.00 and 999 MHz shall be expressed in MHz (letter M);
between 1.00 and 999 GHz shall be expressed in GHz (letter G).

(3) Examples:

Table with 2 columns of frequency ranges and their corresponding alphanumeric designations (e.g., 0.002 Hz—H002, 180.5 kHz—181K).

(c) The necessary bandwidth may be determined by one of the following methods:

(1) Use of the formulas included in the table, in paragraph (g) of this section, which also gives examples of necessary bandwidths and designation of corresponding emissions;

(2) For frequency modulated radio systems which have a substantially linear relationship between the value of input voltage to the modulator and the resulting frequency deviation of the carrier and which carry either single sideband suppressed carrier frequency division multiplex speech channels or television, computation in accordance with provisions of paragraph (f) of this section and formulas and methods indicated in the table, in paragraph (g) of this section;

(3) Computation in accordance with Recommendations of the International Radio Consultative Committee (C.C.I.R.);

(4) Measurement in cases not covered by paragraph (c) (1), (2), or (3) of this section.

(d) The value so determined should be used when the full designation of an emission is required. However, the necessary bandwidth so determined is not the only characteristic of an emission to be considered in evaluating the interference that may be caused by that emission.

(e) In the formulation of the table in paragraph (g) of this section, the following terms are employed:

- Bn = Necessary bandwidth in hertz
B = Modulation rate in bauds
N = Maximum possible number of black plus white elements to be transmitted per second, in facsimile
M = Maximum modulation frequency in hertz
C = Sub-carrier frequency in hertz
D = Peak frequency deviation, i.e., half the difference between the maximum and minimum values of the instantaneous frequency. The instantaneous frequency in hertz is the time rate of change in phase in radians divided by 2
t = Pulse duration in seconds at half-amplitude
tr = Pulse rise time in seconds between 10% and 90% of maximum amplitude
K = An overall numerical factor which varies according to the emission and which depends upon the allowable signal distortion.

Federal Communications Commission

§ 2.202

$N_c$  = Number of baseband telephone channels in radio systems employing multichannel multiplexing

$P$  = Continuity pilot sub-carrier frequency (Hz) (continuous signal utilized to verify performance of frequency-division multiplex systems).

(f) Determination of values of  $D$  and  $B_n$  for systems specified in paragraph (c)(2) of this section:

(1) Determination of  $D$  in systems for multichannel telephony:

(i) The rms value of the per-channel deviation for the system shall be specified. (In the case of systems employing preemphasis or phase modulation, this value of per-channel deviation shall be specified at the characteristic baseband frequency.)

(ii) The value of  $D$  is then calculated by multiplying the rms value of the per-channel deviation by the appropriate factors, as follows:

Number of message circuits	Multiplying factors	Limits of X ( $P_{avg}$ (dBmO))
More than 3, but less than 12 .....	$4.47 \times$ [a factor specified by the equipment manufacturer or station licensee, subject to Commission approval].	
At least 12, but less than 60 .....	$\frac{3.76 \text{ antilog}(X+2 \log_{10} N_c)}{20}$	X: -2 to +2.6.
At least 60, but less than 240 .....	$\frac{3.76 \text{ antilog}(X+4 \log_{10} N_c)}{20}$	X: -5.6 to -1.0.
240 or more .....	$\frac{3.76 \text{ antilog}(X+10 \log_{10} N_c)}{20}$	X: -19.6 to -15.0.

Where X represents the average power in a message circuit in dBmO;  $N_c$  is the number of circuits in the multiplexed message load; 3.76 corresponds to a peak load factor of 11.5 dB.

(2) The necessary bandwidth ( $B_n$ ) normally is considered to be numerically equal to:

(i)  $2M+2DK$ , for systems having no continuity pilot subcarrier or having a continuity pilot subcarrier whose frequency is not the highest modulating the main carrier;

(ii)  $2P+2DK$ , for systems having a continuity pilot subcarrier whose frequency exceeds that of any other signal modulating the main carrier, unless the conditions set forth in paragraph (f)(3) of this section are met.

(3) As an exception to paragraph (f)(2)(ii) of this section, the necessary bandwidth ( $B_n$ ) for such systems is nu-

merically equal to  $2P$  or  $2M+2DK$ , whichever is greater, provided the following conditions are met:

(i) The modulation index of the main carrier due to the continuity pilot subcarrier does not exceed 0.25, and

(ii) In a radio system of multichannel telephony, the rms frequency deviation of the main carrier due to the continuity pilot subcarrier does not exceed 70 percent of the rms value of the per-channel deviation, or, in a radio system for television, the rms deviation of the main carrier due to the pilot does not exceed 3.55 percent of the peak deviation of the main carrier.

(g) Table of necessary bandwidths:

Description of emission	Necessary bandwidth		Designation of emission
	Formula	Sample calculation	
<b>I. NO MODULATING SIGNAL</b>			
Continuous wave emission.			NON (zero)
<b>II. AMPLITUDE MODULATION</b>			
1. Signal With Quantized or Digital Information			
Continuous wave telegraphy.	$B_n=BK$ , $K=5$ for fading circuits, $K=3$ for non-fading circuits	25 words per minute; $B=20$ , $K=5$ , Bandwidth: 100 Hz	100HA1A

§ 2.202

47 CFR Ch. I (10–1–02 Edition)

Description of emission	Necessary bandwidth		Designation of emission
	Formula	Sample calculation	
Telegraphy by on-off keying of a tone modulated carrier.	$B_n=BK+2M$ , $K=5$ for fading circuits, $K=3$ for non-fading circuits	25 words per minute; $B=20$ , $M=1000$ , $K=5$ , Bandwidth: 2100 Hz=2.1 kHz	2K10A2A
Selective calling signal, single-sideband full carrier.	$B_n=M$	Maximum code frequency is: 2110 Hz, $M=2110$ , Bandwidth: 2110 Hz=2.11 kHz	2K11H2B
Direct-printing telegraphy using a frequency shifted modulating sub-carrier single-sideband suppressed carrier.	$B_n=2M+2DK$ , $M=B+2$	$B=50$ , $D=35$ Hz (70 Hz shift), $K=1.2$ , Bandwidth: 134 Hz	134HJ2B
Telegraphy, single sideband reduced carrier.	$B_n$ =central frequency+ $M+DK$ , $M=B+2$	15 channels; highest central frequency is: 2805 Hz, $B=100$ , $D=42.5$ Hz (85 Hz shift), $K=0.7$ Bandwidth: 2.885 Hz=2.885 kHz	2K89R7B

2. Telephony (Commercial Quality)

Telephony double-sideband.	$B_n=2M$	$M=3000$ , Bandwidth=6000 Hz=6 kHz	6K00A3E
Telephony, single-sideband, full carrier.	$B_n=2M$	$M=3000$ , Bandwidth: 3000 Hz=3 kHz	3K00H3E
Telephony, single-sideband suppressed carrier.	$B_n=M$ – lowest modulation frequency	$M=3000$ , lowest modulation frequency is 3000 Hz, 2700 Hz Bandwidth: 2700Hz=2.7 kHz	2K70J3E
Telephony with separate frequency modulated signal to control the level of demodulated speech signal, single-sideband, reduced carrier.	$B_n=M$	Maximum control frequency is 2990 Hz, $M=2990$ , Bandwidth: 2990 Hz=2.99 kHz	2K99R3E
Telephony with privacy, single-sideband, suppressed carrier (two or more channels).	$B_n=N_c$ , $M$ – lowest modulation frequency in the lowest channel	$N_c=2$ , $M=3000$ lowest modulation frequency is 250 Hz, Bandwidth: 5750 Hz=5.75 kHz	5K75J8E
Telephony, independent sideband (two or more channels).	$B_n$ =sum of $M$ for each sideband	2 channels, $M=3000$ , Bandwidth: 6000 Hz=6 kHz	6K00B8E

3. Sound Broadcasting

Sound broadcasting, double-sideband.	$B_n=2M$ , $M$ may vary between 4000 and 10000 depending on the quality desired	Speech and music, $M=4000$ , Bandwidth: 8000 Hz= 8 kHz	8K00A3E
Sound broadcasting, single-sideband reduced carrier (single channel).	$B_n=M$ , $M$ may vary between 4000 and 10000 depending on the quality desired	Speech and music, $M=4000$ , Bandwidth: 4000 Hz= 4 kHz	4K00R3E
Sound broadcasting, single-sideband, suppressed carrier.	$B_n=M$ – lowest modulation frequency	Speech and music, $M=4500$ , lowest modulation frequency=50 Hz, Bandwidth: 4450 Hz=4.45 kHz	4K45J3E

4. Television

Television, vision and sound.	Refer to CCIR documents for the bandwidths of the commonly used television systems	Number of lines=525; Nominal video bandwidth: 4.2 MHz, Sound carrier relative to video carrier=4.5 MHz	5M75C3F
		Total vision bandwidth: 5.75 MHz; FM aural bandwidth including guardbands: 250,000 Hz	250KF3E
		Total bandwidth: 6 MHz	6M25C3F

Description of emission	Necessary bandwidth		Designation of emission
	Formula	Sample calculation	
5. Facsimile			
Analogue facsimile by sub-carrier frequency modulation of a single-sideband emission with reduced carrier.	$B_n=C-N+2+DK$ , $K=1.1$ (typically)	$N=1100$ , corresponding to an index of cooperation of 352 and a cyler rotation speed of 60 rpm. Index of cooperation is the product of the drum diameter and number of lines per unit length $C=1900$ , $D=400$ Hz, Bandwidth= $2.890$ Hz= $2.89$ kHz	2K89R3C
Analogue facsimile; frequency modulation of an audio frequency sub-carrier which modulates the main carrier, single-sideband suppressed carrier.	$B_n=2M+2DK$ , $M=N/2$ , $K=1.1$ (typically)	$N=1100$ , $D=400$ Hz, Bandwidth: $1980$ Hz= $1.98$ kHz	1K98J3C
6. Composite Emissions			
Double-sideband, television relay.	$B_n=2C+2M+2D$	Video limited to 5 MHz, audio on 6.5 MHz frequency modulated subcarrier deviation=50 kHz: $C=6.5 \times 10^6$ $D=50 \times 10^3$ Hz, $M=15,000$ , Bandwidth: $13.13 \times 10^6$ Hz= $13.13$ MHz	13M2A8W
Double-sideband radio relay system.	$B_n=2M$	10 voice channels occupying baseband between 1 kHz and 164 kHz; $M=164,000$ bandwidth= $328,000$ Hz= $328$ kHz	328KA8E
Double-sideband emission of VOR with voice (VOR=VHF omnidirectional radio range).	$B_n=2C_{max}+2M+2DK$ , $K=1$ (typically)	The main carrier is modulated by: —a 30 Hz sub-carrier—a carrier resulting from a 9960 Hz tone frequency modulated by a 30 Hz tone—a telephone channel—a 1020 Hz keyed tone for continual Morse identification. $C_{max}=9960$ , $M=30$ , $D=480$ Hz, Bandwidth: $20,940$ Hz= $20.94$ kHz	20K9A9W
Independent sidebands; several telegraph channels together with several telephone channels.	$B_n$ =sum of M for each sideband	Normally composite systems are operated in accordance with standardized channel arrangements, (e.g. CCIR Rec. 348-2) 3 telephone channels and 15 telegraphy channels require the bandwidth $12,000$ Hz= $12$ kHz	12K0B9W
<b>III-A. FREQUENCY MODULATION</b>			
1. Signal With Quantized or Digital Information			
Telegraphy without error-correction (single channel).	$B_n=2M+2DK$ , $M=B+2$ , $K=1.2$ (typically)	$B=100$ , $D=85$ Hz (170 Hz shift), Bandwidth: 304 Hz	304HF1B
Four-frequency duplex telegraphy.	$B_n=2M+2DK$ , $B$ =Modulation rate in bands of the faster channel. If the channels are synchronized: $M=B+2$ , otherwise $M=2B$ , $K=1.1$ (typically)	Spacing between adjacent frequencies=400 Hz; Synchronized channels; $B=100$ , $M=50$ , $D=600$ Hz, Bandwidth: $1420$ Hz= $1.42$ kHz	1K42F7B
2. Telephony (Commercial Quality)			
Commercial telephony ...	$B_n=2M+2DK$ , $K=1$ (typically, but under conditions a higher value may be necessary)	For an average case of commercial telephony, $M=3,000$ , Bandwidth: $16,000$ Hz= $16$ kHz	16K0F3E
3. Sound Broadcasting			
Sound broadcasting .....	$B_n=2M+2DK$ , $K=1$ (typically)	Monaural, $D=75,000$ Hz, $M=15,000$ , Bandwidth: $18,000$ Hz= $180$ kHz	180KF3E

§ 2.202

47 CFR Ch. I (10–1–02 Edition)

Description of emission	Necessary bandwidth			Designation of emission	
	Formula		Sample calculation		
4. Facsimile					
Facsimile by direct frequency modulation of the carrier; black and white.	$B_n=2M+2DK$ , (typically)	$M=N+2$	$K=1.1$	$N=1100$ elements/sec; $D=400$ Hz, Bandwidth: 1980 Hz=1.98 kHz	1K98F1C
Analogue facsimile .....	$B_n=2M+2DK$ , (typically)	$M=N+2$	$K=1.1$	$N=1100$ elements/sec; $D=400$ Hz, Bandwidth: 1980 Hz=1.98 kHz	1K98F3C
5. Composite Emissions (See Table III–B)					
Radio-relay system, frequency division multiplex.	$B_n=2P+2DK$ , $K=1$			Microwave radio relay system specifications: 60 telephone channels occupying baseband between 60 and 300 kHz; rms per-channel deviation 200 kHz; pilot at 331 kHz produces 200 kHz rms deviation of main carrier. Computation of $B_n$ : $D=(200 \times 10^3 \times 3.76 \times 1.19)$ , $\text{Hz}=0.895 \times 10^6$ , $P=0.331 \times 10^6$ Hz; Bandwidth: $2.452 \times 10^6$ Hz	2M45F8E
Radio-relay system frequency division multiple.	$B_n=2M+2DK$ , $K=1$			Microwave radio relay systems specifications: 1200 telephone channels occupying baseband between 60 and 5564 kHz; rms per channel deviation 200 kHz; continuity pilot at 6199 kHz produces 140 kHz rms deviation of main carrier. Computation of $B_n$ : $D=(20^0 \times 10^3 \times 3.76 \times 3.63)=2.73 \times 10^6$ ; $M=5.64 \times 10^6$ Hz; $P=6.2 \times 10^6$ Hz; $(2M+2DK < 2P)$ ; Bandwidth $16.59 \times 10^6$ Hz	16M6F8E
Radio-relay system, frequency division multiplex.	$B_n=2P$			Microwave radio relay system specifications: Multiplex 600 telephone channels occupying baseband between 60 and 2540 kHz; continuity pilot at 8500 kHz produces 140 kHz rms deviation of main carrier. Computation of $B_n$ : $D=(200 \times 10^3 \times 3.76 \times 2.565)=1.93 \times 10^6$ Hz; $M=2.54 \times 10^6$ Hz; $2DK \leq 2P$ Bandwidth: $17 \times 10^6$ Hz	17M0F8E
Unmodulated pulse emission.	$B_n=2K+t$ , $K$ depends upon the ratio of pulse rise time. Its value usually falls between 1 and 10 and in many cases it does not need to exceed 6			Primary Radar Range resolution: 150 m, $K=1.5$ (triangular pulse where $t_r=t_f$ , only components down to 27 dB from the strongest are considered) Then $t_r=2 \times$ range resolution $\div$ velocity of light $=2 \times 150 \div 3 \times 10^8 = 1 \times 10^{-6}$ seconds, Bandwidth: $3 \times 10^6$ Hz=3 MHz	3M00P0N
6. Composite Emissions					
Radio-relay system .....	$B_n=2K+t$ , $K=1.6$			Pulse position modulated by 36 voice channel baseband; pulse width at half amplitude=0.4 us, Bandwidth: $8 \times 10^6$ Hz=8 MHz (Bandwidth independent of the number of voice channels)	8M00M7E

[28 FR 12465, Nov. 22, 1963, as amended at 37 FR 8883, May 2, 1972; 37 FR 9996, May 18, 1972; 48 FR 16492, Apr. 18, 1983; 49 FR 48698, Dec. 14, 1984]