

## § 173.224

## 49 CFR Ch. I (10–1–02 Edition)

must not substantially impair the protective properties of the cushioning material.

(3) Receptacles for gases, their contents and filling densities must conform to the applicable requirements of this subchapter, unless otherwise approved by the Associate Administrator.

(c) The total net quantity of hazardous materials contained in one item of equipment, machinery or apparatus must not exceed the following:

- (1) 1 kg (2.2 pounds) in the case of solids;
- (2) 0.5 L (0.3 gallons) in the case of liquids;
- (3) 0.5 kg (1.1 pounds) in the case of Division 2.2 gases; and

(4) A total quantity of not more than the aggregate of that permitted in paragraphs (c)(1) through (c)(3) of this section, for each category of material in the package, when a package contains hazardous materials in two or more of the categories in paragraphs (c)(1) through (c)(3) of this section.

(d) When a package contains hazardous materials in two or more of the categories listed in paragraphs (c)(1) through (c)(3) of this section, the total quantity required by §172.202(c) of this subchapter to be entered on the shipping paper, must be the aggregate quantity of all hazardous materials, expressed as net mass.

[64 FR 10779, Mar. 5, 1999, as amended at 64 FR 44428, Aug. 16, 1999; 66 FR 45379, Aug. 28, 2001]

### § 173.224 Packaging and control and emergency temperatures for self-reactive materials.

(a) *General.* When the §172.101 table of this subchapter specifies that a Division 4.1 material be packaged in accordance with this section, only packagings which conform to the provisions of this section may be used. Each packaging must conform to the general packaging requirements of subpart B of this part and the applicable requirements of part 178 of this subchapter. Non-bulk packagings must meet Packing Group II performance levels. To avoid unnecessary confinement, metallic non-bulk packagings meeting Packing Group I are not authorized. Self-reactive materials which require temperature control are subject to the pro-

visions of §173.21(f). Packagings required to bear a Class 1 subsidiary label must conform to §§173.60 through 173.62.

(b) *Self-Reactive Materials Table.* The Self-Reactive Materials Table specifies, by technical name, those self-reactive materials that are authorized for transportation and not subject to the approval provisions of §173.124(a)(2)(iii). A self-reactive material identified by technical name in the following table is authorized for transportation only if it conforms to all applicable provisions of the table. The column headings of the Self-Reactive Materials Table are as follows:

(1) *Technical name.* Column 1 specifies the technical name.

(2) *ID number.* Column 2 specifies the identification number which is used to identify the proper shipping name in the §172.101 table.

(3) *Concentration of self-reactive material.* Column 3 specifies the concentration (percent) limitations, if any, in mixtures or solutions for the self-reactive material. Limitations are given as minimums, maximums, or a range, as appropriate. A range includes the lower and upper limits (i.e., “53–100” means from, and including, 53 percent to, and including 100 percent).

(4) *Packing method.* Column 4 specifies the highest packing method which is authorized for the self-reactive material. A packing method corresponding to a smaller package size may be used, but a packing method corresponding to a larger package size may not be used. The Table of Packing Methods in §173.225(d) defines the packing methods. Bulk packagings are authorized as specified in §173.225(d) for Type F self-reactive substances. Additional bulk packagings are authorized if approved by the Associate Administrator.

(5) *Control temperature.* Column 5 specifies the control temperature in °C. Temperatures are specified only when temperature controls are required (see §173.21(f)).

(6) *Emergency temperature.* Column 6 specifies the emergency temperature in °C. Temperatures are specified only when temperature controls are required (see §173.21(f)).

(7) Notes. Column 7 specifies other applicable provisions, as set forth in notes following the table.

SELF-REACTIVE MATERIALS TABLE

Self-reactive substance (1)	Identification No. (2)	Concentration— (%) (3)	Packing method (4)	Control temperature— (°C) (5)	Emergency temperature (6)	Notes (7)
Azodicarbonamide formulation type B, temperature controlled.	3232	<100 .....	OP5	.....	.....	1
Azodicarbonamide formulation type C .....	3224	<100 .....	OP6	.....	.....	.....
Azodicarbonamide formulation type C, temperature controlled.	3234	<100 .....	OP6	.....	.....	1
Azodicarbonamide formulation type D .....	3226	<100 .....	OP7	.....	.....	.....
Azodicarbonamide formulation type D, temperature controlled.	3236	<100 .....	OP7	.....	.....	1
2,2'-Azodi(2,4-dimethyl-4-methoxyvaleronitrile).	3236	100 .....	OP7	-5 .....	+5 .....	.....
2,2'-Azodi(2,4-dimethylvaleronitrile) .....	3236	100 .....	OP7	+10 .....	+15 .....	.....
2,2'-Azodi(ethyl 2-methylpropionate) .....	3235	100 .....	OP7	+20 .....	+25 .....	.....
1,1-Azodi(hexahydrobenzotriazole) .....	3226	100 .....	OP7	.....	.....	.....
2,2'-Azodi(isobutyronitrile) .....	3234	100 .....	OP6	+40 .....	+45 .....	.....
2,2'-Azodi(isobutyronitrile) as a water based paste.	3224	.....	.....	≤50% .....	OP6 .....	.....
2,2-Azodi(2-methylbutyronitrile) .....	3236	100 .....	OP7	+35 .....	+40 .....	.....
Benzene-1,3-disulphohydrazide, as a paste.	3226	52 .....	OP7	.....	.....	.....
Benzene sulphohydrazide .....	3226	100 .....	OP7	.....	.....	.....
4-(Benzyl(ethyl)amino)-3-ethoxybenzenediazonium zinc chloride.	3226	100 .....	OP7	.....	.....	.....
4-(Benzyl(methyl)amino)-3-ethoxybenzenediazonium zinc chloride.	3236	100 .....	OP7	+40 .....	+45 .....	.....
3-Chloro-4-diethylaminobenzenediazonium zinc chloride.	3226	100 .....	OP7	.....	.....	.....
2-Diazo-1-Naphthol-4-sulphochloride .....	3222	100 .....	OP5	.....	.....	.....
2-Diazo-1-Naphthol-5-sulphochloride .....	3222	100 .....	OP5	.....	.....	.....
2,5-Diethoxy-4-morpholinobenzenediazonium zinc chloride.	3236	67-100 .....	OP7	+35 .....	+40 .....	.....
2,5-Diethoxy-4-morpholinobenzenediazonium zinc chloride.	3236	66 .....	OP7	+40 .....	+45 .....	.....
2,5-Diethoxy-4-morpholinobenzenediazonium tetrafluoroborate.	3236	100 .....	OP7	+30 .....	+35 .....	.....
2,5-Diethoxy-4-(phenylsulphonyl)benzenediazonium zinc chloride.	3236	67 .....	OP7	+40 .....	+45 .....	.....
Diethylene glycol bis(allyl carbonate) + Diisopropylperoxydicarbonate.	3237	≥88+≤12 .....	OP8	-10 .....	0 .....	.....
2,5-Dimethoxy-4-(4-methylphenylsulphonyl)benzenediazonium zinc chloride.	3236	79 .....	OP7	+40 .....	+45 .....	.....
4-Dimethylamino-6-(2-dimethylaminoethoxy)toluene-2-diazonium zinc chloride.	3236	100 .....	OP7	+40 .....	+45 .....	.....
N,N'-Dinitroso-N,N'-dimethyl-terephthalamide, as a paste.	3224	72 .....	OP6	.....	.....	.....
N,N'-Dinitrosopentamethylenetetramine ..	3224	82 .....	OP6	.....	.....	2
Diphenyloxide-4,4'-disulphohydrazide .....	3226	100 .....	OP7	.....	.....	.....
4-Dipropylaminobenzenediazonium zinc chloride.	3226	100 .....	OP7	.....	.....	.....
2-(N,N-Ethoxycarbonylphenylamino)-3-methoxy-4-(N-methyl-N-cyclohexylamino)benzenediazonium zinc chloride.	3236	63-92 .....	OP7	+40 .....	+45 .....	.....
2-(N,N-Ethoxycarbonylphenylamino)-3-methoxy-4-(N-methyl-N-cyclohexylamino)benzenediazonium zinc chloride.	3236	62 .....	OP7	+35 .....	+40 .....	.....

SELF-REACTIVE MATERIALS TABLE—Continued

Self-reactive substance (1)	Identification No. (2)	Concentration— (%) (3)	Packing method (4)	Control temperature— (°C) (5)	Emergency temperature (6)	Notes (7)
N-Formyl-2-(nitromethylene)-1,3-perhydrothiazine.	3236	100 .....	OP7	+45 .....	+50 .....	.....
2-(2-Hydroxyethoxy)-1-(pyrrolidin-1-yl)benzene-4-diazonium zinc chloride.	3236	100 .....	OP7	+45 .....	+50 .....	.....
3-(2-Hydroxyethoxy)-4-(pyrrolidin-1-yl)benzenediazonium zinc chloride.	3236	100 .....	OP7	+40 .....	+45 .....	.....
2-(N,N-Methylaminoethylcarbonyl)-4-(3,4-dimethyl-phenylsulphonyl)benzene diazonium zinc chloride.	3236	96 .....	OP7	+45 .....	+50 .....	.....
4-Methylbenzenesulphonylhydrazide .....	3226	100 .....	OP7	.....	.....	.....
3-Methyl-4-(pyrrolidin-1-yl)benzenediazonium tetrafluoroborate.	3234	95 .....	OP6	+45 .....	+50 .....	.....
4-Nitrosophenol .....	3236	100 .....	OP7	+35 .....	+40 .....	.....
Self-reactive liquid, sample .....	3223	.....	OP2	.....	.....	3
Self-reactive liquid, sample, temperature control.	3233	.....	OP2	.....	.....	3
Self-reactive solid, sample .....	3224	.....	OP2	.....	.....	3
Self-reactive solid, sample, temperature control.	3234	.....	OP2	.....	.....	3
Sodium 2-diazo-1-naphthol-4-sulphonate	3226	100 .....	OP7	.....	.....	.....
Sodium 2-diazo-1-naphthol-5-sulphonate	3226	100 .....	OP7	.....	.....	.....
Tetramine palladium (II) nitrate .....	3234	100 .....	OP6	+30 .....	+35 .....	.....

NOTES:

1. The emergency and control temperatures must be determined in accordance with § 173.21(f).
2. With a compatible diluent having a boiling point of not less than 150 °C.
3. Samples may only be offered for transportation under the provisions of paragraph(c)(3) of this section.

(c) *New self-reactive materials, formulations and samples.* (1) Except as provided for samples in paragraph (c)(3) of this section, no person may offer, accept for transportation, or transport a self-reactive material which is not identified by technical name in the Self-Reactive Materials Table of this section, or a formulation of one or more self-reactive materials which are identified by technical name in the table, unless the self-reactive material is assigned a generic type and shipping description and is approved by the Associate Administrator under the provisions of § 173.124(a)(2)(iii).

(2) Except as provided by an approval issued under § 173.124(a)(2)(iii), intermediate bulk and bulk packagings are not authorized.

(3) *Samples.* Samples of new self-reactive materials or new formulations of self-reactive materials identified in the Self-Reactive Materials Table in paragraph (b) of this section, for which complete test data are not available, and which are to be transported for further testing or product evaluation, may be assigned an appropriate shipping description for Self-reactive mate-

rials Type C, packaged and offered for transportation under the following conditions:

(i) Data available to the person offering the material for transportation must indicate that the sample would pose a level of hazard no greater than that of a self-reactive material Type B and that the control temperature, if any, is sufficiently low to prevent any dangerous decomposition and sufficiently high to prevent any dangerous phase separation;

(ii) The sample must be packaged in accordance with packing method OP2;

(iii) Packages of the self-reactive material may be offered for transportation and transported in a quantity not to exceed 10 kg (22 pounds) per transport vehicle; and

(iv) One of the following shipping descriptions must be assigned:

(A) Self-reactive, liquid, type C, 4.1, UN3223.

(B) Self-reactive, solid, type C, 4.1, UN3224.

(C) Self-reactive, liquid, type C, temperature controlled, 4.1, UN3233.

(D) Self-reactive, solid, type C, temperature controlled, 4.1, UN3234.

[Amdt. 173-241, 59 FR 67511, Dec. 29, 1994, as amended by Amdt. 173-242, 60 FR 26806, May 18, 1995; Amdt. 173-246, 60 FR 49110, Sept. 21, 1995; Amdt. 173-256, 61 FR 51338, Oct. 1, 1996; Amdt. 173-261, 62 FR 24734, 24735, May 6, 1997; 62 FR 45702, Aug. 28, 1997; 64 FR 10779, Mar. 5, 1999; 65 FR 58630, Sept. 29, 2000; 66 FR 33431, June 21, 2001; 66 FR 45379, Aug. 28, 2001]

**§ 173.225 Packaging requirements and other provisions for organic peroxides.**

(a) *General.* When the §172.101 table specifies that an organic peroxide be packaged under this section, the organic peroxide must be packaged and offered for transportation in accordance with the provisions of this section. Each packaging must conform to the general requirements of subpart B of part 173 and to the applicable requirements of part 178 of this subchapter. Non-bulk packagings must meet Packing Group II performance levels. To avoid unnecessary confinement, metallic non-bulk packagings meeting Packing Group I are not authorized. No used material, other than production residues or regrind from the same production process, may be used in plastic packagings. Organic peroxides which require temperature control are subject to the provisions of §173.21(f).

(b) *Organic peroxides table.* The following Organic Peroxides Table specifies, by technical name, those organic peroxides that are authorized for transportation and not subject to the approval provisions of §173.128 of this part. An organic peroxide identified by technical name in the following table is authorized for transportation only if it conforms to all applicable provisions of the table. For an organic peroxide not identified in the table by technical name or a formulation of identified organic peroxides, the provisions of paragraph (c) of §173.128 apply. The column headings of the Organic Peroxides Table are as follows:

(1) *Technical name.* The first column specifies the technical name.

(2) *ID number.* The second column specifies the identification (ID) number which is used to identify the proper shipping name in the §172.101 table. The word "EXEMPT" appearing in the

column denotes that the material is not regulated as an organic peroxide.

(3) *Concentration of organic peroxide.* The third column specifies concentration (mass percent) limitations, if any, in mixtures or solutions for the organic peroxide. Limitations are given as minimums, maximums, or a range, as appropriate. A range includes the lower and upper limits (i.e., "53-100" means from, and including, 53 percent to, and including 100 percent). See introductory paragraph of §172.203(k) of this subchapter for additional description requirements for an organic peroxide that may qualify for more than one generic listing, depending on its concentration.

(4) *Concentration of diluents.* The fourth column specifies the type and concentration (mass percent) of diluent or inert solid, when required. Other types and concentrations of diluents may be authorized if approved by the Associate Administrator.

(i) The required mass percent of "Diluent type A" is specified in column 4a. A diluent type A is an organic liquid that does not detrimentally affect the thermal stability or increase the hazard of the organic peroxide and with a boiling point not less than 150 °C at atmospheric pressure. Type A diluents may be used for desensitizing all organic peroxides.

(ii) The required mass percent of "Diluent type B" is specified in column 4b. A diluent type B is an organic liquid which is compatible with the organic peroxide and which has a boiling point, at atmospheric pressure, of less than 150 °C (302 °F) but at least 60 °C (140 °F), and a flash point greater than 5 °C (41 °F). Type B diluents may be used for desensitizing all organic peroxides provided that the boiling point is at least 60 °C (140 °F) above the SADT of the peroxide in a 50 kg (110 lbs) package. A type A diluent may be used to replace a type B diluent in equal concentration.

(iii) The required mass percent of "Inert solid" is specified in column 4c. An inert solid is a solid that does not detrimentally affect the thermal stability or increase the hazard of the organic peroxide.