

§ 200.943

plant annually. Of these, two shall be interim samples (taken every six months) and one an annual sample. In addition, two samples of each certified quality shall be taken annually from sources other than the manufacturer, *i.e.*, brought in the market place from distributors or stores, not from the factory. The administrator shall select samples for testing, and testing shall be conducted, in accordance with the applicable standards in a laboratory accredited by the National Voluntary Laboratory Accreditation Program (NVLAP) of the National Bureau of Standards, U.S. Department of Commerce.

(2) The administrator shall visit the manufacturer's facility at least once every six months to assure that the initially accepted quality control procedures continue to be followed.

[51 FR 17928, May 16, 1986]

§ 200.943 Supplementary specific requirements under the HUD building product standards and certification program for the grademarking of lumber.

(a) *Applicable standard.* (1) In accordance with UM 38j, lumber shall be grademarked in compliance with the U.S. Department of Commerce Voluntary Product Standard PS 20-94 American Softwood Lumber Standard.

(2) This standard has been approved by the Director of the Federal Register for incorporation by reference in accordance with 5 U.S.C. 552(a) and 1 CFR part 51. It is available from the U.S. Department of Commerce, NIST, Office of Voluntary Product Standards, Gaithersburg, MD 20899.

(b) *Labeling.* Under the procedures set forth in § 200.935(d)(6) concerning labeling of a product, the administrator's validation mark and the manufacturer's certification of compliance with the applicable standard are required on the certification label issued by the administrator to the manufacturer. However, in the case of grademarking of lumber, the following information shall be included on the certification label or mark:

- (1) The registered symbol which identifies the grading agency;
- (2) Species or species combination;
- (3) Grade;

24 CFR Ch. II (4-1-03 Edition)

(4) Identification of the applicable grading rules when not indicated by the species identification or agency symbol;

(5) Mill or grader;

(6) For members which are less than 5 inches in nominal thickness, indication that the lumber was green or dry at the time of dressing;

(7) Indication that the lumber was finger jointed; and

(8) The certification mark shall be affixed to each piece of lumber.

(c) *Periodic tests and quality assurance.* Periodic tests and quality assurance inspections shall be carried out by the American Lumber Standard Committee as defined in PS 20-94.

[63 FR 5423, Feb. 2, 1998]

§ 200.944 Supplementary specific requirements under the HUD building product standards and certification program for plywood and other performance rated wood-based structural-use panels.

(a)(1) All plywood made to specifications of Voluntary Product Standard, PS 1-83, "Construction and Industrial Plywood" (published by the U.S. Department of Commerce, National Bureau of Standards (May 1984)) and grade marked as PS 1-83 shall conform to the requirements of PS 1-83, except that all veneers may be D-grade. A copy of PS 1-83 may be obtained from the U.S. Department of Commerce, National Institute for Standards and Technology, Office of Product Standards, Gaithersburg, MD 20899.

(2) All plywood panels not meeting the veneer grade requirements of PS 1-83, and all performance rated composite and nonveneer structural-use panels shall comply with the requirements described in the APA PRP-108, "Performance Standards and Policies for Structural-Use panels" (published by the American Plywood Association, June 1988). However, in ASTM D-3043-87, "Standard Methods of Testing Structural Panels in Flexure" (published by the American Society for Testing and Materials, August 28, 1987), Method B may be used in lieu of Method C for measuring the mechanical properties of the panel, provided that the test specimen has a width of at least 12 inches. The impact load shall