

CFR 745.227(b), except that the definition of lead-based paint shall not include a loading (area concentration) or mass concentration greater than that in the definition at §35.110 of this part.

(b) *Risk assessments.* (1) Risk assessments shall be performed in accordance with methods and standards established either by a State or Indian tribe under a program authorized by EPA, or by EPA at 40 CFR 745.227(d), and paragraph (b)(2) of this section.

(2) Risk assessors shall use levels defining dust-lead hazards and soil-lead hazards that are no greater than those promulgated by EPA pursuant to section 403 of the Toxic Substances Control Act (15 U.S.C. 2683), or, if such levels are not in effect, the following for dust or soil:

(i) *Dust.* A dust-lead hazard shall be a dust-lead level equal to or greater than the applicable loading (area concentration), based on wipe samples, in the following table:

INTERIM DUST LEAD STANDARDS

Evaluation method	Surface	Interior window sills, µg/ft ² (mg/m ²)	Window troughs, µg/ft ² (mg/m ²)
	Floors, µg/ft ² (mg/m ²)		
Lead Hazard Screen	25 (0.27)	125 (1.4)	Not Applicable.
Risk Assessment	40 (0.43)	250 (2.7)	Not Applicable.
Reevaluation	40 (0.43)	250 (2.7)	Not Applicable.
Clearance	40 (0.43)	250 (2.7)	800 (8.6).

Note: "Floors" includes carpeted and uncarpeted interior floors.

(ii) *Soil.* (A) A soil-lead hazard for play areas frequented by children under 6 years of age shall be bare soil with lead equal to or exceeding 400 micrograms per gram.

(B) For other areas, soil-lead hazards shall be bare soil that totals more than 9 square feet (0.8 square meters) per property with lead equal to or exceeding 2,000 micrograms per gram.

(3) Lead hazard screens shall be performed in accordance with the methods and standards established either by a State or Indian tribe under a program authorized by EPA, or by EPA at 40 CFR 745.227(c), and paragraph (b)(2) of this section. If the lead hazard screen indicates the need for a follow-up risk assessment (e.g., if dust-lead measurements exceed the levels established for lead hazard screens in this section), a risk assessment shall be conducted in accordance with paragraphs (b)(1) and (b)(2) of this section. Dust, soil, and paint samples collected for the lead hazard screen may be used in the risk assessment. If the lead hazard screen does not indicate the need for a follow-up risk assessment, no further risk-assessment is required.

(c) It is strongly recommended, but not required, that lead-based paint inspectors and risk assessors provide a summary of the results suitable for

posting or distribution to occupants in compliance with §35.125.

§ 35.1325 Abatement.

Abatement shall be performed in accordance with methods and standards established either by a State or Indian tribe under a program authorized by EPA, or by EPA at 40 CFR 745.227(e), and shall be completed by achieving clearance in accordance with §35.1340. If encapsulation or enclosure is used as a method of abatement, ongoing lead-based paint maintenance activities shall be performed as required by the applicable subpart of this part in accordance with §35.1355. Abatement of an intact, factory-applied prime coating on metal surfaces is not required unless the surface is a friction surface.

§ 35.1330 Interim controls.

Interim controls of lead-based paint hazards identified in a risk assessment shall be conducted in accordance with the provisions of this section. Interim control measures include paint stabilization of deteriorated paint, treatments for friction and impact surfaces where levels of lead dust are above the levels specified in §35.1320, dust control, and lead-contaminated soil control. As provided by §35.155, interim