

Minerals Management Service, Interior

§ 250.615

shall be submitted to the District Supervisor and shall include a new schematic of the tubing subsurface equipment if any subsurface equipment has been changed.

[53 FR 10690, Apr. 1, 1988, as amended at 58 FR 49928, Sept. 24, 1993. Redesignated and amended at 63 FR 29479, 29485, May 29, 1998; 65 FR 35824, June 6, 2000; 68 FR 8435, Feb. 20, 2003]

§ 250.614 Well-control fluids, equipment, and operations.

The following requirements apply during all well-workover operations with the tree removed:

(a) Well-control fluids, equipment, and operations shall be designed, utilized, maintained, and/or tested as necessary to control the well in foreseeable conditions and circumstances, including subfreezing conditions. The well shall be continuously monitored during well-workover operations and shall not be left unattended at anytime unless the well is shut in and secured.

(b) When coming out of the hole with drill pipe or a workover string, the annulus shall be filled with well-control fluid before the change in such fluid level decreases the hydrostatic pressure 75 pounds per square inch (psi) or every five stands of drill pipe or workover string, whichever gives a lower decrease in hydrostatic pressure. The number of stands of drill pipe or workover string and drill collars that may be pulled prior to filling the hole and the equivalent well-control fluid volume shall be calculated and posted near the operator's station. A mechanical, volumetric, or electronic device for measuring the amount of well-con-

trol fluid required to fill the hold shall be utilized.

(c) The following well-control-fluid equipment shall be installed, maintained, and utilized:

(1) A fill-up line above the uppermost BOP;

(2) A well-control, fluid-volume measuring device for determining fluid volumes when filling the hole on trips; and

(3) A recording mud-pit-level indicator to determine mud-pit-volume gains and losses. This indicator shall include both a visual and an audible warning device.

§ 250.615 Blowout prevention equipment.

(a) The BOP system, system components and related well-control equipment shall be designed, used, maintained, and tested in a manner necessary to assure well control in foreseeable conditions and circumstances, including subfreezing conditions. The working pressure rating of the BOP system and system components shall exceed the expected surface pressure to which they may be subjected. If the expected surface pressure exceeds the rated working pressure of the annular preventer, the lessee shall submit with Form MMS-124, requesting approval of the well-workover operation, a well-control procedure that indicates how the annular preventer will be utilized, and the pressure limitations that will be applied during each mode of pressure control.

(b) The minimum BOP system for well-workover operations with the tree removed must meet the appropriate standards from the following table:

| When | The minimum BOP stack must include |
|---|--|
| (1) The expected pressure is less than 5,000 psi. | Three BOPs consisting of an annular, one set of pipe rams, and one set of blind or blind-shear rams. |
| (2) The expected pressure is 5,000 psi or greater or you use multiple tubing strings. | Four BOPs consisting of an annular, two sets of pipe rams, and one set of blind or blind-shear rams. |
| (3) You handle multiple tubing strings simultaneously. | Four BOPs consisting of an annular, one set of pipe rams, one set of dual pipe rams, and one set of blind or blind-shear rams. |
| (4) You use a tapered drill string | At least one set of pipe rams that are capable of sealing around each size of drill string. If the expected pressure is greater than 5,000 psi, then you must have at least two sets of pipe rams that are capable of sealing around the larger size drill string. You may substitute one set of variable bore rams for two sets of pipe rams. |
| (5) It is after February 21, 2006 | At least one set of blind-shear rams. The blind-shear rams must be capable of shearing the drill pipe or tubing in the hole. |

§ 250.616

30 CFR Ch. II (7-1-03 Edition)

(c) The BOP systems for well-workover operations with the tree removed shall be equipped with the following:

(1) A hydraulic-actuating system that provides sufficient accumulator capacity to supply 1.5 times the volume necessary to close all BOP equipment units with a minimum pressure of 200 psi above the precharge pressure without assistance from a charging system. No later than December 1, 1988, accumulator regulators supplied by rig air and without a secondary source of pneumatic supply, shall be equipped with manual overrides, or alternately, other devices provided to ensure capability of hydraulic operations if rig air is lost;

(2) A secondary power source, independent from the primary power source, with sufficient capacity to close all BOP system components and hold them closed;

(3) Locking devices for the pipe-ram preventers;

(4) At least one remote BOP-control station and one BOP-control station on the rig floor; and

(5) A choke line and a kill line each equipped with two full opening valves and a choke manifold. At least one of the valves on the choke-line shall be remotely controlled. At least one of the valves on the kill line shall be remotely controlled, except that a check valve on the kill line in lieu of the remotely controlled valve may be installed provided two readily accessible manual valves are in place and the check valve is placed between the manual valves and the pump. This equipment shall have a pressure rating at least equivalent to the ram preventers.

(d) The minimum BOP-system components for well-workover operations with the tree in place and performed through the wellhead inside of conventional tubing using small-diameter jointed pipe (usually 3/4 inch to 1 1/4 inch) as a work string, i.e., small-tubing operations, shall include the following:

- (1) Two sets of pipe rams, and
- (2) One set of blind rams.

(e) The minimum BOP-system components for well-workover operations with the tree in place and performed by manipulating spooled, nonjointed pipe

through the wellhead, i.e., coiled-tubing operations, shall include the following:

(1) One set of pipe rams hydraulically operated,

(2) One two-way slip assembly hydraulically operated,

(3) One pipe-cutter assembly hydraulically operated,

(4) One set of blind rams hydraulically operated,

(5) One pipe-stripper assembly, and

(6) One spool with side outlets.

(f) The minimum BOP-system components for well-workover operations with the tree in place and performed by moving tubing or drill pipe in or out of a well under pressure utilizing equipment specifically designed for that purpose, i.e., snubbing operations, shall include the following:

(1) One set of pipe rams hydraulically operated, and

(2) Two sets of stripper-type pipe rams hydraulically operated with spacer spool.

(g) An inside BOP or a spring-loaded, back-pressure safety valve and an essentially full-opening, work-string safety valve in the open position shall be maintained on the rig floor at all times during well-workover operations when the tree is removed or during well-workover operations with the tree installed and using small tubing as the work string. A wrench to fit the work-string safety valve shall be readily available. Proper connections shall be readily available for inserting valves in the work string. The full-opening safety valve is not required for coiled tubing or snubbing operations.

[53 FR 10690, Apr. 1, 1988, as amended at 54 FR 50616, Dec. 8, 1989; 58 FR 49928, Sept. 24, 1993. Redesignated at 63 FR 29479, May 29, 1998, as amended at 68 FR 8435, Feb. 20, 2003]

§ 250.616 Blowout preventer system testing, records, and drills.

(a) Prior to conducting high-pressure tests, all BOP system components shall be successfully tested to a low pressure of 200 to 300 psi. Ram-type BOP's, related control equipment, including the choke and kill manifolds, and safety valves shall be successfully tested to the rated working pressure of the BOP equipment or as otherwise approved by the District Supervisor. Variable bore