

## § 250.805

indicated by control circuitry actuation.

(12) Prior to the commencement of production, the lessee shall notify the District Supervisor when the lessee is ready to conduct a preproduction test and inspection of the integrated safety system. The lessee shall also notify the District Supervisor upon commencement of production in order that a complete inspection may be conducted.

(b) *Records.* The lessee shall maintain records for a period of 2 years for each subsurface and surface safety device installed. These records shall be maintained by the lessee at the lessee's field office nearest the OCS facility or other locations conveniently available to the District Supervisor. These records shall be available for review by a representative of MMS. The records shall show the present status and history of each device, including dates and details of installation, removal, inspection, testing, repairing, adjustments, and reinstallation.

[53 FR 10690, Apr. 1, 1988, as amended at 55 FR 47753, Nov. 15, 1990; 62 FR 5331, Feb. 5, 1997. Redesignated at 63 FR 29479, May 29, 1998, as amended at 65 FR 35824, June 6, 2000; 67 FR 51760, Aug. 9, 2002; 68 FR 47, Jan. 2, 2003]

### § 250.805 Safety device training.

Personnel installing, inspecting, testing, and maintaining these safety devices and personnel operating the production platforms shall be qualified in accordance with subpart O.

### § 250.806 Safety and pollution prevention equipment quality assurance requirements.

(a) *General requirements.* (1) Except as provided in paragraph (b)(1) of this section, you may install only certified safety and pollution prevention equipment (SPPE) in wells located on the OCS. SPPE includes the following:

(i) Surface safety valves (SSV) and actuators;

(ii) Underwater safety valves (USV) and actuators; and

(iii) Subsurface safety valves (SSSV) and associated safety valve locks and landing nipples.

(2) Certified SPPE is equipment the manufacturer certifies as manufactured under a quality assurance pro-

## 30 CFR Ch. II (7-1-03 Edition)

gram MMS recognizes. MMS considers all other SPPE as noncertified. MMS recognizes two quality assurance programs:

(i) ANSI/ASME SPPE-1, Quality Assurance and Certification of Safety and Pollution-Prevention Equipment Used in Offshore Oil and Gas Operations; and

(ii) API Spec Q1, Specification for Quality Programs.

(3) All SSV's and USV's must meet the technical specifications of API Spec 6A and 6AV1. All SSSVs must meet the technical specifications of API Specification 14A.

(4) For information on all standards mentioned in this section, see §250.198.

(b) *Use of noncertified SPPE.* (1) Before April 1, 1998, you may continue to use and install noncertified SPPE if it was in your inventory as of April 1, 1988, and was included in a list of noncertified SPPE submitted to MMS prior to August 29, 1988.

(2) On or after April 1, 1998:

(i) You may not install additional noncertified SPPE; and

(ii) When noncertified SPPE that is already in service requires offsite repair, remanufacturing, or hot work such as welding, you must replace it with certified SPPE.

(c) *Recognizing other quality assurance programs.* The MMS will consider recognizing other quality assurance programs covering the manufacture of SPPE. If you want MMS to evaluate other quality assurance programs, submit relevant information about the program and reasons for recognition by MMS to the Chief, Engineering and Operations Division; Minerals Management Service; Mail Stop 4700; 381 Elden Street; Herndon, Virginia 20170-4817.

[62 FR 42671, Aug. 8, 1997. Redesignated at 63 FR 29479, May 29, 1998, as amended at 63 FR 37068, July 9, 1998; 65 FR 76935, Dec. 8, 2000]

### § 250.807 Hydrogen sulfide.

Production operations in zones known to contain hydrogen sulfide (H<sub>2</sub>S) or in zones where the presence of H<sub>2</sub>S is unknown, as defined in §250.490 of this part, shall be conducted in accordance with that section and other

relevant requirements of subpart H, Production Safety Systems.

[53 FR 10690, Apr. 1, 1988. Redesignated and amended at 63 FR 29479, 29485, May 29, 1998; 68 FR 8435, Feb. 20, 2003]

### Subpart I—Platforms and Structures

#### § 250.900 General requirements.

(a) The lessee shall design, fabricate, install, use, inspect, and maintain all platforms and structures (platforms) on the Outer Continental Shelf (OCS) to assure their structural integrity for the safe conduct of drilling, workover, and production operations, considering the specific environmental conditions at the platform location.

(b) All new fixed or bottom-founded platforms (i.e., platforms or other structures, e.g., single-well caissons, artificial islands), shall be designed, fabricated, installed, inspected, and maintained in accordance with all the requirements of this section and §§ 250.901 and 250.904 through 250.914 of this subpart. Applications submitted pursuant to § 250.901 shall require the approval by the Regional Supervisor prior to platform installation.

(c) All new platforms which meet any of the conditions listed below shall be subject to the Platform Verification Program and shall be designed, fabricated, and installed in accordance with the requirements of §§ 250.901 through 250.914 of this part.

(1) Platforms installed in water depths exceeding 400 feet,

(2) Platforms having natural periods in excess of 3 seconds,

(3) Platforms installed in areas of unstable bottom conditions,

(4) Platforms having configurations and designs which have not previously been used or proven for use in the area, or

(5) Platforms installed in seismically active areas.

(d) Major modification to any platform shall be subject to the requirements of this subpart and shall require the approval of the Regional Supervisor. Major modification means any structural changes which materially alter the approved plan or causes a major deviation from approved operations.

(e)(1) Major repairs of damage to any platform shall require the prior approval of the Regional Supervisor. Major repairs of damage means corrective operations involving structural members affecting the structural integrity of a portion or all of the platform.

(2) Under emergency conditions, repairs to primary structural elements may be made to restore an existing permitted condition without prior approval. The Regional Supervisor shall be notified within 24 hours of the damage that occurred and repairs that were made. The Regional Supervisor's approval for repairs shall be obtained.

(f) The requirements for an application for approval for the reuse or conversion of the use of an existing fixed or mobile platforms shall be determined on a case-by-case basis. An application shall be submitted to the Regional Supervisor for approval and shall include location, intended use, and demonstrate the adequacy of the design and structural condition of the platform.

(g) In addition to the requirements of this subpart, platform design, fabrication, and installation shall conform to API RP 2A-WSD "Recommended Practice For Planning, Designing, And Constructing Fixed Offshore Platforms—Working Stress Design," (incorporated by reference, see § 250.198), or American Concrete Institute (ACI) 357R, "Guide for the Design and Construction of Fixed Offshore Concrete Structures," (incorporated by reference, see § 250.198), as appropriate. Alternative codes or rules may be utilized with approval of the Regional Supervisor. The requirements contained in these documents (API RP 2A-WSD and ACI 327R) are incorporated by reference in this part, see § 250.198.

[53 FR 10690, Apr. 1, 1988. Redesignated and amended at 63 FR 29479, 29485, May 29, 1998; 64 FR 9065, Feb. 24, 1999; 68 FR 19355, Apr. 21, 2003]

#### § 250.901 Application for approval.

(a) All applications under the provisions of this subpart shall be submitted to the Regional Supervisor for approval. All significant changes or modifications to approved applications