

§ 250.912

(iii) Concreting records including weight, moisture content, mix proportions, test methods and results, ambient conditions during the pour, and test equipment calibration data;

(iv) Deviations from design or fabrication specifications and repairs carried out;

(v) Towing records; and

(vi) Data on initial structural settlements.

[53 FR 10690, Apr. 1, 1988; 53 FR 26067, July 11, 1988. Redesignated and amended at 63 FR 29479, 29486, May 29, 1998; 64 FR 9065, Feb. 24, 1999]

§ 250.912 Periodic inspection and maintenance.

(a) All platforms installed in the OVS shall be inspected periodically in accordance with the provisions of section 14, Surveys of API RP 2A-WSD (incorporated by reference, see §250.198). However, use of an inspection interval which exceeds 5 years shall require prior approval by the Regional Supervisor. Proper maintenance shall be performed to assure the structural integrity of the platform as a workbase for oil and gas operations.

(b) A report shall be submitted annually on November 1 to the Regional Supervisor stating which platforms have been inspected in the preceding 12 months, the extent and area of inspection, and the type of inspection employed, i.e., visual, magnetic particle, ultrasonic testing. A summary of the testing results shall be submitted indicating what repairs, if any, were needed and the overall structural condition of the platform.

[53 FR 10690, Apr. 1, 1988, as amended at 55 FR 51415, Dec. 14, 1990. Redesignated at 63 FR 29479, May 29, 1998, as amended at 68 FR 19355, Apr. 21, 2003]

§ 250.914 Records.

The lessee shall compile, retain, and make available to Minerals Management Service representatives for the functional life of all platforms, the as-built structural drawings, the design assumptions and analyses, a summary of the nondestructive examination records, and the inspection results

30 CFR Ch. II (7-1-03 Edition)

from platform inspections required by §250.912 of this part.

[53 FR 10690, Apr. 1, 1988. Redesignated and amended at 63 FR 29479, 29486, May 29, 1998]

Subpart J—Pipelines and Pipeline Rights-of-Way

§ 250.1000 General requirements.

(a) Pipelines and associated valves, flanges, and fittings shall be designed, installed, operated, maintained, and abandoned to provide safe and pollution-free transportation of fluids in a manner which does not unduly interfere with other uses in the Outer Continental Shelf (OCS).

(b) An application shall be submitted to the Regional Supervisor and approval obtained prior to the installation, modification, or abandonment of a pipeline which qualifies as a lease term pipeline (see §250.1001, Definitions) and prior to the installation of a right-of-way pipeline or the modification or relinquishment of a pipeline right-of-way.

(c)(1) Department of the Interior (DOI) pipelines, as defined in §250.1001, must meet the requirements in §§250.1000 through 250.1008.

(2) A pipeline right-of-way grant holder must identify in writing to the Regional Supervisor the operator of any pipeline located on its right-of-way, if the operator is different from the right-of-way grant holder.

(3) A producing operator must identify for its own records, on all existing pipelines located on its lease or right-of-way, the specific points at which operating responsibility transfers to a transporting operator.

(i) Each producing operator must, if practical, durably mark all of its above-water transfer points by April 14, 1999 or the date a pipeline begins service, whichever is later.

(ii) If it is not practical to durably mark a transfer point, and the transfer point is located above water, then the operator must identify the transfer point on a schematic located on the facility.

(iii) If a transfer point is located below water, then the operator must