

(2) A white buoy with a black top may be used to indicate to a vessel operator that he must pass to the north or east of the buoy.

(3) In addition, a buoy showing alternate vertical red and white stripes may be used to indicate to a vessel operator that an obstruction to navigation extends from the nearest shore to the buoy and that he must not pass between the buoy and shore. The number of white and red stripes is discretionary, provided that the white stripes are twice the width of the red stripes.

[CGFR 66-32, 31 FR 10321, July 30, 1966, as amended by CGD 97-018, 63 FR 33574, June 19, 1998]

§ 66.10-35 Navigation lights.

A red light shall only be used on a solid colored red buoy. A green light shall only be used on a solid colored black or a solid colored green buoy. White lights shall be used for all other buoys. When a light is used on a cardinal system buoy or a vertically striped white and red buoy, it shall always be quick flashing.

[CGD 97-018, 63 FR 33574, June 19, 1998]

PART 67—AIDS TO NAVIGATION ON ARTIFICIAL ISLANDS AND FIXED STRUCTURES

Subpart 67.01—General Requirements

- Sec.
 67.01-1 Scope.
 67.01-5 Definitions.
 67.01-10 Authority to regulate and delegation of functions.
 67.01-15 Classification of structures.
 67.01-20 Prescribing lines of demarcation.
 67.01-30 Equivalents.

Subpart 67.05—General Requirements for Lights

- 67.05-1 Arrangement of obstruction lights.
 67.05-5 Multiple obstruction lights.
 67.05-10 Characteristics of obstruction lights.
 67.05-15 Operating periods of obstruction lights.
 67.05-20 Minimum lighting requirements.
 67.05-25 Special lighting requirements.

Subpart 67.10—General Requirements for Fog Signals

- 67.10-1 Apparatus requirements.
 67.10-5 Location requirements.
 67.10-10 Operating requirements.
 67.10-15 Approval of fog signals.
 67.10-20 Fog signal tests.
 67.10-25 Application for tests.
 67.10-30 Withdrawal of approval.
 67.10-35 Notice of approval and withdrawal of approval.
 67.10-40 Fog signals authorized for use prior to January 1, 1973.

Subpart 67.15—Miscellaneous Marking Requirements

- 67.15-1 Lights and signals on attendant vessels.
 67.15-5 Seismographic and surveying operations.
 67.15-10 Spoil banks, artificial islands, and dredged channels.

Subpart 67.20—Class “A” Requirements

- 67.20-1 Class “A” structures.
 67.20-5 Obstruction lights.
 67.20-10 Fog signal.

Subpart 67.25—Class “B” Requirements

- 67.25-1 Class “B” structures.
 67.25-5 Obstruction lights.
 67.25-10 Fog signal.

Subpart 67.30—Class “C” Requirements

- 67.30-1 Class “C” structures.
 67.30-5 Obstruction lights.
 67.30-10 Fog signals.

Subpart 67.35—Applications

- 67.35-1 Procedure.
 67.35-5 Contents of application.
 67.35-10 Private aids to navigation.
 67.35-15 To whom addressed.

Subpart 67.40—Notification

- 67.40-1 Notification to District Commander.
 67.40-5 Waivers.
 67.40-10 Communication with owner.
 67.40-15 Marking at owner's expense.
 67.40-20 Charges invoiced to owner.
 67.40-25 Penalty.

Subpart 67.50—District Regulations

- 67.50-1 Scope.
 67.50-5 First Coast Guard District.
 67.50-15 Fifth Coast Guard District.
 67.50-20 Seventh Coast Guard District.
 67.50-25 Eighth Coast Guard District.
 67.50-30 Ninth Coast Guard District.
 67.50-35 Eleventh Coast Guard District.