

**§ 411.25**

point source subject to the provisions of this subpart.

| Pollutant or pollutant property | Pretreatment standard |
|---------------------------------|-----------------------|
| pH .....                        | No limitation.        |
| BOD5 .....                      | Do.                   |
| TSS .....                       | Do.                   |

[40 FR 6440, Feb. 11, 1975, as amended at 60 FR 33951, June 29, 1995]

**§ 411.25 Standards of performance for new sources.**

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

| Effluent characteristic                     | Effluent limitations (maximum for any 1 day)     |
|---------------------------------------------|--------------------------------------------------|
|                                             | Metric units (kg/kg of dust leached)             |
| TSS .....                                   | 0.4.                                             |
| Temperature (heat) .....                    | Not to exceed 3 °C rise above inlet temperature. |
| pH .....                                    | Within the range 6.0 to 9.0.                     |
| English units (lb/1,000 lb of dust leached) |                                                  |
| TSS .....                                   | 0.4.                                             |
| Temperature (heat) .....                    | Not to exceed 3 °C rise above inlet temperature. |
| pH .....                                    | Within the range 6.0 to 9.0.                     |

**§ 411.26 Pretreatment standards for new sources.**

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33951, June 29, 1995]

**§ 411.27 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the conventional pollutant control technology (BCT).**

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants

**40 CFR Ch. I (7-1-03 Edition)**

(which are defined in § 401.16) in § 411.22 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24999, July 9, 1986]

**Subpart C—Materials Storage Piles Runoff Subcategory**

**§ 411.30 Applicability; description of the materials storage piles runoff subcategory.**

The provisions of this subpart are applicable to discharges resulting from the runoff of rainfall which derives from the storage of materials including raw materials, intermediate products, finished products and waste materials which are used in or derived from the manufacture of cement under either Subcategory—A or B.

**§ 411.31 Specialized definitions.**

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *10 year, 24 hour rainfall event* shall mean a rainfall event with a probable recurrence interval of once in ten years as defined by the National Weather Service in Technical Paper No. 40, "Rainfall Frequency Atlas of the United States," May 1961, and subsequent amendments, or equivalent regional or state rainfall probability information developed therefrom.

**§ 411.32 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.**

(a) Except as provided in §§ 125.30 through 125.32, and subject to the provisions of paragraph (b) of this section, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic | Effluent limitations   |
|-------------------------|------------------------|
| TSS .....               | Not to exceed 50 mg/l. |