

Environmental Protection Agency

§ 415.92

the electrolytic process and by the oxidation of alkyl hydroanthraquinones.

§ 415.91 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *product* shall mean hydrogen peroxide as a one hundred percent hydrogen peroxide solution.

(c) The term *Cyanide A* shall mean those cyanides amenable to chlorination and is determined by the methods specified in 40 CFR 136.3.

(d) The term *process wastewater* means any water which, during manufacturing or processing, comes into direct contact with or results from the production or use of any raw material, intermediate product, finished product, by-product, or waste product. The term "process wastewater" does not include contaminated non-process wastewater, as defined below.

(e) The term *process wastewater pollutants* means pollutants present in process wastewater.

(f) The term *contaminated nonprocess wastewater* shall mean any water which, during manufacturing or processing, comes into incidental contact with any raw material, intermediate product, finished product, by-product or waste product by means of (1) rainfall runoff; (2) accidental spills; (3) accidental leaks caused by the failure of process equipment, which are repaired within the shortest reasonable time not to exceed 24 hours after discovery; and (4) discharges from safety showers and related personal safety equipment: Provided, that all reasonable measures have been taken (i) to prevent, reduce and control such contact to the maximum extent feasible; and (ii) to miti-

gate the effects of such contact once it has occurred.

§ 415.92 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

(a) Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart and manufacturing hydrogen peroxide by the oxidation of alkyl hydroanthraquinones must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

SUBPART I—HYDROGEN PEROXIDE ORGANIC PROCESS

Pollutant or pollutant property	BPT limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kg (or pounds per 1,000 lb) of product	
TSS	0.80	0.40
TOC	0.44	0.22
pH	(¹)	(¹)

¹ Within the range 6.0 to 9.0.

(b) Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart and manufacturing hydrogen peroxide by the electrolytic process must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

§ 415.110

**SUBPART I—HYDROGEN PEROXIDE
ELECTROLYTE PROCESS**

Pollutant or pollutant property	BPT limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kgg (or pounds per 1,000 lb) of product	
TSS	0.0050	0.0025
Cyanide A	0.00040	0.00020
pH	(¹)	(¹)

¹ Within the range 6.0 to 9.0.

**Subpart J—Nitric Acid Production
Subcategory [Reserved]**

**Subpart K—Potassium Metal
Production Subcategory**

§ 415.110 Applicability; description of the potassium metal production subcategory.

The provisions of this subpart are applicable to discharges resulting from the production of potassium metal.

§ 415.111 Specialized definitions. [Reserved]

§ 415.112 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT): There shall be no discharge of process wastewater pollutants to navigable waters.

§ 415.113 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of efflu-

ent reduction attainable by the application of the best available technology economically achievable (BAT): There shall be no discharge of process wastewater pollutants to navigable waters.

§ 415.114 [Reserved]

§ 415.115 New source performance standards (NSPS).

Any new source subject to this subpart must achieve the following new source performance standards (NSPS): There shall be no discharge of process wastewater pollutants to navigable waters.

§ 415.116 Pretreatment standards for new sources (PSNS).

Except as provided in § 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources (PSNS): There shall be no discharge of process wastewater pollutants to navigable waters.

**Subpart L—Potassium Dichromate
Production Subcategory**

§ 415.120 Applicability; description of the potassium dichromate production subcategory.

The provisions of this subpart are applicable to discharges and to the introduction of pollutants resulting from the production of potassium dichromate into treatment works which are publicly owned.

§ 415.121 Specialized definitions. [Reserved]

§ 415.122 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT): There shall be no discharge of process