

§ 417.10

40 CFR Ch. I (7–1–03 Edition)

417.153 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

417.154 [Reserved]

417.155 Standards of performance for new sources.

417.156 Pretreatment standards for new sources.

Subpart P—Manufacture of Liquid Detergents Subcategory

417.160 Applicability; description of the manufacture of liquid detergents subcategory.

417.161 Specialized definitions.

417.162 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

417.163 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

417.164 [Reserved]

417.165 Standards of performance for new sources.

417.166 Pretreatment standards for new sources.

Subpart Q—Manufacture of Detergents by Dry Blending Subcategory

417.170 Applicability; description of the manufacturing of detergents by dry blending subcategory.

417.171 Specialized definitions.

417.172 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

417.173 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

417.174 [Reserved]

417.175 Standards of performance for new sources.

417.176 Pretreatment standards for new sources.

Subpart R—Manufacture of Drum Dried Detergents Subcategory

417.180 Applicability; description of the manufacture of drum dried detergents subcategory.

417.181 Specialized definitions.

417.182 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best

practicable control technology currently available.

417.183 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

417.184 [Reserved]

417.185 Standards of performance for new sources.

417.186 Pretreatment standards for new sources.

Subpart S—Manufacture of Detergent Bars and Cakes Subcategory

417.190 Applicability; description of the manufacture of detergent bars and cakes subcategory.

417.191 Specialized definitions.

417.192 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

417.193 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

417.194 Pretreatment standards for existing sources.

417.195 Standards of performance for new sources.

417.196 Pretreatment standards for new sources.

AUTHORITY: Secs. 301, 304 (b) and (c), 306 (b) and (c), and 307(c) of the Federal Water Pollution Control Act as amended, (the Act); 33 U.S.C. 1251, 1311, 1314 (b) and (c), 1316 (b) and (c) and 1317(c), 86 Stat. 816 et seq.; Pub. L. 92–500.

SOURCE: 39 FR 13372, Apr. 12, 1974, unless otherwise noted.

Subpart A—Soap Manufacturing by Batch Kettle Subcategory

§ 417.10 Applicability; description of the soap manufacturing by batch kettle subcategory.

The provisions of this subpart are applicable to discharges resulting from the operations in which neat soap is produced through saponification of animal and vegetable fats and oils by boiling in kettles.

§ 417.11 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and