

**Environmental Protection Agency**

**§ 419.27**

sources (PSES). The following standards apply to the total refinery flow contribution to the POTW:

Pollutant or pollutant property	Pretreatment standards for new sources—maximum for any 1 day
	Milligrams per liter (mg/l)
Oil and grease .....	100
Ammonia .....	100

<sup>1</sup> Where the discharge to the POTW consists solely of sour waters, the owner or operator has the option of complying with this limit or the daily maximum mass limitation for ammonia set forth in § 419.23 (a) and (b).

**§ 419.26 Standards of performance for new sources (NSPS).**

(a) Any new source subject to this subpart must achieve the following new source performance standards (NSPS):

Pollutant or pollutant property	NSPS effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed
	Metric units (kilograms per 1,000 m <sup>3</sup> of feedstock)	
BOD5 .....	16.3	8.7
TSS .....	11.3	7.2
COD <sup>1</sup> .....	118.0	61
oil and grease .....	4.8	2.6
Phenolic compounds .....	0.119	0.058
Ammonia (as N) .....	18.8	8.6
Sulfide .....	0.105	0.048
Total chromium .....	0.24	0.14
Hexavalent chromium .....	0.020	0.0088
pH .....	( <sup>2</sup> )	( <sup>2</sup> )
	English units (pounds per 1,000 bbl of feedstock)	
BOD5 .....	5.8	3.1
TSS .....	4.0	2.5
COD <sup>1</sup> .....	41.5	21
Oil and grease .....	1.7	0.93
Phenolic compounds .....	0.042	0.020
Ammonia (as N) .....	6.6	3.0
Sulfide .....	0.037	0.017
Total chromium .....	0.084	0.049
Hexavalent chromium .....	0.0072	0.0032
pH .....	( <sup>2</sup> )	( <sup>2</sup> )

<sup>1</sup> See footnote following table in § 419.13(d).  
<sup>2</sup> Within the range 6.0 to 9.0.

(b) The limits set forth in paragraph (a) of this section are to be multiplied by the following factors to calculate the maximum for any 1 day and maximum average of daily values for 30 consecutive days.

(1) Size Factor.

1,000 bbl of feedstock per stream day	Size factor
Less than 24.9 .....	0.91
25.0 to 49.9 .....	0.95
50.0 to 74.9 .....	1.04
75.0 to 99.9 .....	1.13
100.0 to 124.9 .....	1.23
125.0 to 149.9 .....	1.35
150.0 or greater .....	1.41

(2) Process factor.

Process configuration	Process factor
Less than 2.49 .....	0.58
2.5 to 3.49 .....	0.63
3.5 to 4.49 .....	0.74
4.5 to 5.49 .....	0.88
5.5 to 5.99 .....	1.00
6.0 to 6.49 .....	1.09
6.5 to 6.99 .....	1.19
7.0 to 7.49 .....	1.29
7.5 to 7.99 .....	1.41
8.0 to 8.49 .....	1.53
8.5 to 8.99 .....	1.67
9.0 to 9.49 .....	1.82
9.5 or greater .....	1.89

(3) See the comprehensive example in subpart D, § 419.42(b)(3).

(c) The provisions of § 419.16(c) apply to discharges of process wastewater pollutants attributable to ballast water by a point source subject to the provisions of this subpart.

(d) The quantity and quality of pollutants or pollutant properties controlled by this paragraph, attributable to once-through cooling water, are excluded from the discharge allowed by paragraph (b) of this section. Once-through cooling water may be discharged with a total organic carbon concentration not to exceed 5 mg/l.

(e) *Effluent limitation for runoff.* [Reserved]

[47 FR 46446, Oct. 18, 1982, as amended at 50 FR 28523, July 12, 1985; 50 FR 32414, Aug. 12, 1985]

**§ 419.27 Pretreatment standards for new sources (PSNS).**

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must