

**§ 419.45**

of wastewater, the quantity of pollutants discharged shall not exceed the quantity determined by multiplying the flow of contaminated runoff as determined by the permit writer times the concentrations listed in the following table:

Pollutant or pollutant property	BCT effluent limitations for contaminated runoff	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed
	Metric unit (kilograms per 1,000 m <sup>3</sup> of flow)	
BOD <sub>5</sub> .....	48.	26.
TSS .....	33.	21.
Oil and grease .....	15.	8.
pH .....	( <sup>1</sup> )	( <sup>1</sup> )
	English units (pounds per 1,000 gallons of flow)	
BOD <sub>5</sub> .....	0.40	0.22
TSS .....	0.28	0.18
Oil and grease .....	0.13	0.067
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 6.0 to 9.0.

[50 FR 28526, July 12, 1985]

**§ 419.45 Pretreatment standards for existing sources (PSES).**

Except as provided in 40 CFR 403.7 and 403.13 any existing source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for existing sources (PSES). The following standards apply to the total refinery flow contribution to the POTW:

Pollutant or pollutant property	Pretreatment standards for existing sources—maximum for any 1 day
	Milligrams per liter (mg/l)
Oil and grease .....	100
Ammonia (as N) .....	<sup>1</sup> 100

<sup>1</sup> Where the discharge to the POTW consists solely of sour waters, the owner or operator has the option of complying with this limit or the daily maximum mass limitation for ammonia set forth in § 419.43 (a) and (b).

**40 CFR Ch. I (7-1-03 Edition)**

**§ 419.46 Standards of performance for new sources (NSPS).**

(a) Any new source subject to this subpart must achieve the following new source performance standards (NSPS):

Pollutant or pollutant property	NSPS effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed
	Metric units (kilograms per 1,000 m <sup>3</sup> of feedstock)	
BOD <sub>5</sub> .....	34.6	18.4
TSS .....	23.4	14.9
COD <sup>1</sup> .....	245.0	126.0
Oil and grease .....	10.5	5.6
Phenolic compounds .....	0.25	0.12
Ammonia as N .....	23.4	10.7
Sulfide .....	0.220	0.10
Total chromium .....	0.52	0.31
Hexavalent chromium .....	0.046	0.021
pH .....	( <sup>2</sup> )	( <sup>2</sup> )
	English units (pounds per 1,000 bbl of feedstock)	
BOD <sup>1</sup> .....	12.2	6.5
TSS .....	8.3	5.3
COD <sup>1</sup> .....	87.0	45.0
Oil and grease .....	3.8	2.0
Phenolic compounds .....	0.088	0.043
Ammonia as N .....	8.3	3.8
Sulfide .....	0.078	0.035
Total chromium .....	0.180	0.105
Hexavalent chromium .....	0.022	0.0072
pH .....	( <sup>2</sup> )	( <sup>2</sup> )

<sup>1</sup> See footnote following table in § 419.13(d).

<sup>2</sup> Within the range 6.0 to 9.0.

(b) The limits set forth in paragraph (a) of this section are to be multiplied by the following factors to calculate the maximum for any one day and maximum average of daily values for thirty consecutive days.

(1) Size factor.

1,000 bbl of feedstock per stream day	Size factor
Less than 49.9 .....	0.71
50.0 to 74.9 .....	0.74
75.0 to 99.9 .....	0.81
100.0 to 124.9 .....	0.88
125.0 to 149.9 .....	0.97
150.0 to 174.9 .....	1.05
175.0 to 199.9 .....	1.14
200.0 or greater .....	1.19

(2) Process factor.

Process configuration	Process factor
Less than 6.49 .....	0.81

**Environmental Protection Agency**

**§ 419.52**

Process configuration	Process factor
6.5 to 7.49 .....	0.88
7.5 to 7.99 .....	1.00
8.0 to 8.49 .....	1.09
8.5 to 8.99 .....	1.19
9.0 to 9.49 .....	1.29
9.5 to 9.99 .....	1.41
10.0 to 10.49 .....	1.53
10.5 to 10.99 .....	1.67
11.0 to 11.49 .....	1.82
11.5 to 11.99 .....	1.98
12.0 to 12.49 .....	2.15
12.5 to 12.99 .....	2.34
13.0 or greater .....	2.44

(3) See the comprehensive example in subpart D, § 419.42(b)(3).

(c) The provisions of § 419.16(c) apply to discharges of process wastewater pollutants attributable to ballast water by a point source subject to the provision of this subpart.

(d) The quantity and quality of pollutants or pollutant properties controlled by this paragraph, attributable to once-through cooling water, are excluded from the discharge allowed by paragraph (b) of this section. Once-through cooling water may be discharged with a total organic carbon concentration not to exceed 5 mg/l.

(e) *Effluent Limitations for Runoff.* [Reserved]

[47 FR 46446, Oct. 18, 1982, as amended at 50 FR 28523, 28528, July 12, 1985; 50 FR 32414, Aug. 12, 1985]

**§ 419.47 Pretreatment standards for new sources (PSNS).**

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources (PSNS).

(a) The following standards apply to the total refinery flow contribution to the POTW:

Pollutant or pollutant property	Pretreatment standards for new sources, maximum for any 1 day
	Milligrams per liter (mg/l)
Oil and grease .....	100

Pollutant or pollutant property	Pretreatment standards for new sources, maximum for any 1 day
Ammonia (as N) .....	1 100

<sup>1</sup> Where the discharge to the POTW consists solely of sour waters, the owner or operator has the option of complying with this limit or the daily maximum mass limitation for ammonia set forth in § 419.46 (a) and (b).

(b) The following standard is applied to the cooling tower discharge part of the total refinery flow to the POTW by multiplying: (1) The standard; (2) by the total refinery flow to the POTW; and (3) by the ratio of the cooling tower discharge flow to the total refinery flow.

Pollutant or pollutant property	Pretreatment standards for new sources, maximum for any 1 day
	Milligrams per liter (mg/l)
Total chromium .....	1

**Subpart E—Integrated Subcategory**

**§ 419.50 Applicability; description of the integrated subcategory.**

The provisions of this subpart are applicable to all discharges resulting from any facility that produces petroleum products by the use of topping, cracking, lube oil manufacturing processes, and petrochemical operations, whether or not the facility includes any process in addition to topping, cracking, lube oil manufacturing processes, and petrochemical operations.

**§ 419.51 Specialized definitions.**

The general definitions, abbreviations, and methods of analysis set forth in part 401 of this chapter and the specialized definitions set forth in § 419.31 shall apply to this subpart.

**§ 419.52 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).**

(a) Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must