

§ 420.17

40 CFR Ch. I (7-1-03 Edition)

achieve the following pretreatment standards for new sources (PSNS), as applicable.

(a) *By-product cokemaking.* (1) Any new source subject to the provisions of this section that commenced discharging after November 19, 2012 and before November 18, 2002 must continue to achieve the standards specified in § 420.16 of title 40 of the Code of Federal Regulations, revised as of July 1, 2001, (except for the standards for phenols 4AAP) for ten years beginning on the date the source commenced discharge or during the period of depreciation or amortization of the facility, whichever comes first, after which the source must achieve the standards specified in § 420.15(a).

(2) Except as provided in 40 CFR 403.7, the following standards apply with respect to each new source that commences construction after November 18, 2002:

SUBPART A—PRETREATMENT STANDARDS FOR NEW SOURCES (PSNS)

Regulated parameter	Maximum daily ¹	Maximum monthly avg. ¹
Ammonia-N ²	0.00293	0.00202
Benzo(a)pyrene	0.0000110	0.00000612
Cyanide	0.00297	0.00208
Naphthalene	0.0000111	0.00000616

¹ Pounds per thousand lb of product.

² The pretreatment standards for ammonia are not applicable to sources that discharge to a POTW with nitrification capability (defined at § 420.02(s)).

(A) Increased loadings, not to exceed 13.3 percent of the above limitations, shall be provided for process wastewaters from coke oven gas wet desulfurization systems, but only to the extent such systems generate process wastewaters.

(B) Increased loadings shall be provided for process wastewaters from other wet air pollution control systems (except those from coal charging and coke pushing emission controls), coal tar processing operations and coke plant groundwater remediation systems, but only to the extent such systems generate process wastewaters and those wastewaters are co-treated with process wastewaters from by-product cokemaking wastewaters.

(C) Increased loadings, not to exceed 44.2 percent of the above limitations, shall be provided for water used for the

optimization of coke plant biological treatment systems.

(b) *Cokemaking—non-recovery.* Except as provided in 40 CFR 403.7, the following standards apply with respect to each new source that commences construction after November 18, 2002: There shall be no discharge of process wastewater pollutants to POTWs.

[67 FR 64263, Oct. 17, 2002]

§ 420.17 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional technology (BCT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional technology.

(a) *By-product cokemaking—iron and steel.*

SUBPART A

Pollutant or pollutant property	BCT effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kgg (pounds per 1,000 lb) of product	
TSS	0.253	0.131
O&G	0.0327	0.0109
pH	(¹)	(¹)

¹ Within the range of 6.0 to 9.0.

(1) Increased loadings, not to exceed 11 percent of the above limitations, are allowed for by-product coke plants which have wet desulfurization systems but only to the extent such systems generate an increased effluent volume.

(2) Increased loadings, not to exceed 27 percent of the above limitations, are allowed for by-product coke plants which include indirect ammonia recovery systems but only to the extent that such systems generate an increased effluent volume.

(b) *By-product cokemaking—merchant.*

SUBPART A

Pollutant or pollutant property	BCT effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kg (pounds per 1,000 lb) of product	
TSS	0.270	0.140
O&G	0.0348	0.0116
pH	(¹)	(¹)

¹ Within the range of 6.0 to 9.0.

(1) Increased loadings, not to exceed 10 percent of the above limitations, are allowed for by-product coke plants which have wet desulfurization systems but only to the extent such systems generate an increased effluent volume.

(2) Increased loadings, not to exceed 25 percent of the above limitations, are allowed for by-product coke plants which include indirect ammonia recovery systems but only to the extent that such systems generate an increased effluent volume.

(c) *Cokemaking—non-recovery.* Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this segment must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): There shall be no discharge of process wastewater pollutants to waters of the U.S.

[47 FR 23284, May 27, 1982, as amended at 67 FR 64264, Oct. 17, 2002]

§ 420.18 Pretreatment standards compliance dates.

Compliance with the pretreatment standards for existing sources set forth in § 420.15 of this subpart is required not later than October 17, 2005 whether or not the pretreatment authority issues or amends a pretreatment permit requiring such compliance. Until that date, the pretreatment standards for existing sources set forth in Subpart A of title 40 of the Code of Federal Regulations, revised as of July 1, 2001, shall continue to apply.

[67 FR 64264, Oct. 17, 2002]

Subpart B—Sintering Subcategory

§ 420.20 Applicability; description of the sintering subcategory.

The provisions of this subpart are applicable to discharges and to the introduction of pollutants into publicly owned treatment works resulting from sintering operations conducted by the heating of iron bearing wastes (mill scale and dust from blast furnaces and steelmaking furnaces) together with fine iron ore, limestone, and coke fines in an ignition furnace to produce an agglomerate for charging to the blast furnace.

§ 420.21 Specialized definitions.

As used in this subpart:

(a) For the sintering subcategory, the term *product* means sinter agglomerated from iron-bearing materials.

(b) The term *dry air pollution control system* means an emission control system that utilizes filters to remove iron-bearing particles (fines) from blast furnace or sintering off-gases.

(c) The term *minimum level (ML)* means the level at which the analytical system gives recognizable signals and an acceptable calibration point. For 2,3,7,8-tetrachlorodibenzofuran, the minimum level is 10 pg/L per EPA Method 1613B for water and wastewater samples.

(d) The term *pg/L* means picograms per liter (ppt = 1.0×10⁻¹² gm/L).

(e) The term *sintering* means a process for agglomerating iron-bearing materials into small pellets (sinter) that can be charged to a blast furnace.

(f) The term *wet air pollution control system* means an emission control system that utilizes water to clean process or furnace off-gases.

[67 FR 64264, Oct. 17, 2002]

§ 420.22 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must