

§ 420.23

40 CFR Ch. I (7-1-03 Edition)

achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

(a) *Sintering operations with wet air pollution control system.* The following table presents BPT limitations for sintering operations with wet air pollution control systems:

SUBPART B—EFFLUENT LIMITATIONS (BPT)

Pollutants or pollutant property	BPT effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kkg (pounds per 1000 lb) of product	
TSS	0.0751	0.0250
O&G	0.0150	0.00501
pH	(¹)	(¹)

¹ Within the range of 6.0 to 9.0.

(b) *Sintering operations with dry air pollution control system.* There shall be no discharge of process wastewater pollutants to waters of the U.S.

[67 FR 64264, Oct. 17, 2002]

§ 420.23 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point

source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available control technology economically achievable (BAT).

(a) *Sintering operations with wet air pollution control system.* The following table presents BAT limitations for sintering operations with wet air pollution control systems:

SUBPART B—EFFLUENT LIMITATIONS (BAT)

Regulated parameter	Maximum daily ¹	Maximum monthly avg. ¹
Ammonia-N ²	0.0150	0.00501
Cyanide ³	0.00300	0.00150
Lead	0.000451	0.000150
Phenols (4AAP) ²	0.000100	0.0000501
2,3,7,8-TCDF	<ML	
TRC ³	0.000250	
Zinc	0.000676	0.000225

¹ Pounds per thousand lb of product.

² Limits for these parameters apply only when sintering waste water is co-treated with ironmaking wastewater.

³ Applicable only when sintering process wastewater is chlorinated.

(b) *Sintering operations with dry air pollution control system.* There shall be no discharge of process wastewater pollutants to waters of the U.S.

[67 FR 64264, Oct. 17, 2002]

§ 402.24 New source performance standards (NSPS).

New sources subject to this subpart must achieve the following new source performance standards (NSPS), as applicable.

(a) Any new source subject to the provisions of this section that commenced discharging after November 19, 2012 and before November 18, 2002 must continue to achieve the applicable standards specified in § 420.24 of title 40 of the Code of Federal Regulations, revised as of July 1, 2001, except that after the expiration of the applicable time period specified in 40 CFR 122.29(d)(1), the source must also achieve the effluent limitations specified in § 420.23 for 2,3,7,8-TCDF.