

§ 424.23

the limitations (except for pH) shall be 3.3 times those listed in the table in this section (or, for English units, "lb/ton of product" rather than "lb/Mwh," and the limitations (except for pH) shall be three times those listed in the table).

[39 FR 6809, Feb. 22, 1974, as amended at 39 FR 17841, May 21, 1974; 60 FR 33957, June 29, 1995]

§ 424.23 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best available technology economically achievable:

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
Metric units (kg/Mwh)		
Chromium total	0.001	0.0005
Chromium VI0001	.00005
Manganese total011	.005
Cyanide total0005	.0003
Phenols0004	.0002
English units (lb/Mwh)		
Chromium total002	.0012
Chromium VI0002	.0001
Manganese total023	.012
Cyanide total001	.0006
Phenols0009	.0005

Provided, however, That for nonelectric furnace smelting processes, the units of effluent limitations set forth in this section shall be read as "kg/kg of product" rather than "kg/Mwh," and the limitations (except for pH) shall be 3.3 times those listed in the table in this section (or, for English units, "lb/ton of product" rather than "lb/Mwh," and the limitations (except for pH) shall be three times those listed in the table).

[44 FR 50744, Aug. 29, 1979]

40 CFR Ch. I (7-1-03 Edition)

§ 424.24 [Reserved]

§ 424.25 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
Metric units (kg/Mwh)		
TSS	0.032	0.016
Chromium total001	.0005
Chromium VI0001	.00005
Manganese total011	.005
Cyanide total0005	.0003
Phenols0004	.0002
pH	(¹)	(¹)
English units (lb/Mwh)		
TSS071	.035
Chromium total002	.0012
Chromium VI0002	.0001
Manganese total023	.012
Cyanide total001	.0006
Phenols0009	.0005
pH	(¹)	(¹)

¹ Within the range 6.0 to 9.0.

Provided, however, That for nonelectric furnace smelting processes, the units of effluent limitations set forth in this section shall be read as "kg/kg of product" rather than "kg/Mwh," and the limitations (except for pH) shall be 3.3 times those listed in the table in this section (or, for English units, "lb/ton of product" rather than "lb/Mwh," and the limitations (except for pH) shall be three times those listed in the table).

[39 FR 6809, Feb. 22, 1974, as amended at 39 FR 17841, May 21, 1974]

§ 424.26 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33957, June 29, 1995]