

Decrease in Storage Targets for Carson Division Diversion Demand Less than 271,000 acre-feet									
Target Adjust-ment	Carson Division Demand	Jan-May	June	July	Aug	Sep	Oct	Nov	Dec
0	271.0	174	190	160	100	64	52	74	101
-1	270.4	173	189	159	99	63	51	73	100
-2	269.9	172	188	158	98	62	50	72	99
-3	269.3	171	187	157	97	61	49	71	98
-4	268.7	170	186	156	96	60	48	70	97
-5	268.1	169	185	155	95	59	47	69	96
-6	267.6	168	184	154	94	58	46	68	95
-7	267.0	167	183	153	93	57	45	67	94
-8	266.4	166	182	152	92	56	44	66	93
-9	265.8	165	181	151	91	55	43	65	92
-10	265.3	164	180	150	90	54	42	64	91
-11	264.7	163	179	149	89	53	41	63	90
-12	264.1	162	178	148	88	52	40	62	89
-13	263.5	161	177	147	87	51	39	61	88
-14	263.0	160	176	146	86	50	38	60	87
-15	262.4	159	175	145	85	49	37	59	86
-16	261.8	158	174	144	84	48	36	58	85
-17	261.2	157	173	143	83	47	35	57	84
-18	260.7	156	172	142	82	46	34	56	83
-19	260.1	155	171	141	81	45	33	55	82
-20	259.5	154	170	140	80	44	32	54	81
-21	258.9	153	169	139	79	43	31	53	80
-22	258.4	152	168	138	78	42	30	52	79
-23	257.8	151	167	137	77	41	29	51	78
-24	257.2	150	166	136	76	40	28	50	77
-25	256.6	149	165	135	75	39	27	49	76
-26	256.1	148	164	134	74	38	26	48	75
-27	255.5	147	163	133	73	37	25	47	74
-28	254.9	146	162	132	72	36	24	46	73
-29	254.3	145	161	131	71	35	23	45	72
-30	253.8	144	160	130	70	34	22	44	71
-31	253.2	143	159	129	69	33	21	43	70
-32	252.6	142	158	128	68	32	20	42	69
-33	252.0	141	157	127	67	31	19	41	68
-34	251.5	140	156	126	66	30	18	40	67
-35	250.9	139	155	125	65	29	17	39	66
-36	250.3	138	154	124	64	28	16	38	65
-37	249.7	137	153	123	63	27	15	37	64

§418.23 Diversion of Rock Dam Ditch water.

Project water may be diverted directly to Rock Dam Ditch from the Truckee Canal only when diversions cannot be made from the outlet works of Lahontan Reservoir. Such diversions will require the prior written approval

of the Bureau and be used in calculating Project diversions.

§418.24 Precautionary drawdown and spills from Lahontan Reservoir.

(a) Even though flood control is not a specifically authorized purpose of the Project, at the request of the District

§418.25

and in consultation with other interested parties and the approval of the Bureau, precautionary drawdown of Lahontan Reservoir may be made to limit potential flood damage along the Carson River. The Bureau will develop criteria for precautionary drawdown in consultation with the District and other interested parties.

(1) The drawdown must be scheduled sufficiently in advance and at such a rate of flow in order to divert as much water as possible into the Project irrigation system for delivery to eligible land or storage in reregulating reservoirs for later use on eligible land.

(2) During periods of precautionary drawdown, or when water is spilled from Lahontan Reservoir, Project diversions will be determined by comparison with other years' data and normalized by comparison of differences in climatological data. The Bureau will estimate the normalization in consultation with the District and other interested parties.

(3) Spills from Lahontan Reservoir and precautionary drawdown of the reservoir to create space for storing flood waters from the Carson River Basin that are in excess of the normalized diversions will not be used in calculating Project diversions.

(4) Water captured in Project facilities as a result of a precautionary drawdown or spill will not be counted as storage in Lahontan Reservoir for the purpose of calculating Truckee River Diversions. Such water will not be counted as diversions to the Project unless such water is beneficially applied as described in (a)(5) of this section.

(5) Water from precautionary drawdowns or spills that is captured in Project facilities must be used to the maximum extent possible, and counted as deliveries to eligible lands in the year of the drawdown. If all the drawdown water captured in Project facilities cannot be used in the year of capture for delivery to eligible lands, then that water must be delivered to eligible lands in subsequent years to the maximum extent possible and counted against the water users' annual allocation.

(b) If a precautionary drawdown in one month results in a failure to meet

43 CFR, Subtitle B, Ch. I (10-1-03 Edition)

the Lahontan Reservoir storage objective for that month, the storage objective in subsequent months will be reduced by one-half of the difference between that month's storage objective and actual end-of-month storage. The Bureau is not liable for any damage or water shortage resulting from a precautionary drawdown.

§418.25 Water use for other than Newlands Project purposes.

The District will release sufficient water to meet the vested water rights below Sagouspe Dam as specified in the *Alpine* decree. These water rights are usually met by return flows. Releases for these water rights will in no case exceed the portion of 1,300 acre-feet per year not supplied by return flows. This water must be accounted for at the USGS gauge number 10312275 (the Carson River at Tarzyn Road near Fallon). Releases for this purpose will not be considered in determining Project diversions since the lands to which the water is being delivered are not part of the Project. (See §418.15(b)(2)(ii).) Any flow past this gage in excess of the amount specified in this part will be absorbed by the District as an efficiency loss.

§418.26 Charges for water use.

The District must maintain a financing and accounting system which produces revenue sufficient to repay its operation and maintenance costs and to discharge any debt to the United States. The District should give consideration to adopting a system which provides reasonable financial incentives for the economical and efficient use of water.

§418.27 Distribution system operation.

(a) The District must permit only its authorized employees or agents to open and close individual turnouts and operate the distribution system facilities. After obtaining Bureau approval, the District may appoint agents to operate individual headgates on a specific lateral if it can be shown that the water introduced to the lateral by a District employee is completely scheduled and can be fully accounted for with a reasonable allowance for seepage and evaporation losses.