

Federal Communications Commission

§ 21.106

listed in subpart K. Assignment of frequencies will be made only in such a manner as to facilitate the rendition of communication service on an interference-free basis in each service area. Unless otherwise indicated, each frequency available for use by stations in this service will be assigned exclusively to a single applicant in any service area. All applicants for, and licensees of, stations in this service shall cooperate in the selection and use of the frequencies assigned in order to minimize interference and thereby obtain the most effective use of the authorized facilities. In the event harmful interference occurs or appears likely to occur between two or more radio systems and such interference cannot be resolved between the licensees thereof, the Commission may, after notice and opportunity for hearing, require the licensees to make such changes in operating techniques or equipment as it may deem necessary to avoid such interference.

[61 FR 26675, May 28, 1996]

§ 21.101 Frequency tolerance.

(a) The carrier frequency of each transmitter authorized in these services shall be maintained within the following percentage of the reference frequency except as otherwise provided in paragraph (b) of this section or in the applicable subpart of this part (unless otherwise specified in the instrument of station authorization the reference frequency shall be deemed to be the assigned frequency):

Frequency range (MHz)	Frequency tolerance for fixed stations (percent)
2,150 to 2,162 ^{1 2}	0.001
2,596 to 2,680 ²	0.005

¹ Beginning Aug. 9, 1975, this tolerance will govern the marketing of equipment pursuant to §§ 2.803 and 2.805 of this chapter and the issuance of all authorizations for new radio equipment. Until that date new equipment may be authorized with a frequency tolerance of 0.03 percent in the frequency range 2,200 to 10,500 MHz and equipment so authorized may continue to be used for its life provided that it does not cause interference to the operation of any other licensee. Equipment authorized in the frequency range 2,450 to 10,500 MHz prior to June 23, 1969, at a tolerance of 0.05 percent may continue to be used until February 1, 1976 provided it does not cause interference to the operation of any other licensee.

² Beginning January 21, 2000, the equipment authorized to be used at all MDS main stations, and at all MDS booster stations authorized pursuant to § 21.913(b) of this part, shall maintain a frequency tolerance of 0.001%. MDS booster stations authorized pursuant to § 21.913(e) of this part and MDS response stations authorized pursuant to § 21.909 of this part shall employ transmitters with sufficient frequency stability to ensure that the emission is, at all times, within the required emission mask.

(b) As an additional requirement in any band where the Commission makes assignments according to a specified channel plan, provisions shall be made to prevent the emission included within the occupied bandwidth from radiating outside the assigned channel at a level greater than that specified in § 21.106.

[44 FR 60534, Oct. 19, 1979, as amended at 46 FR 23450, Apr. 27, 1981; 48 FR 50329, Nov. 1, 1983; 48 FR 50732, Nov. 3, 1983; 49 FR 37775, Sept. 26, 1984; 54 FR 10327, Mar. 13, 1989; 54 FR 24905, June 12, 1989; 55 FR 46009, Oct. 31, 1990; 56 FR 57816, Nov. 14, 1991; 61 FR 26675, May 28, 1996; 63 FR 65101, Nov. 25, 1998; 64 FR 63730, Nov. 22, 1999]

§§ 21.102–21.104 [Reserved]

§ 21.105 Bandwidth.

Each authorization issued pursuant to these rules will show, as the emission designator, a symbol representing the class of emission which shall be prefixed by a number specifying the necessary bandwidth. This figure does not necessarily indicate the bandwidth actually occupied by the emission at any instant. In those cases where part 2 of this chapter does not provide a formula for the computation of the necessary bandwidth, the occupied bandwidth may be used in the emission designator.

[49 FR 48700, Dec. 14, 1984]

§ 21.106 Emission limitations.

(a) The mean power of emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:

- (1) When using transmissions other than those employing digital modulation techniques:
 - (i) On any frequency removed from the assigned frequency by more than 50 percent up to and including 100 percent of the authorized bandwidth: At least 25 decibels;
 - (ii) On any frequency removed from the assigned frequency by more than