

calibrate such conveyances. Volumetric measurements in tanks shall be made only in accurately calibrated tanks equipped with suitable measuring devices, whereby the actual contents can be correctly ascertained. If the temperature of spirits (including denatured spirits) is other than the standard of 60 degrees Fahrenheit, gallonage determined by volumetric measurements shall be corrected to the standard temperature by means of table 7. In the case of denatured spirits, the temperature-correction factor for the proof of the spirits used in denaturation will give sufficiently accurate results, except that the temperature-correction factor used for specially denatured spirits, Formula No. 18, should be that given in table 7 for 100 proof spirits. When the quantity of spirits, in wine gallons, has been determined by volumetric measurement, the number of proof gallons shall be obtained by multiplying the wine gallons by the proof of the spirits as determined under § 30.31.

*Example* Gauge glass reading inches—88.  
 Wine gallons per inch—48.96.  
 Temperature °F—72.  
 Proof of spirits—86.8.  
 Temperature correction factor (Table 7)—0.995.  
 48.96 W.G.×88=4308.48 wine gallons.  
 4308.48 W.G.×0.995=4286.94 wine gallons.  
 4286.94 W.G.×0.868=3721.06392=3721.1 proof gallons.

(Sec. 201, Pub. L. 85-859, 72 Stat. 1358, as amended (26 U.S.C. 5204))

[T.D. ATF-198, 50 FR 8535, Mar. 1, 1985, as amended by T.D. ATF-381, 61 FR 37004, July 16, 1996]

**§ 30.52 Procedure for measurement of cased spirits.**

Where the quantity of spirits in a case is to be determined by volume, such determination shall be made by ascertaining the contents of one bottle in the case and multiplying that figure by the number of bottles in the case. For cases containing bottles filled according to the metric system of measure, the quantity determined shall be converted to wine gallons, as provided in § 19.722 of this chapter. The wine gallons of spirits thus determined for one case may then be multiplied by the number of cases containing spirits at the same proof when determining the

quantity of spirits for more than one case. The proof gallons of spirits in cases shall be determined by multiplying the wine gallons by the proof (divided by 100).

(Sec. 201, Pub. L. 85-859, 72 Stat. 1358, as amended (26 U.S.C. 5204))

**Subpart E—Prescribed Tables**

NOTE. The tables referred to in this subpart appear in their entirety in the "Gauging Manual Embracing Instructions and Tables for Determining Quantity of Distilled Spirits by Proof and Weight" which is incorporated by reference in this part (see § 30.1).

**§ 30.61 Table 1, showing the true percent of proof spirit for any indication of the hydrometer at temperatures between zero and 100 degrees Fahrenheit.**

This table shows the true percent of proof of distilled spirits for indications of the hydrometer likely to occur in practice at temperatures between zero and 100 degrees Fahrenheit and shall be used in determining the proof of spirits. The left-hand column contains the reading of the hydrometer and on the same horizontal line, in the body of the table, in the "Temperature" column corresponding to the reading of the thermometer is the corrected reading or "true percent of proof." The table is computed for tenths of a percent.

*Example.*  
 Temperature, °F ..... 75  
 Hydrometer reading ..... 193  
 True percent of proof ..... 189.5

Where fractional readings are ascertained, the proper interpolations will be made (see § 30.23). If the distilled spirits contain dissolved solids, temperature-correction of the hydrometer reading by the use of this table would result in apparent proof rather than true proof.

(Sec. 201, Pub. L. 85-859, 72 Stat. 1358, as amended (26 U.S.C. 5204))

**§ 30.62 Table 2, showing wine gallons and proof gallons by weight.**

The wine and proof gallon content by weight and proof of packages of distilled spirits usually found in actual practice will be ascertained from this table. The left-hand column contains the weights. The true percent of proof is shown on the heading of each page in a range from 90 degrees to 200 degrees.