

§ 460.6

16 CFR Ch. I (1-1-04 Edition)

§ 460.6 “Representative thickness” testing.

All tests except aluminum foil tests must be done at a representative thickness for every thickness shown in a label, fact sheet, ad, or other promotional material. “Representative thickness” means a thickness at which the R-value per unit will vary no more than plus or minus 2% with increases in thickness. However, if the thickness shown in your label, fact sheet, ad, or promotional material is less than the representative thickness, then you can test the insulation at the thickness shown.

§ 460.7 Which test version to use.

Use the version of the ASTM test method that was in effect when this regulation was promulgated. If ASTM changes a test method, the new version will automatically replace the old one in these rules 90 days after ASTM first publishes the change. However, the Commission’s staff or a person affected by the change can petition the Commission during the 90-day period not to adopt the change or to reopen the proceeding to consider it further.

§ 460.8 R-value tolerances.

If you are an industry member, the R-value of any insulation you sell cannot be more than 10% below the R-value shown in a label, fact sheet, ad, or other promotional material for that insulation. However, if you are not a manufacturer, you can rely on the R-value data given to you by the manufacturer, unless you know or should know that the data is false or not based on the proper tests.

§ 460.9 What test records you must keep.

Manufacturers and testing labs must keep records of each item of information in the “Report” section of the ASTM test method that is used for a test. They must also keep the following records:

- (a) The name and address of the testing lab that did each test.
- (b) The date of each test.
- (c) For manufacturers, the date each test report was received from a lab. For labs, the date each test report was sent to a manufacturer.

(d) For extruded polystyrene, polyurethane, and polyisocyanurate, the age (in days) of the specimen that was tested.

(e) For aluminum foil, the emissivity level that was found in the test.

Manufacturers who own their own testing labs need not keep records of the information in paragraph (c) of this section.

Keep these records for at least three years. If the documents show proof for your claims, the three years will begin again each time you make the claim. Federal Trade Commission staff members can check these records at any time, but they must give you reasonable notice first.

§ 460.10 How statements must be made.

All statements called for by this regulation must be made clearly and conspicuously. Among other things, you must follow the Commission’s enforcement policy statement for clear and conspicuous disclosures in foreign language advertising and sales materials, 16 CFR 14.9.

[61 FR 13666, Mar. 28, 1996]

§ 460.11 Rounding off R-values.

R-values shown in labels, fact sheets, ads, or other promotional materials must be rounded to the nearest tenth. However, R-values of 10 or more may be rounded to the nearest whole number.

§ 460.12 Labels.

If you are a manufacturer, you must label all packages of your insulation. The labels must contain:

- (a) The type of insulation.
- (b) A chart showing these items:
 - (1) For mineral fiber batts and blankets: the R-value, length, width, thickness, and square feet of insulation in the package.
 - (2) For all loose-fill insulation except cellulose: The minimum thickness, maximum net coverage area, and minimum weight per square foot at R-values of 11, 19, and 22. You must also give this information for any additional R-values you list on the chart. Labels for