

§467.26**40 CFR Ch. I (7-1-04 Edition)****SUBPART B***Direct Chill Casting Contact Cooling Water*

Pollutant or pollutant property	PSES	
	Maximum for any 1 day	Maximum for monthly average
mg/off-kg (lb/million off-lbs) of aluminum cast by semi-continuous methods		
Chromium	0.59	0.24
Cyanide	0.39	0.16
Zinc	1.94	0.81
TTO	0.92
Oil and grease (alternate monitoring parameter)	69	35

SUBPART B*Solution Heat Treatment Contact Cooling Water*

Pollutant or pollutant property	PSES	
	Maximum for any 1 day	Maximum for monthly average
mg/off-kg (lb/million off-lbs) of aluminum quenched		
Chromium	0.90	0.37
Cyanide	0.59	0.25
Zinc	2.98	1.25
TTO	1.41
Oil and grease (alternate monitoring parameter)	110	53

SUBPART B*Cleaning or Etching Bath*

Pollutant or pollutant property	PSES	
	Maximum for any 1 day	Maximum for monthly average
mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched		
Chromium	0.079	0.032
Cyanide	0.052	0.022
Zinc	0.262	0.109
TTO	0.124
Oil and grease (alternate monitoring parameter)	9.3	4.7

SUBPART B*Cleaning or Etching Rinse*

Pollutant or pollutant property	PSES	
	Maximum for any 1 day	Maximum for monthly average
mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched		
Chromium	0.61	0.25
Cyanide	0.41	0.17
Zinc	2.03	0.85
TTO	0.96
Oil and grease (alternate monitoring parameter)	73	36

SUBPART B*Cleaning or Etching Scrubber Liquor*

Pollutant or pollutant property	PSES	
	Maximum for any 1 day	Maximum for monthly average
mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched		
Chromium	0.85	0.35
Cyanide	0.56	0.23
Zinc	2.83	1.18
TTO	1.34
Oil and grease (alternate monitoring parameter)	100	50

[48 FR 49149, Oct. 24, 1983; 49 FR 11631, 11632, and 11633, Mar. 27, 1984, as amended at 53 FR 52369 and 52370, Dec. 27, 1988]

§ 467.26 Pretreatment standards for new sources.

Except as provided in § 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources. The mass of process wastewater pollutants from the core and ancillary operations introduced into a POTW shall not exceed the values set forth below:

Environmental Protection Agency
§ 467.26
SUBPART B
Core

Pollutant or pollutant property	PSNS	
	Maximum for any 1 day	Maximum for monthly average
mg/off-kg (lb/million off-lbs) of aluminum rolled with emulsions		
Chromium	0.048	0.020
Cyanide	0.026	0.011
Zinc	0.133	0.055
TTO	0.090
Oil and grease (alternate monitoring parameter) ...	1.30	1.30

SUBPART B
Cleaning or Etching Bath

Pollutant or pollutant property	PSNS	
	Maximum for any 1 day	Maximum for monthly average
mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched		
Chromium	0.067	0.027
Cyanide	0.036	0.015
Zinc	0.183	0.075
TTO	0.124
Oil and grease (alternate monitoring parameter)	1.79	1.79

SUBPART B
Direct Chill Casting Contact Cooling Water

Pollutant or pollutant property	PSNS	
	Maximum for any 1 day	Maximum for monthly average
mg/off-kg (lb/million off-lbs) of aluminum cast by semicontinuous methods		
Chromium	0.49	0.20
Cyanide	0.27	0.11
Zinc	1.36	0.56
TTO	0.92
Oil and grease (alternate monitoring parameter)	13.29	13.29

SUBPART B
Solution Heat Treatment Contact Cooling Water

Pollutant or pollutant property	PSNS	
	Maximum for any 1 day	Maximum for monthly average
mg/off-kg (lb/million off-lbs) of aluminum quenched		
Chromium	0.76	0.31
Cyanide	0.41	0.17
Zinc	2.08	0.86
TTO	1.41
Oil and grease (alternate monitoring parameter)	20.37	20.37

SUBPART B
Cleaning or Etching Rinse

Pollutant or pollutant property	PSNS	
	Maximum for any 1 day	Maximum for monthly average
mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched		
Chromium	0.52	0.21
Cyanide	0.28	0.11
Zinc	1.42	0.59
TTO	0.96
Oil and grease (alternate monitoring parameter)	13.91	13.91

SUBPART B
Cleaning or Etching Scrubber Liquor

Pollutant or pollutant property	PSNS	
	Maximum for any 1 day	Maximum for monthly average
mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched		
Chromium	0.72	0.29
Cyanide	0.39	0.16
Zinc	1.97	0.81
TTO	1.34
Oil and grease (alternate monitoring parameter)	19.33	19.33

[48 FR 49149, Oct. 24, 1983; 49 FR 11631 and 11632, Mar. 27, 1984]