

perchloroethylene and wastes that contain perchloroethylene in solvent tanks or solvent containers with no perceptible leaks.

(k) The owner or operator of a dry cleaning system shall inspect the following components weekly for perceptible leaks while the dry cleaning system is operating:

- (1) Hose and pipe connections, fittings, couplings, and valves;
- (2) Door gaskets and seatings;
- (3) Filter gaskets and seatings;
- (4) Pumps;
- (5) Solvent tanks and containers;
- (6) Water separators;
- (7) Muck cookers;
- (8) Stills;
- (9) Exhaust dampers;
- (10) Diverter valves; and
- (11) Cartridge filter housings.

(l) The owner or operator of a dry cleaning facility with a total facility consumption below the applicable consumption levels of § 63.320(d) or (e) shall inspect the components listed in paragraph (k) of this section biweekly for perceptible leaks while the dry cleaning system is operating.

(m) The owner or operator of a dry cleaning system shall repair all perceptible leaks detected under paragraph (k) of this section within 24 hours. If repair parts must be ordered, either a written or verbal order for those parts shall be initiated within 2 working days of detecting such a leak. Such repair parts shall be installed within 5 working days after receipt.

(n) If parameter values monitored under paragraphs (e), (f), or (g) of this section do not meet the values specified in § 63.323(a), (b), or (c), adjustments or repairs shall be made to the dry cleaning system or control device to meet those values. If repair parts must be ordered, either a written or verbal order for such parts shall be initiated within 2 working days of detecting such a parameter value. Such repair parts shall be installed within 5 working days after receipt.

[58 FR 49376, Sept. 22, 1993, as amended at 61 FR 49265, Sept. 19, 1996]

§ 63.323 Test methods and monitoring.

(a) When a refrigerated condenser is used to comply with § 63.322(a)(1) or (b)(1):

(1) The owner or operator shall measure the temperature of the air-perchloroethylene gas-vapor stream on the outlet side of the refrigerated condenser on a dry-to-dry machine, dryer, or reclaimer weekly with a temperature sensor to determine if it is equal to or less than 7.2 °C (45 °F). The temperature sensor shall be used according to the manufacturer's instructions and shall be designed to measure a temperature of 7.2 °C (45 °F) to an accuracy of ± 1.1 °C (± 2 °F).

(2) The owner or operator shall calculate the difference between the temperature of the air-perchloroethylene gas-vapor stream entering the refrigerated condenser on a washer and the temperature of the air-perchloroethylene gas-vapor stream exiting the refrigerated condenser on the washer weekly to determine that the difference is greater than or equal to 11.1 °C (20 °F).

(i) Measurements of the inlet and outlet streams shall be made with a temperature sensor. Each temperature sensor shall be used according to the manufacturer's instructions, and designed to measure at least a temperature range from 0 °C (32 °F) to 48.9 °C (120 °F) to an accuracy of ± 1.1 °C (± 2 °F).

(ii) The difference between the inlet and outlet temperatures shall be calculated weekly from the measured values.

(b) When a carbon adsorber is used to comply with § 63.322(a)(2) or exhaust is passed through a carbon adsorber immediately upon machine door opening to comply with § 63.322(b)(3), the owner or operator shall measure the concentration of perchloroethylene in the exhaust of the carbon adsorber weekly with a colorimetric detector tube, while the dry cleaning machine is venting to that carbon adsorber at the end of the last dry cleaning cycle prior to desorption of that carbon adsorber to determine that the perchloroethylene concentration in the exhaust is equal to or less than 100 parts per million by volume. The owner or operator shall:

(1) Use a colorimetric detector tube designed to measure a concentration of 100 parts per million by volume of perchloroethylene in air to an accuracy of ± 25 parts per million by volume; and

Environmental Protection Agency

§ 63.324

(2) Use the colorimetric detector tube according to the manufacturer's instructions; and

(3) Provide a sampling port for monitoring within the exhaust outlet of the carbon adsorber that is easily accessible and located at least 8 stack or duct diameters downstream from any flow disturbance such as a bend, expansion, contraction, or outlet; downstream from no other inlet; and 2 stack or duct diameters upstream from any flow disturbance such as a bend, expansion, contraction, inlet, or outlet.

(c) If the air-perchloroethylene gas-vapor stream is passed through a carbon adsorber prior to machine door opening to comply with §63.322(b)(3), the owner or operator of an affected facility shall measure the concentration of perchloroethylene in the dry cleaning machine drum at the end of the dry cleaning cycle weekly with a colorimetric detector tube to determine that the perchloroethylene concentration is equal to or less than 300 parts per million by volume. The owner or operator shall:

(1) Use a colorimetric detector tube designed to measure a concentration of 300 parts per million by volume of perchloroethylene in air to an accuracy of ± 75 parts per million by volume; and

(2) Use the colorimetric detector tube according to the manufacturer's instructions; and

(3) Conduct the weekly monitoring by inserting the colorimetric detector tube into the open space above the articles at the rear of the dry cleaning machine drum immediately upon opening the dry cleaning machine door.

(d) When calculating yearly perchloroethylene consumption for the purpose of demonstrating applicability according to §63.320, the owner or operator shall perform the following calculation on the first day of every month:

(1) Sum the volume of all perchloroethylene purchases made in each of the previous 12 months, as recorded in the log described in §63.324(d)(1).

(2) If no perchloroethylene purchases were made in a given month, then the perchloroethylene consumption for that month is zero gallons.

(3) The total sum calculated in paragraph (d) of this section is the yearly perchloroethylene consumption at the facility.

§63.324 Reporting and recordkeeping requirements.

(a) Each owner or operator of a dry cleaning facility shall notify the Administrator or delegated State authority in writing within 270 calendar days after September 23, 1993 (i.e., June 18, 1994) and provide the following information:

(1) The name and address of the owner or operator;

(2) The address (that is, physical location) of the dry cleaning facility;

(3) A brief description of the type of each dry cleaning machine at the dry cleaning facility;

(4) Documentation as described in §63.323(d) of the yearly perchloroethylene consumption at the dry cleaning facility for the previous year to demonstrate applicability according to §63.320; or an estimation of perchloroethylene consumption for the previous year to estimate applicability with §63.320; and

(5) A description of the type of control device(s) that will be used to achieve compliance with §63.322 (a) or (b) and whether the control device(s) is currently in use or will be purchased.

(6) Documentation to demonstrate to the Administrator's satisfaction that each room enclosure used to meet the requirements of §63.322(a)(3) meets the requirements of §63.322(a)(3) (i) and (ii).

(b) Each owner or operator of a dry cleaning facility shall submit to the Administrator or delegated State authority by registered mail on or before the 30th day following the compliance dates specified in §63.320 (b) or (c) or June 18, 1994, whichever is later, a notification of compliance status providing the following information and signed by a responsible official who shall certify its accuracy:

(1) The yearly perchloroethylene solvent consumption limit based upon the yearly solvent consumption calculated according to §63.323(d);

(2) Whether or not they are in compliance with each applicable requirement of §63.322; and