

(5) Each owner or operator using a control or recovery device shall keep the following records readily accessible:

(i) Continuous records of the equipment operating parameters specified to be monitored under § 63.497(a) or specified by the Administrator in accordance with § 63.497(b). For flares, the records specified in Table 3 of 40 CFR part 63, subpart G shall be maintained in place of continuous records.

(ii) Records of the daily average value of each continuously monitored parameter for each operating day, except as provided in paragraphs (d)(5)(ii)(D) and (d)(5)(ii)(E) of this section.

(A) The daily average shall be calculated as the average of all values for a monitored parameter recorded during the operating day, except as provided in paragraph (d)(5)(ii)(B) of this section. The average shall cover a 24-hour period if operation is continuous, or the number of hours of operation per operating day if operation is not continuous.

(B) Monitoring data recorded during periods of monitoring system breakdowns, repairs, calibration checks, and zero (low-level) and high-level adjustments shall not be included in computing the hourly or daily averages. In addition, monitoring data recorded during periods of non-operation of the EPPU (or specific portion thereof) resulting in cessation of organic HAP emissions or during periods of start-up, shutdown, or malfunction shall not be included in computing the hourly or daily averages. Records shall be kept of the times and durations of all such periods and any other periods of process or control device operation when monitors are not operating.

(C) The operating day shall be the period defined in the operating permit or the Notification of Compliance Status in § 63.506(e)(8) or (e)(5). It may be from midnight to midnight or another 24-hour period.

(D) If all recorded values for a monitored parameter during an operating day are below the maximum, or above the minimum, level established in the Notification of Compliance Status in § 63.506(e)(5) or in the operating permit, the owner or operator may record that

all values were below the maximum or above the minimum level, rather than calculating and recording a daily average for that operating day.

(E) For flares, records of the times and duration of all periods during which the pilot flame is absent shall be kept rather than daily averages. The records specified in this paragraph are not required during periods when emissions are not routed to the flare, or during startups, shutdowns, or malfunctions when the owner or operator complies with the applicable requirements of subpart A of this part, as directed by § 63.506(b)(1).

(iii) Hourly records of whether the flow indicator specified under § 63.497(d)(1) was operating and whether a diversion was detected at any time during the hour, as well as records of the times of all periods when the vent stream is diverted from the control device or the flow indicator is not operating.

(iv) Where a seal mechanism is used to comply with § 63.497(d)(2), hourly records of flow are not required.

(A) For compliance with § 63.497(d)(2), the owner or operator shall record whether the monthly visual inspection of the seals or closure mechanisms has been done, and shall record instances when the seal mechanism is broken, the bypass line damper or valve position has changed, or the key for a lock-and-key type configuration has been checked out, and records of any car-seal that has broken.

(B) [Reserved]

[62 FR 46925, Sept. 5, 1996, as amended at 65 FR 38068, June 19, 2000]

§ 63.499 Back-end process provisions—reporting.

(a) The owner or operator of an affected source with back-end process operations shall submit the information required in paragraphs (a)(1) through (a)(3) of this section, for each back-end process operation at the affected source, as part of the Notification of Compliance Status specified in § 63.506(e)(5).

(1) The type of elastomer product processed in the back-end operation.

(2) The type of process (solution process, emulsion process, etc.)

(3) If the back-end process operation is subject to an emission limitation in §63.494(a), whether compliance will be achieved by stripping technology, or by control or recovery devices.

(b) Each owner or operator of a back-end process operation using stripping to comply with an emission limitation in §63.494(a), and demonstrating compliance by stripper parameter monitoring, shall submit reports as specified in paragraphs (b)(1) and (b)(2) of this section.

(1) As part of the Notification of Compliance Status specified in §63.506(e)(5), the owner or operator shall submit the information specified in §63.498(c)(1).

(2) For organic HAP content/stripper monitoring parameter re-determinations, and the addition of new grades, the information specified in §63.498(c)(1) shall be submitted in the next periodic report specified in §63.506(e)(6).

(c) Each owner or operator of an affected source with a back-end process operation control or recovery device that shall comply with an emission limitation in §63.494(a) shall submit the information specified in paragraphs (c)(1) through (c)(3) of this section as part of the Notification of Compliance Status specified in §63.506(e)(5).

(1) The residual organic HAP content, adjusted for the control or recovery device emission reduction, determined in accordance with §63.496(c)(1), for each test run in the compliance determination.

(2) The operating parameter level established in accordance with §63.497(c), along with supporting documentation.

(3) The information specified in paragraphs (c)(3)(i) when using a flare, and the information specified in paragraph (c)(3)(ii) of this section when using a boiler or process heater.

(i) The flare design (*i.e.*, steam-assisted, air-assisted, or non-assisted); all visible emission readings, heat content determinations, flow rate measurements, and exit velocity determinations made during the compliance determination; and all periods during the compliance determination when the pilot flame is absent.

(ii) A description of the location at which the vent stream is introduced into the boiler or process heater.

(d) Whenever a process change, as defined in §63.496(d), is made that causes the redetermination of the compliance status for the back-end process operations, the owner or operator shall submit a report within 180 days after the process change as specified in §63.506(e)(7)(iii). The report shall include:

(1) A description of the process change;

(2) The results of the redetermination of the compliance status, determined in accordance with §63.496(b), and recorded in accordance with §63.498(d)(1), and

(3) Documentation of the re-establishment of a parameter level for the control or recovery device, defined as either a maximum or minimum operating parameter, that indicates proper operation of the control or recovery device, in accordance with §63.497(c) and recorded in accordance with §63.498(d)(2).

(e) If an owner or operator uses a control or recovery device other than those listed in §63.497(a) or requests approval to monitor a parameter other than those specified in §63.497(a), the owner or operator shall submit a description of planned reporting and recordkeeping procedures as required under §63.506(e)(3) or (e)(8). The Administrator will specify appropriate reporting and recordkeeping requirements as part of the review of the Precompliance Report or Operating Permit application.

[62 FR 46925, Sept. 5, 1996, as amended at 65 FR 38068, June 19, 2000]

§ 63.500 Back-end process provisions—carbon disulfide limitations for styrene butadiene rubber by emulsion processes.

(a) Owners or operators of sources subject to this subpart producing styrene butadiene rubber using an emulsion process shall operate the process such that the carbon disulfide concentration in each crumb dryer exhausts shall not exceed 45 ppmv.

(1) The owner or operator shall develop standard operating procedures for the addition of sulfur containing