

**Environmental Protection Agency**

**§ 63.901**

General provisions reference	Summary of requirements	Applies to subpart MM	Explanation
63.10(d)(5) .....	Periodic and immediate start-up, shutdown, and malfunction reports.	Yes.	The use of flares to meet the standards in subpart MM is not anticipated.
63.10(e) .....	Additional reporting requirements for sources with CMS.	Yes.	
63.10(f) .....	Waiver of recordkeeping and reporting requirements.	Yes.	
63.11 .....	Control device requirements for flares.	No .....	
63.12 .....	State authority and delegations.	Yes.	
63.13 .....	Addresses of State air pollution control agencies and EPA Regional Offices.	Yes.	
63.14 .....	Incorporations by reference ....	Yes.	
63.15 .....	Availability of information and confidentiality.	Yes.	

[66 FR 3193, Jan. 12, 2001, as amended at 66 FR 16408, Mar. 26, 2001; 69 FR 25323, May 6, 2004]

**Subpart OO—National Emission Standards for Tanks—Level 1**

SOURCE: 61 FR 34184, July 1, 1996, unless otherwise noted.

**§ 63.900 Applicability.**

The provisions of this subpart apply to the control of air emissions from tanks for which another subpart of 40 CFR parts 60, 61, or 63 references the use of this subpart for such air emission control. These air emission standards for tanks are placed here for administrative convenience and only apply to those owners and operators of facilities subject to the other subparts that reference this subpart. The provisions of 40 CFR part 63, subpart A—General Provisions do not apply to this subpart except as noted in the subpart that references this subpart.

**§ 63.901 Definitions.**

All terms used in this subpart shall have the meaning given to them in the Act and in this section. If a term is defined in both this section and in another subpart that references the use of this subpart, then the definition in this subpart shall take precedence when implementing this subpart.

*Closure device* means a cap, hatch, lid, plug, seal, valve, or other type of fitting that, when the device is secured in the closed position, prevents or reduces air emissions to the atmosphere by blocking an opening in a fixed roof.

Closure devices include devices that are detachable from the cover (e.g., a sampling port cap), manually operated (e.g., a hinged access lid or hatch), or automatically operated (e.g., a spring-loaded pressure relief valve).

*Fixed roof* means a cover that is mounted on a tank in a stationary position and does not move with fluctuations in the level of the liquid managed in the tank.

*No detectable organic emissions* means no escape of organics to the atmosphere as determined using the procedure specified in §63.905(a) of this subpart.

*Regulated-material* means the material (e.g. waste, wastewater, off-site material) required to be managed in tanks using air emission controls in accordance with the standards specified in this subpart.

*Safety device* means a closure device such as a pressure relief valve, frangible disc, fusible plug, or any other type of device which functions to prevent physical damage or permanent deformation to equipment by venting gases or vapors during unsafe conditions resulting from an unplanned, accidental, or emergency event. For the purpose of this subpart, a safety device is not used for routine venting of gases or vapors from the vapor headspace underneath a cover such as during filling of the unit or to adjust the pressure in this vapor headspace in response to