

each single surface sample in the composite. The weighted arithmetic mean is obtained by summing, for all samples, the product of the sample's result multiplied by the number of subsamples in the sample, and dividing the sum by the total number of subsamples contained in all samples. For example, the weighted arithmetic mean of a single surface sample containing 60 µg/ft<sup>2</sup>, a composite sample (three subsamples) containing 100 µg/ft<sup>2</sup>, and a composite sample (4 subsamples) containing 110 µg/ft<sup>2</sup> is 100 µg/ft<sup>2</sup>. This result is based on the equation  $[60+(3*100)+(4*110)]/(1+3+4)$ .

*Window trough* means, for a typical double-hung window, the portion of the exterior window sill between the interior window sill (or stool) and the frame of the storm window. If there is no storm window, the window trough is the area that receives both the upper and lower window sashes when they are both lowered. The window trough is sometimes referred to as the window "well."

*Wipe sample* means a sample collected by wiping a representative surface of known area, as determined by ASTM E1728, "Standard Practice for Field Collection of Settled Dust Samples Using Wipe Sampling Methods for Lead Determination by Atomic Spectrometry Techniques, or equivalent method, with an acceptable wipe material as defined in ASTM E 1792, "Standard Specification for Wipe Sampling Materials for Lead in Surface Dust."

#### § 745.65 Lead-based paint hazards.

(a) *Paint-lead hazard*. A paint-lead hazard is any of the following:

(1) Any lead-based paint on a friction surface that is subject to abrasion and where the lead dust levels on the nearest horizontal surface underneath the friction surface (e.g., the window sill, or floor) are equal to or greater than the dust-lead hazard levels identified in paragraph (b) of this section.

(2) Any damaged or otherwise deteriorated lead-based paint on an impact surface that is caused by impact from a related building component (such as a door knob that knocks into a wall or a door that knocks against its door frame.

(3) Any chewable lead-based painted surface on which there is evidence of teeth marks.

(4) Any other deteriorated lead-based paint in any residential building or child-occupied facility or on the exterior of any residential building or child-occupied facility.

(b) *Dust-lead hazard*. A dust-lead hazard is surface dust in a residential dwelling or child-occupied facility that contains a mass-per-area concentration of lead equal to or exceeding 40 µg/ft<sup>2</sup> on floors or 250 µg/ft<sup>2</sup> on interior window sills based on wipe samples.

(c) *Soil-lead hazard*. A soil-lead hazard is bare soil on residential real property or on the property of a child-occupied facility that contains total lead equal to or exceeding 400 parts per million (µg/g) in a play area or average of 1,200 parts per million of bare soil in the rest of the yard based on soil samples.

(d) *Work practice requirements*. Applicable certification, occupant protection, and clearance requirements and work practice standards are found in regulations issued by EPA at 40 CFR part 745, subpart L and in regulations issued by the Department of Housing and Urban Development (HUD) at 24 CFR part 35, subpart R. The work practice standards in those regulations do not apply when treating paint-lead hazards of less than:

(1) Two square feet of deteriorated lead-based paint per room or equivalent,

(2) Twenty square feet of deteriorated paint on the exterior building, or

(3) Ten percent of the total surface area of deteriorated paint on an interior or exterior type of component with a small surface area.

### Subpart E—Residential Property Renovation

SOURCE: 63 FR 29919, June 1, 1998, unless otherwise noted.

#### § 745.80 Purpose.

This subpart contains regulations developed under Title IV (15 U.S.C. 2681-2692) of the Toxic Substances Control Act and applies to all renovations of target housing performed for compensation. The purpose of this subpart is to require each person who performs

## Environmental Protection Agency

## § 745.84

a renovation of target housing for compensation to provide a lead hazard information pamphlet to the owner and occupant of such housing prior to commencing the renovation.

### § 745.81 Effective date.

The requirements in this subpart shall take effect on June 1, 1999.

### § 745.82 Applicability.

(a) Except as provided in paragraph (b) of this section, this subpart applies to all renovations of target housing performed for compensation.

(b) This subpart does not apply to renovation activities that are limited to the following:

(1) Minor repair and maintenance activities (including minor electrical work and plumbing) that disrupt 2 square feet or less of painted surface per component.

(2) Emergency renovation operations.

(3) Renovations in target housing in which a written determination has been made by an inspector (certified pursuant to either Federal regulations at § 745.226 or a State or Tribal certification program authorized pursuant to § 745.324) that the components affected by the renovation are free of paint or other surface coatings that contain lead equal to or in excess of 1.0 milligram per square centimeter or 0.5 percent by weight, where the renovator has obtained a copy of the determination.

### § 745.83 Definitions.

For purposes of this part, the definitions in § 745.103 as well as the following definitions apply:

*Administrator* means the Administrator of the Environmental Protection Agency.

*Emergency renovation operations* means renovation activities, such as operations necessitated by non-routine failures of equipment, that were not planned but result from a sudden, unexpected event that, if not immediately attended to, presents a safety or public health hazard, or threatens equipment and/or property with significant damage.

*Multi-family housing* means a housing property consisting of more than four dwelling units.

*Pamphlet* means the EPA pamphlet developed under section 406(a) of TSCA for use in complying with this and other rulemakings under Title IV of TSCA and the Residential Lead-Based Paint Hazard Reduction Act, or any State or Tribal pamphlet approved by EPA pursuant to 40 CFR 745.326 that is developed for the same purpose. This includes reproductions of the pamphlet when copied in full and without revision or deletion of material from the pamphlet (except for the addition or revision of State or local sources of information).

*Person* means any natural or judicial person including any individual, corporation, partnership, or association; any Indian Tribe, State, or political subdivision thereof; any interstate body; and any department, agency, or instrumentality of the Federal Government.

*Renovation* means the modification of any existing structure, or portion thereof, that results in the disturbance of painted surfaces, unless that activity is performed as part of an abatement as defined by this part (40 CFR 745.223). The term renovation includes (but is not limited to): the removal or modification of painted surfaces or painted components (e.g., modification of painted doors, surface preparation activity (such as sanding, scraping, or other such activities that may generate paint dust)); the removal of large structures (e.g., walls, ceiling, large surface replastering, major re-plumbing); and window replacement.

*Renovator* means any person who performs for compensation a renovation.

### § 745.84 Confidential business information.

(a) Those who assert a confidentiality claim for submitted information must provide EPA with two copies of their submission. The first copy must be complete and contain all information being claimed as confidential. The second copy must contain only information not claimed as confidential. EPA will place the second copy of the submission in the public file.

(b) EPA will disclose information subject to a claim of confidentiality only to the extent permitted by section 14 of TSCA and 40 CFR part 2, subpart