

§ 174.360

46 CFR Ch. I (10-1-04 Edition)

(ii) In the absence of a contract, the construction work of which is begun on or after August 1, 1992; or

(iii) Which is completed on or after February 1, 1997.

§ 174.360 Calculations.

Each ship to which this subpart applies, must meet the minimum standard of subdivision and damage stability required for that ship by the International Convention for the Safety of Life at Sea, 1974, as amended, chapter

II-1, part B-1. Compliance with the applicable requirements must be demonstrated by calculations and reflected in information on loading restrictions, such as a maximum height of the center of gravity (KG) or minimum metacentric height (GM) curve that is part of the stability information required by §170.110 of this chapter and Regulation 25-8 of The International Convention for the Safety of Life at Sea, 1974, as amended, chapter II-1, part B-1.

INDEX

SUBCHAPTER S—SUBDIVISION AND STABILITY

EDITORIAL NOTE: This listing is provided for informational purposes only. It is compiled and kept current by the U.S. Coast Guard, Department of Homeland Security. This index is updated as of October 1, 2003.

Part, Subpart, or Section

A

Addresses:

Material incorporated by reference	170.015
Merchant marine technical offices	170.100
Aft peak bulkhead, passenger vessels	171.090
Alterations	170.001(b), 170.005
Auxiliary sailing vessels:	
Defined	170.055(a)
Large passenger vessels	171.045
Small passenger vessels	170.055, 171.010
Weather criterion for	170.160

B

Ballast, fixed. (See Fixed ballast)

Barges:

Deck cargo	Part 174, Subpart B
Definitions	170.055 (b) and (q)
Large passenger	171.045
Oceanographic research	173.070
Tank. (See Tank barges)	
Weather criterion for	170.160
Bulk cargo vessels, special requirements for	Part 172
Buoyancy:	
Air tanks	171.070(d), 171.095(c)
Foam flotation material	170.245
Internal	171.070(d), 171.095(c)
Standards of flooding	171.017

C

Calculations:

Samples of, in stability booklet	170.110(d)
Stability text results	170.175(a)
Submittal of	170.090
Catamarans	171.057
Center of gravity:	
Determination of	Part 170, Subpart F
Estimated position on tank vessels	170.200
In stability booklet	170.110(d)
Subchapter O barges	172.090(b)
Tanks	170.075(a)(5)

46 CFR Ch. I (10–1–04 Edition)

Virtual increase of Part 170, Subpart I
Collision bulkhead:
 Oceanographic research vessels 173.075, 173.085
 Passenger vessels 171.060, 171.065, 171.070, 171.085
Consumable liquids: Effect on stability calculations 170.285, 170.290
Cranes:
 Data required 170.095
 Requirements for vessels with Part 173, Subpart B
Cross curves, required 170.090(b)(3)
Cross-flooding:
 Liquefied gas carriers, system standards 172.195(g)
 Passenger vessels, system standards 171.080(e)
 Subchapter O tankships, system standards 172.150(g)

D

Damage stability calculations:
 Liquefied gas carriers, local damage 172.205
 Liquefied gas carriers, major damage 172.170
 MODU's, standards for 174.065
 Nautical school ships, standards for 173.055, 173.080
 Oceanographic research vessels, standards for 173.080
 Passenger vessels:
 Cockpits 171.145(e)(3)
 Types I and II 171.080
 Type III 171.082
 Well decks 171.150(b)(2)
 Subchapter D tank barges carrying cargoes other than oil 172.050
 Subchapter O barges, standards for 172.103
 Subchapter O tankships, standards for 172.133
Dangerous cargoes Part 172, Subparts E and F
Dead covers:
 Oceanographic research vessels, required 173.085(k)
 Passenger vessels, required 171.117, 171.119(a)(2), 171.122(g)
Deadweight surveys 170.175(c)
Deck cargo barges. (See Barges)
Definitions:
 Concerning a vessel 170.055
 General terms 170.050
 Pertaining to lifting 173.010
 Pertaining to liquefied gas carriers 172.160
 Pertaining to MODU's 174.035
 Pertaining to passenger vessels 171.010
 Pertaining to Subchapter O tankships 172.127
Discontinuous bulkhead deck, passenger vessels 171.015(c)
Discontinuous weather deck 170.170(b)
Double bottoms, passenger vessels:
 Manholes in 171.108
 Permeability of 171.066(b)(4)
 Required 171.105
 Watertight floors in 171.109
 Wells in 171.106
Downflooding:
 Angle 170.055(g)
 Deck cargo barges 174.015
 Defined (except MODU's) 170.055(e)
 Lifting vessels 173.020(b)
 Liquefied gas carriers 172.195
 Mobile offshore drilling units (MODU's):

Subchapter S Index

Considered.....	174.045
Defined.....	174.035(b)
Oil tankers.....	170.055(p)
Sailing passenger vessels.....	171.055
Subchapter O barges.....	172.090
Subchapter O tankships.....	172.150
Tugboats and towboats.....	174.145
Vessels of unusual proportion and form.....	170.173
Vessels which tow.....	173.095
Draft marks.....	170.075(a)(6), 170.180(e)
Drainage of weather decks.....	Part 171, Subpart H
Deck cargo barges.....	Part 174, Subpart B

E

Equalization. (See Cross-flooding)	
Equivalent plane bulkhead, passenger vessels:	
Defined.....	171.010(c)
Required:	
Type I subdivision.....	171.067(f)
Type II subdivision.....	171.073(c)
Equivalentents.....	170.010
Estimated lightweight vertical center of gravity.....	170.200
Existing vessels.....	170.001(b)

F

Ferry:	
Collision bulkheads.....	171.060(d)
Defined.....	171.010(d)
Fixed ballast.....	170.110(d)(14), 170.235
Floodable length:	
Curves required.....	170.090(b)(4)
Defined.....	171.010(f)
Passenger vessels:	
Standards, Type I.....	171.065
Standards, Type II.....	171.070
Standards, Type III.....	171.075
Floors, watertight—in double bottoms.....	171.109
Foam flotation.....	170.245, 171.070(d), 171.095(c)
Foreign vessels.....	170.001(a)(2)
Freeboard: Allowable heeling limits, general.....	170.170(a)
Freeing ports:	
Minimum Area.....	171.150
Required.....	171.135
Free surface:	
Instructions concerning:	
Counterballasting.....	170.125(b)(1)
Stability booklet.....	170.110(d)(6)
Subchapter O tank barges, assumption.....	172.087(b)
Treatment of, general.....	Part 170, Subpart I

G

Grain in bulk.....	Part 172, Subpart B
“Grandfathering”.....	170.001(b)

46 CFR Ch. I (10-1-04 Edition)

H

Hazardous liquids Part 172, Subparts E, F
Hopper barges:
 Subchapter D cargoes other than oil 172.050
 Subchapter O cargoes 172.100, 172.110
Hydrostatic curves (curves of form), required 170.075(a)(3)

I

Inclining experiments. (See Stability test)
Incorporation by reference:
 General 170.015
 IMO Resolution A.265(VIII) 170.135, 171.075, 171.082
 MIL-P-21929B 170.245(b)(9)
Intact stability:
 Deck cargo barges 174.015, 174.020
 Large passenger vessels:
 Catamarans 171.057
 Passenger heel 171.050
 Sailing 171.055
 Lifting vessels 173.020, 173.025
 Liquefied gas carriers 172.165
 Mobile offshore drilling units (MODU's) 174.045
 Passenger vessels:
 Cockpits 171.145(e)(1)
 Well decks 171.150(b)(2)
 Subchapter O barges 172.090, 172.095
 Tugboats and Towboats 174.145
 Vessels of unusual proportion and form 170.170(d), 170.173
 Weather Criterion 170.160, 170.170
International voyage:
 Passenger vessels:
 Aft peak bulkhead required 171.090(a)
 Defined 171.010(h)
 Double bottoms required for 171.105(a)
 Shaft tunnels 171.100(a)
 Special considerations 171.068
 Standards 171.045
 Subdivision requirements 170.265(d)(1)
 Watertight door requirements 170.265(d)(1)

L

Large Passenger vessels Part 171, Subpart C
Lifting:
 Data submittal requirements 170.095
 Operating information requirements 170.125
 Standards Part 173, Subpart B
Lightweight:
 Defined 170.055(j)
 Information required, stability booklet 170.110(d)(1)
 Determination of Part 170, Subpart F
Lines drawing required 170.075(a)(2), 170.180(a)
Liquefied flammable gas, barges Part 172, Subpart C
Liquefied gas carriers Part 172, Subpart G
LNG Carriers. (See Liquefied gas carriers)
Load line:
 Certificate stability information on 170.110(e), 170.120(b)

Subchapter S Index

Length, defined.....	170.055(h)(5)
Locks required:	
Cargo space watertight doors.....	170.275(b)
Port lights below the bulkhead deck.....	171.116(f)(4)

M

Machinery space bulkhead, passenger vessels.....	171.095
Main transverse watertight bulkhead.....	170.055(k)
Manholes, passenger vessels:	
Double bottoms.....	171.108
Prohibited locations.....	171.111(h)
Margin line:	
Passenger vessels:	
Air tankage or internal buoyancy.....	171.070(d)(2)
Dead covers required on port lights, below.....	171.117(a)
Location of.....	171.015
Location of openings.....	171.111(f), (g)
Openings in trunks.....	171.113(c)(2)
Stepped bulkheads.....	171.067(b)(3)
Submergence of.....	171.017, 171.080(d)(3), 171.100(b)
Volume below.....	Tables 171.065(a), 171.066, 171.068
Volume of passenger spaces above.....	171.065(b)
Watertight integrity above.....	Part 171, Subpart G
Test head:	
Form flotation material.....	170.245(b)(3)
Watertight doors.....	170.270(b)
Military specifications, MIL-P-21929B.....	170.015(b), 170.245(b)
Mobile offshore drilling units (MODU's):	
Stability information required.....	170.110(a)
Standards for.....	174.005(b), Part 174, Subpart C

N

Nautical school ships, standards.....	171.001(b), 173.001(b), Part 173, Subpart C
---------------------------------------	---

O

Oceanographic vessel, standards.....	171.001(b), 173.001(c), Part 173, Subpart D
Oil in bulk, standards for vessels carrying.....	172.005(c), Part 172, Subpart D
Openings:	
Closed by weathertight covers:	
Liquefied gas carriers.....	172.195
Mobile offshore drilling units.....	174.045(c)
Oil tankers.....	172.065(g)
Subchapter O tankships.....	172.150
Downflooding through:	
General.....	170.055(e), (f)
Mobile offshore drilling units.....	174.035(b), 174.065(a)
Subchapter O barges.....	172.090(d)
Sailing passenger vessels.....	171.055(e)
Mobile offshore drilling units:	
Closures for.....	174.100
Watertight, closed automatically.....	174.015(b)
Watertight, closed rapidly.....	174.045
Passenger vessels:	
Cockpit openings.....	171.145(a)(2)
Collision bulkhead.....	171.085
Special consideration, exposed weather decks.....	171.122(f)

46 CFR Ch. I (10–1–04 Edition)

Vessel sides.....Part 171, Subpart F
Watertight bulkheads.....Part 171, Subpart E
Watertight, closed automatically:
Mobile offshore drilling units174.015(b)
Towing vessels173.095(e)

P

Passenger vessels, standards..... Part 171
Penetrations (See Openings)
Permeability
Calculation of, Type I subdivision 171.066
Damage stability:
Liquefied gas carriers.....172.185
Mobile offshore drilling units174.090
Oil tankers.....172.065(f)
Passenger vessels171.080(c)
Subchapter O tankships172.140
Defined 170.055(m)
Uniform average permeability:
Type I subdivision Table 171.068
Type II subdivision..... 171.072
Plans:
Approval:
GeneralPart 170, Subpart C, 170.180
Required.....170.075
Specific170.093
Submittal of 170.100, 170.180
Port lights 171.116

R

Repairs:
General 170.001(b), 170.005
In way of fixed ballast 170.235(b)
Roll stabilization tanks 170.295
Rudders, towline pull criterion..... 173.095

S

Sailing vessels:
Defined..... 170.055(a), (1)
Intact stability standards:
Catamarans171.057
Large passenger vessels.....171.055
Weather criterion 170.160
School ships (See Nautical school ships)
Shaft power, towline pull criterion 173.095
Shaft tunnels:
On passenger vessels 171.100, 171.106(c)
Watertight doors in 170.260(d)
Short international voyages, vessels on:
Class 3 doors 170.265(d)(1)
Defined 171.010(m)
Double bottoms not required..... 171.105(h)(2)
Special considerations 171.068
Side ports, passenger vessels 171.118
Sister vessel, stability test dispensed with 170.175(c)

Subchapter S Index

Small passenger vessels, standards.....	Part 171
Stability booklets:	
Contents of	170.110
Lifting vessels, additional information	170.125
Submission and approval required.....	170.080
Vessels with Type III subdivision, additional information.....	170.135
Stability letters:	
In lieu of stability booklet	170.110(e)
Required	170.120
Stability test:	
General	170.175
Information required before test	170.085
Plans and information required at test	170.180
Preparations for test	170.185
Test procedure, modification of.....	170.190
Stern tubes, passenger vessels	171.100
Subdivision:	
Oceanographic vessels	173.075, 173.085
Passenger vessels:	
Additional requirements	Part 171, Subpart D
Calculations:	
Type I.....	171.065, 171.066, 171.067, 171.068
Type II.....	171.070, 171.072, 171.073
Type III	171.075
Requirements, large passenger vessels	171.060
Trunks, effect of	171.113(b)(3)
Subdivision load line (draft), passenger vessels:	
Cockpits	171.145(e), (f)
Dead cover locations	171.117(b)
Deepest, defined.....	171.010(b)
Openings in hull, small passenger vessels	171.119(a)
Port light locations	171.116(b)(2)
Transverse damage extent, relationship to.....	171.065(h)(2), Table 171.080(a)
Ventilators and side port locations	171.118(c)
Superstructures:	
Buoyancy of:	
Liquefied gas carriers	172.195(e)
Oil tankers.....	172.065(h)
Subchapter O tankships	172.150
Integrity of, mobile offshore drilling units	174.100(b)
Points of downflooding in:	
General.....	170.055(e)
Mobile offshore drilling units	174.035(b)(1)
Port lights in, oceanographic vessels.....	173.085(k)

T

Tank barge:	
Assumed center of gravity for	170.200(b)(2)
Carrying oil in bulk	Part 172, Subpart D
Carrying Subchapter D cargoes other than oil	Part 172, Subpart C
Carrying Subchapter O cargoes.....	Part 172, Subpart E
Defined	170.055(q)
Tank vessel:	
Assumed center of gravity.....	170.200
Defined	170.055(p)
Standards for	Part 172, Subparts C, D, E, F, G
Tests:	

46 CFR Ch. I (10–1–04 Edition)

Foam flotation material..... 170.245
Stability..... 170.085, Part 170, Subpart F
Watertight doors..... 170.270
Towboats. (See Towing)
Towing, standards for... 173.001(d), Part 173, Subpart E, 174.005(d), Part 174, Subpart E
Towline pull criterion..... 173.095
Tugboats. (See Towing)

U

Unusual proportion and form, vessels of..... 170.173

V

Ventilators, automatic—passenger vessels..... 171.118

W

Watertight bulkheads:
Doors, standards for..... 171.122, 171.124, Part 170, Subpart H
Liquefied gas carriers 172.175, 172.195
Mobile offshore drilling units 174.080, 174.085
Oceanographic vessels, ducts through 173.085(o)
Oil tankers..... 172.065
Passenger vessels:
Above weatherdeck 171.122
Large passenger vessels, requirements 171.065, 171.067, 171.068, 171.070, 171.073
Machinery space..... 171.095
Penetrations of.....Part 171, Subpart E
Watertight floors 171.109
Subchapter D barges not carrying oil..... 172.050
Subchapter O barges 172.104
Subchapter O tankships..... 172.133(d), 172.150
Watertight doors. (See Watertight bulkheads)
Weather criterion..... Part 170, Subpart E
Wind heeling moment: MODU's..... 174.035(b)(2), 174.045, 174.055, 174.065(a)(2),
174.100(d)(2)