

§ 27.301

46 CFR Ch. I (10–1–04 Edition)

with any of the following standards for fuel systems rather than with those of paragraph (e) of this section:

- (1) ABYC H-33 (incorporated by reference in § 27.102).
- (2) Chapter 5 of NFPA 302 (incorporated by reference in § 27.102).
- (3) 33 CFR chapter I, subchapter S (Boating Safety).

Subpart C—Fire-Suppression Equipment for Towing Vessels

§ 27.301 What are the requirements for fire pumps, fire mains, and fire hoses on towing vessels?

By April 29, 2005, you must provide for your towing vessel either a self-priming, power-driven, fixed fire-pump, a fire main, and hoses and nozzles in accordance with paragraphs (a) through (c) of this section; or a portable pump, and hoses and nozzles, in accordance with paragraphs (d) and (e) of this section.

(a) The fixed fire-pump must be capable of—

(1) Delivering water simultaneously from the two highest hydrants, or from both branches of the fitting if the highest hydrant has a Siamese fitting, at a pitot-tube pressure of at least 344 kPa (50 psi) and a flow rate of at least 300 lpm (80 gpm); and

(2) Being energized remotely from a safe place outside the engine room and from the pump.

(b) All valves necessary for the operation of the fire main must be kept in the open position or must be capable of operation from the same place where the remote fire pump control is located.

(c) The fire main must have a sufficient number of fire hydrants with attached hose to reach any part of the machinery space using a single length of fire hose.

(d) The hose must be lined commercial fire-hose, at least 40mm (1.5 inches) in diameter, 15 meters (50 feet) in length, and fitted with a nozzle made of corrosion-resistant material capable of providing a solid stream and a spray pattern.

(e) The portable fire pump must be self-priming and power-driven, with—

(1) A minimum capacity of at least 300 lpm (80 gpm) at a discharge gauge

pressure of not less than 414 kPa (60 psi), measured at the pump discharge;

(2) A sufficient amount of lined commercial fire hose at least 40mm (1.5 inches) in diameter and 15 meters (50 feet) in length, immediately available to attach to it so that a stream of water will reach any part of the vessel; and

(3) A nozzle made of corrosion-resistant material capable of providing a solid stream and a spray pattern.

(f) You must stow the pump with its hose and nozzle outside of the machinery space.

§ 27.303 What are the requirements for fire-extinguishing equipment on towing vessels in inland service, and on towing vessels in ocean or coastal service whose construction was contracted for before August 27, 2003?

You must carry on your towing vessel both—

(a) The minimum number of hand-portable fire extinguishers required by subpart 25.30 of this part; and

(b) By April 29, 2005, either—

(1) An approved B-V semi-portable fire-extinguishing system to protect the engine room; or

(2) A fixed fire-extinguishing system installed to protect the engine room of the vessel.

§ 27.305 What are the requirements for fire-extinguishing equipment on towing vessels in ocean or coastal service whose construction was contracted for on or after August 27, 2003?

(a) You must carry on your towing vessel both—

(1) The minimum number of hand-portable fire extinguishers required by subpart 25.30 of this part; and

(2) An approved B-V semi-portable fire-extinguishing system to protect the engine room.

(b) You must have a fixed fire-extinguishing system installed to protect the engine room of the vessel.

(c) This section does not apply to any towing vessel pushing a barge ahead, or hauling a barge alongside, when the barge's coastwise or Great Lakes route is restricted (as indicated on its certificate of inspection), so that the barge may operate "in fair weather only,

within 12 miles of shore,” or with words to that effect.

PART 28—REQUIREMENTS FOR COMMERCIAL FISHING INDUSTRY VESSELS

Subpart A—General Provisions

- Sec.
 28.10 Authority.
 28.20 OMB control numbers.
 28.30 Applicability.
 28.40 Incorporation by reference.
 28.50 Definition of terms used in this part.
 28.60 Exemption letter.
 28.65 Termination of unsafe operations.
 28.70 Approved equipment and material.
 28.73 Accepted organizations.
 28.76 Similarly qualified organizations.
 28.80 Report of casualty.
 28.90 Report of injury.
 28.95 Right of appeal.

Subpart B—Requirements for All Vessels

- 28.100 Applicability.
 28.105 Lifesaving equipment—general requirements.
 28.110 Life preservers or other personal flotation devices.
 28.115 Ring life buoys.
 28.120 Survival craft.
 28.125 Stowage of survival craft.
 28.130 Survival craft equipment.
 28.135 Lifesaving equipment markings.
 28.140 Operational readiness, maintenance, and inspection of lifesaving equipment.
 28.145 Distress signals.
 28.150 Emergency Position Indicating Radio Beacons (EPIRBs).
 28.155 Excess fire detection and protection equipment.
 28.160 Portable fire extinguishers.
 28.165 Injury placard.

Subpart C—Requirements for Documented Vessels That Operate Beyond the Boundary Lines or With More Than 16 Individuals On Board, or for Fish Tender Vessels Engaged in the Aleutian Trade

- 28.200 Applicability.
 28.205 Fireman's outfit and self-contained breathing apparatus.
 28.210 First aid equipment and training.
 28.215 Guards for exposed hazards.
 28.225 Navigational information.
 28.230 Compasses.
 28.235 Anchors and radar reflectors.
 28.240 General alarm system.
 28.245 Communication equipment.
 28.250 High water alarms.
 28.255 Bilge pumps, bilge piping, and dewatering systems.
 28.260 Electronic position fixing devices.

- 28.265 Emergency instructions.
 28.270 Instruction, drills, and safety orientation.
 28.275 Acceptance criteria for instructors and course curricula.

Subpart D—Requirements for Vessels Which Have Their Keel Laid or Are at a Similar Stage of Construction on or After or Which Undergo a Major Conversion Completed on or After September 15, 1991, and That Operate With More Than 16 Individuals on Board

- 28.300 Applicability and general requirements.
 28.305 Lifesaving and signaling equipment.
 28.310 Launching of survival craft.
 28.315 Fire pumps, fire mains, fire hydrants, and fire hoses.
 28.320 Fixed gas fire extinguishing systems.
 28.325 Fire detection systems.
 28.330 Galley hood and other fire protection equipment.
 28.335 Fuel systems.
 28.340 Ventilation of enclosed engine and fuel tank spaces.
 28.345 Electrical standards for vessels less than 79 feet (24 meters) in length.
 28.350 General requirements for electrical systems.
 28.355 Main source of electrical power.
 28.360 Electrical distribution systems.
 28.365 Overcurrent protection and switched circuits.
 28.370 Wiring methods and materials.
 28.375 Emergency source of electrical power.
 28.380 General structural fire protection.
 28.385 Structural fire protection for vessels that operate with more than 49 individuals on board.
 28.390 Means of escape.
 28.395 Embarkation stations.
 28.400 Radar and depth sounding devices.
 28.405 Hydraulic equipment.
 28.410 Deck rails, lifelines, storm rails, and hand grabs.

Subpart E—Stability

- 28.500 Applicability.
 28.501 Substantial alterations.
 28.505 Vessel owner's responsibility.
 28.510 Definitions of stability terms.
 28.515 Submergence test as an alternative to stability calculations.
 28.520–28.525 [Reserved]
 28.530 Stability instructions.
 28.535 Inclining test.
 28.540 Free surface.
 28.545 Intact stability when using lifting gear.
 28.550 Icing.
 28.555 Freeing ports.
 28.560 Watertight and weathertight integrity.
 28.565 Water on deck.