

to the requirements of part 56 of subchapter F (Marine Engineering) of this chapter.

(c) Piping shall be provided with adequate support to take the weight of the piping off valves and fittings and to prevent excessive vibration and stresses on tank connections.

(d) For nonpressure vessel type tanks, the cargo handling arrangements and piping shall provide for emptying of a damaged tank, including cargo contained by a secondary barrier.

[CGFR 66-33, 31 FR 15269, Dec. 6, 1966, as amended by CGFR 68-82, 33 FR 18807, Dec. 18, 1968]

**§ 38.10-15 Safety relief valves—TB/ALL.**

(a) Each tank shall be fitted with or (subject to approval by the Commandant) connected to one or more safety relief valves designed, constructed and flow tested for capacity in conformance with subpart 162.017 or 162.018 of subchapter Q (Specifications) of this chapter.

(b) Safety relief valves conforming to subpart 162.017 of subchapter Q (Specifications) of this chapter may be used on tanks for a maximum pressure of 10 pounds per square inch gage. Safety relief valves conforming to subpart 162.018 of subchapter Q (Specifications) of this chapter may be used for any pressure.

(c) The safety relief valves shall have a combined relieving capacity to discharge the greater of the following with not more than 20 percent rise in pressure (in the tank) above the maximum allowable pressure:

(1) The vapors evaporated by an ambient air temperature of 115° F. plus the maximum flow rate of the cargo filling pipes or,

(2) The vapors generated under fire exposure computed using the formulas of § 54.15-25(c) of subchapter F (Marine Engineering) of this chapter.

(d) The safety relief valves shall meet the arrangement and inspection requirements of § 54.15-25 of subchapter F (Marine Engineering) of this chapter.

(e) Means shall be provided to protect nonpressure vessel tanks from excessive external pressure.

(f) Void spaces between the primary and secondary barriers of nonpressure

vessel type tanks shall be protected by relief devices. The relief setting shall not be higher than the void test pressure, and shall not exceed 90 percent of the setting of the safety relief valve protecting the primary tank.

[CGFR 68-82, 33 FR 18807, Dec. 18, 1968]

**§ 38.10-20 Liquid level gaging devices—TB/ALL.**

(a) Each tank shall be fitted with a liquid level gaging device of approved design to indicate the maximum level to which the tank may be filled with liquid:

(1) Between -20° F. and 130° F. for unrefrigerated service; or,

(2) Within the operating temperature range for tanks operating below atmospheric temperature.

(b) Liquid level gaging devices may be of the following types: Rotary tube, slip tube, magnetic, automatic float, or similar types approved by the Commandant. Except as otherwise provided in this section, fixed tube devices are not acceptable as the primary gaging device.

(c) All gaging devices shall be arranged so that the maximum liquid level for product being carried, to which the tank may be filled is readily determinable. The maximum gallonage capacity as required by § 38.15-1 shall be:

(1) Marked on the tank system nameplate or gaging device; or,

(2) Shown in the ullage tables.

(d) Gaging devices that require bleeding of the product to the atmosphere, such as the rotary tube, fixed tube, and slip tube, shall be so designed that the bleed valve maximum opening is not larger than a No. 54 drill size (0.055-inch diameter), unless provided with an excess flow valve.

(e) For pressure vessel type tanks each automatic float, continuous reading tape or similar type gage not mounted directly on the tank or dome shall be fitted with a shutoff device located as close to the tank as practicable. When an automatic float gaging device, which gages the entire height of the tank is used, a fixed tube gage set in the range of 85 percent to 90 percent of the water capacity of the tank shall be provided in addition as a means of checking the accuracy of the