

(10) *Message Validity.* An EAS Decoder must provide error detection and validation of the header codes of each message to ascertain if the message is valid. Header code comparisons may be accomplished through the use of a bit-by-bit compare or any other error detection and validation protocol. A header code must only be considered valid when two of the three headers match exactly. Duplicate messages must not be relayed automatically.

(11) A header code with the EAN Event code specified in § 11.31(c) that is received through any of the audio inputs must override all other messages.

(b) *Attention Signal.* EAS Decoders at broadcast stations shall have detection and activation circuitry that will demute a receiver upon detection of the two audio tones of 853 Hz and 960 Hz. To prevent false responses, decoders designed to use the two tones for broadcast receiver demuting shall comply with the following:

(1) *Time Delay.* A minimum time delay of 8 but not more than 16 seconds of tone reception shall be incorporated into the demuting or activation process to insure that the tones will be audible for a period of at least 4 seconds. After July 1, 1995, the time delay shall be 3-4 seconds.

(2) *Operation Bandwidth.* The decoder circuitry shall not respond to tones which vary more than  $\pm 5$  Hz from each of the frequencies, 853 Hz and 960 Hz.

(3) *Reset Ability.* The decoder shall have a means to manually or automatically reset the associated broadcast receiver to a muted state.

(c) Decoders shall be capable of operation within the tolerances specified in this section as well as those in § 11.32 (b), (c) and (d).

[59 FR 67092, Dec. 28, 1994, as amended at 60 FR 55999, Nov. 6, 1995; 67 FR 18510, Apr. 16, 2002]

#### § 11.34 Acceptability of the equipment.

(a) An EAS Encoder used for generating the EAS codes and the Attention Signal must be Certified in accordance with the procedures in part 2, subpart J, of this chapter. The data and information submitted must show the capability of the equipment to meet the requirements of this part as well as the

requirements contained in part 15 of this chapter for digital devices.

(b) Decoders used for the detection of the EAS codes and receiving the Attention Signal must be Certified in accordance with the procedures in part 2, subpart J, of this chapter. The data and information submitted must show the capability of the equipment to meet the requirements of this part as well as the requirements contained in part 15 of this chapter for digital devices.

(c) The functions of the EAS decoder, Attention Signal generator and receiver, and the EAS encoder specified in §§ 11.31, 11.32 and 11.33 may be combined and Certified as a single unit provided that the unit complies with all specifications in this rule section.

(d) Manufacturers must include instructions and information on how to install, operate and program an EAS Encoder, EAS Decoder, or combined unit and a list of all State and county FIPS numbers with each unit sold or marketed in the U.S.

(e) Waiver requests of the Certification requirements for EAS Encoders or EAS Decoders which are constructed for use at a broadcast station or subject cable system, but are not offered for sale will be considered on an individual basis in accordance with part 1, subpart G, of this chapter.

(f) Modifications to existing authorized EAS decoders, encoders or combined units necessary to implement the new EAS codes specified in § 11.31 and to implement the selective displaying and logging feature specified in § 11.33(a)(4) will be considered Class I permissive changes that do not require a new application for and grant of equipment certification under part 2, subpart J of this chapter.

(g) All existing and new models of EAS encoders, decoders and combined units manufactured after August 1, 2003 must be capable of generating and detecting the new EAS codes specified in § 11.31 in order to be certified under part 2, subpart J of this chapter. All existing and new models of EAS decoders and combined units manufactured after August 1, 2003 must have the selective displaying and logging capability specified in § 11.33(a)(4) in order

## § 11.35

to be certified under part 2, subpart J of this chapter.

[59 FR 67092, Dec. 28, 1994, as amended at 60 FR 56000, Nov. 6, 1995; 67 FR 18510, Apr. 16, 2002]

### § 11.35 Equipment operational readiness.

(a) Broadcast stations and cable systems and wireless cable systems are responsible for ensuring that EAS Encoders, EAS Decoders and Attention Signal generating and receiving equipment used as part of the EAS are installed so that the monitoring and transmitting functions are available during the times the stations and systems are in operation. Additionally, broadcast stations and cable systems and wireless cable systems must determine the cause of any failure to receive the required tests or activations specified in §§ 11.61(a) (1) and (2). Appropriate entries must be made in the broadcast station log as specified in § 73.1820 and § 73.1840 of this chapter, cable system record as specified in §§ 76.1700, 76.1708, and 76.1711 of this chapter, MDS/MMDS station records as specified in § 21.304 of this chapter, indicating reasons why any tests were not received.

(b) If the EAS Encoder or EAS Decoder becomes defective, the broadcast station, cable system or wireless cable system may operate without the defective equipment pending its repair or replacement for 60 days without further FCC authority. Entries shall be made in the broadcast station log, cable system or wireless cable system station records showing the date and time the equipment was removed and restored to service. For personnel training purposes, the required monthly test script must still be transmitted even though the equipment for generating the EAS message codes, Attention Signal and EOM code is not functioning.

(c) If repair or replacement of defective equipment is not completed within 60 days, an informal request shall be submitted to the District Director of the FCC field office serving the area in which the broadcast station, cable system or wireless cable system is located for additional time to repair the defective equipment. This request must explain what steps have been taken to repair or replace the defective equip-

## 47 CFR Ch. I (10–1–04 Edition)

ment, the alternative procedures being used while the defective equipment is out of service, and when the defective equipment will be repaired or replaced.

[63 FR 29664, June 1, 1998, as amended at 65 FR 53614, Sept. 5, 2000]

### Subpart C—Organization

#### § 11.41 Participation in EAS.

(a) All broadcast stations and cable systems and wireless cable systems specified in § 11.11 are categorized as Participating National (PN) sources unless authorized by the FCC to be a Non-Participating (NN) sources.

(b) A broadcast station and cable system and wireless cable system may submit a written request to the FCC asking to be a Non-Participating National (NN) source. The FCC may then issue a Non-participating National Authorization letter. NN sources must go off the air during a national EAS activation after transmitting specified information.

(1) A station or system that is a Non-participating National (NN) source under § 11.18(f) that wants to become a Participating National (PN) source in the national level EAS must submit a written request to the FCC.

(2) NN sources may voluntarily participate in the State and Local Area EAS. Participation is at the discretion of broadcast station and cable system and wireless cable system management and should comply with State and Local Area EAS Plans.

(c) All sources, including NN, must have immediate access to an Operating Handbook. They should contact the FCC to ensure that they are on the FCC EAS mailing list.

[63 FR 29664, June 1, 1998, as amended at 65 FR 21658, Apr. 24, 2000]

#### § 11.42 Participation by communications common carriers.

(a) During activation of the National level EAS, communications common carriers which have facilities available in place may, without charge, connect:

(1) An originating source from the nearest service area to a selected Test Center and then to the radio and television broadcast networks, and cable networks and program suppliers for the