

other earth station, or any space station beyond those limitations that would be expected to be imposed by an earth station employing an antenna conforming to the reference patterns defined in paragraphs (a) and (b) of this section.

(f) An earth station with an antenna not conforming to the standards of paragraphs (a) and (b) of this section will be routinely authorized after February 15, 1985 upon a finding by the Commission that unacceptable levels of interference will not be caused under conditions of uniform 2° orbital spacings. An earth station antenna initially authorized on or before February 15, 1985 will be authorized by the Commission to continue to operate as long as such operations are found not to cause any unacceptable levels of adjacent satellite interference. In either case, the Commission will impose appropriate terms and conditions in its authorization of such facilities and operations.

(g) The antenna performance standards of small antennas operating in the 12/14 GHz band with diameters as small as 1.2 meters starts at 1.25° instead of 1° as stipulated in paragraph (a) of this section.

(h)(1) The gain of any antennas to be employed in transmission from a gateway earth station antenna operating in the frequency bands 10.7-11.7 GHz, 12.75-13.15 GHz, 13.2125-13.25 GHz, 13.8-14.0 GHz, and 14.4-14.5 GHz and communicating with NGSO FSS satellites shall lie below the envelope defined as follows:

$$29 - 25 \log_{10} (\theta) \text{ dBi} - 10 \text{ dBi}$$

$$1^{\text{B}} \leq \theta \leq 36^{\text{B}}$$

$$36^{\text{B}} \leq \theta \leq 180^{\text{B}}$$

Where:  $\theta$  is the angle in degrees from the axis of the main lobe, and dBi refers to dB relative to an isotropic radiator.

(2) For the purposes of this section, the peak gain of an individual sidelobe may not exceed the envelope defined in paragraph (h)(1) of this section.

[48 FR 40255, Sept. 6, 1983, as amended at 50 FR 2675, Jan. 18, 1985; 50 FR 39004, Sept. 26, 1985; 58 FR 13420, Mar. 11, 1993; 66 FR 10630, Feb. 16, 2001]

#### § 25.210 Technical requirements for space stations in the Fixed-Satellite Service.

(a) All space stations in the Fixed-Satellite Service used for domestic service in the 4/6 GHz frequency band shall:

(1) Use orthogonal linear polarization with one of the planes defined by the equatorial plane;

(2) Be designed so that the polarization sense of uplink transmissions is opposite to that of downlink transmissions on the same transponder; and

(3) Shall be capable of switching polarization sense upon ground command.

(b) All space stations in the Fixed-Satellite Service in the 20/30 GHz band shall use either orthogonal linear or orthogonal circular polarization. Those space stations utilizing orthogonal linear polarization shall also comply with paragraph (a) of this section.

(c) All space stations in the Fixed-Satellite Service shall have a minimum capability to change transponder saturation flux densities by ground command in 4 dB steps over a range of 12 dB.

(d) All space stations in the Fixed-Satellite Service in the 20/30 GHz band shall employ state-of-the-art full frequency reuse either through the use of orthogonal polarizations within the same beam and/or through the use of spatially independent beams.

(e) [Reserved]

(f) All space stations in the Fixed-Satellite Service in the 3600-3700 MHz, 3700-4200 MHz, 5091-5250 MHz, 5825-5925 MHz, 5925-6425 MHz, 6425-6525 MHz, 6525-6700 MHz, 6700-7025 MHz, 10.7-10.95 GHz, 10.95-11.2 GHz, 11.2-11.45 GHz, 11.45-11.7 GHz, 11.7-12.2 GHz, 12.2-12.7 GHz, 12.75-13.15 GHz, 13.15-13.2125 GHz, 13.2125-13.25 GHz, 13.75-14.0 GHz, 14.0-14.5 GHz and 15.43-15.63 GHz bands shall employ state-of-the-art full frequency reuse either through the use of orthogonal polarizations within the same beam and/or the use of spatially independent beams.

(g)-(h) [Reserved]

(i) Space station antennas in the Fixed-Satellite Service must be designed to provide a cross-polarization isolation such that the ratio of the on axis co-polar gain to the cross-polar

§ 25.211

gain of the antenna in the assigned frequency band shall be at least 30 dB within its primary coverage area.

(j) Space stations to be operated in the geostationary satellite orbit must be:

(1) Designed with the capability of being maintained in orbit within 0.05° of their assigned orbital longitude,

(2) Maintained in orbit at their assigned orbital longitude within the longitudinal tolerance specified by the Commission, and

(3) The Commission may authorize operations at assigned orbital longitudes offset by 0.05° or multiples thereof from the nominal orbital location specified in the station authorizations.

(k) Antenna measurements of both co-polarized and cross-polarized performance must be made on all antennas employed by space stations both within the primary coverage area to facilitate coordination with other Commission space station licensees and outside the primary coverage area to facilitate international frequency coordination with other Administrations. The results of such measurements shall be submitted to the Commission within thirty days after preliminary in-orbit testing is completed.

(l) All operators of space stations shall, on June 30 of each year, file a report with the International Bureau and the Commission's Columbia Operations Center in Columbia, Maryland, containing the following information current as of May 31 of that year:

(1) Status of satellite construction and anticipated launch dates, including any major problems or delays encountered;

(2) A listing of any non-scheduled transponder outages for more than thirty minutes and the cause(s) of such outages;

(3) A detailed description of the utilization made of each transponder on each of the in-orbit satellites. This description should identify the total capacity or the percentage of time each transponder is actually used for transmission, and the amount of unused system capacity in the transponder. This information is not required for those transponders that are sold on a non-common carrier basis. In that case, op-

erators should indicate the number of transponders sold on each in-satellite orbit.

(4) Identification of any transponders not available for service or otherwise not performing to specifications, the cause of these difficulties, and the date any transponder was taken out of service or the malfunction identified.

[58 FR 13420, Mar. 11, 1993, as amended at 61 FR 9952, Mar. 12, 1996; 62 FR 5931, Feb. 10, 1997; 62 FR 61457, Nov. 18, 1997; 68 FR 51508, Aug. 27, 2003]

EFFECTIVE DATE NOTE: At 69 FR 54587, Sept. 9, 2004, §25.210 was amended by revising paragraph (j), effective Oct. 12, 2004. For the convenience of the user, the revised text is set forth as follows:

§ 25.210 Technical requirements for space stations in the Fixed-Satellite Service.

\* \* \* \* \*

(j) Space stations operated in the geostationary satellite orbit must be maintained within 0.05° of their assigned orbital longitude in the east/west direction, unless specifically authorized by the Commission to operate with a different longitudinal tolerance, and except as provided in Section 25.283(b) (End-of-life Disposal).

\* \* \* \* \*

§ 25.211 Video transmissions in the Fixed-Satellite Service.

(a) Downlink analog video transmissions in the band 3700–4200 MHz shall be transmitted only on a center frequency of 3700+20N MHz, where N=1 to 24. The corresponding uplink frequency shall be 2225 MHz higher.

(b) All 4/6 GHz analog video transmissions shall contain an energy dispersal signal at all times with a minimum peak-to-peak bandwidth set at whatever value is necessary to meet the power flux density limits specified in §25.208(a) and successfully coordinated internationally and accepted by adjacent U.S. satellite operators based on the use of state of the art space and earth station facilities. Further, all transmissions operating in frequency bands described in §25.208 (b) and (c) shall also contain an energy dispersal signal at all times with a minimum peak-to-peak bandwidth set at whatever value is necessary to meet the power flux density limits specified in