

and the antenna gain pattern requirements in §§25.209(a) and (b). In addition, earth station licensees authorized to operate with one or more space stations described in paragraph (c)(1) of this paragraph in frequency bands shared with terrestrial wireless services shall comply with the requirements in §25.203(c).

(4) In addition to the requirements set forth in paragraph (c)(3) of this section, earth station licensees with a gain equivalent or higher than the gain of a 1.2 meter antenna operating in the 14.0–14.5 GHz band, authorized to operate with one or more space stations described in paragraph (c)(1) of this paragraph in frequency bands greater than 14.5 GHz shall be required to comply with the antenna input power density requirements set forth in §25.212(c).

(d) Applicants requesting authorization of a satellite subject to paragraphs (b) or (c) of this section must submit a narrative statement describing the debris mitigation design and operational strategies, if any, that they will use. Applicants are specifically required to submit a casualty risk assessment if planned post-mission disposal involves atmospheric re-entry of the spacecraft.

(e) In the event that the Commission adopts frequency band-specific service rules for a particular frequency band after it has granted one or more space station or earth station licenses for operations in that frequency band, those licensees will be required to come into compliance with the frequency band-specific service rules within 30 days of the effective date of those rules, unless otherwise specified by either Commission or Bureau Order.

[68 FR 51508, Aug. 27, 2003]

§§ 25.218–25.249 [Reserved]

§ 25.250 Sharing between NGSO MSS Feeder links Earth Stations in the 19.3–19.7 GHz and 29.1–29.5 GHz Bands.

(a) NGSO MSS applicants shall be licensed to operate in the 29.1–29.5 GHz band for Earth-to-space transmissions and 19.3–19.7 GHz for space-to-Earth transmissions from feeder link earth station complexes. A “feeder link earth station complex” may include up to three (3) earth station groups, with

each earth station group having up to four (4) antennas, located within a radius of 75 km of a given set of geographic coordinates provided by NGSO-MSS licensees or applicants.

(b) Licensees of NGSO MSS feeder link earth stations separated by 800 km or less are required to coordinate their operations, see §25.203. The results of the coordination shall be reported to the Commission.

[61 FR 44181, Aug. 28, 1996]

§ 25.251 Special requirements for coordination.

(a) The administrative aspects of the coordination process are set forth in §101.103 of this chapter in the case of coordination of terrestrial stations with earth stations, and in §25.203 in the case of coordination of earth stations with terrestrial stations.

(b) The technical aspects of coordination are based on Appendix S7 of the International Telecommunication Union Radio Regulations and certain recommendations of the ITU Radiocommunication Sector (available at the FCC’s Reference Information Center, Room CY-A257, 445 12th Street, SW., Washington, DC 20554).

[66 FR 10630, Feb. 16, 2001]

§ 25.252 Special requirements for ancillary terrestrial components operating in the 2000–2020 MHz/2180–2200 MHz bands.

(a) Applicants for an ancillary terrestrial component in these bands must demonstrate that ATC base stations shall not:

(1) Exceed an EIRP of –100.6 dBW/4 kHz for out-of-channel emissions at the edge of the MSS licensee’s selected assignment.

(2) Exceed a peak EIRP of 27 dBW in 1.23 MHz.

(3) Exceed an EIRP toward the physical horizon (not to include man-made structures) of 25.5 dBW in 1.23 MHz.

(4) Be located less than 190 meters from all airport runways and aircraft stand areas, including takeoff and landing paths.

(5) Exceed an aggregate power flux density of –51.8 dBW/m² in a 1.23 MHz bandwidth at all airport runways and aircraft stand areas, including takeoff and landing paths and all ATC base