

§ 90.275

47 CFR Ch. I (10-1-04 Edition)

TABLE 2—CHANNELS AVAILABLE IN BUFFALO, DETROIT AND CLEVELAND AREAS—Continued

| Frequency (MHz) | Pool in which assigned |
|-----------------|------------------------|
| 425.23125* | IB |
| 425.23750 | IB |
| 425.24375* | IB |
| 425.250 | PS |
| 425.25625* | PS |
| 425.26250 | PS |
| 425.26875* | PS |
| 425.275 | PS |
| 425.28125* | PS |
| 425.28750 | PS |
| 425.29375* | PS |
| 425.300 | PS |
| 425.30625* | PS |
| 425.31250 | PS |
| 425.31875* | PS |
| 425.325 | PS |
| 425.33125* | PS |
| 425.33750 | PS |
| 425.34375* | PS |
| 425.350 | PS |
| 425.35625* | PS |
| 425.36250 | PS |
| 425.36875* | PS |
| 425.375 | PS |
| 425.38125* | PS |
| 425.38750 | PS |
| 425.39375* | PS |
| 425.400 | PS |
| 425.40625* | PS |
| 425.41250 | PS |
| 425.41875* | PS |
| 425.425 | PS |
| 425.43125* | PS |
| 425.43750 | PS |
| 425.44375* | PS |
| 425.450 | PS |
| 425.45625* | PS |
| 425.46250 | PS |
| 425.46875* | PS |
| 425.475 | PS |
| 425.48125** | PS |

* This frequency will be assigned with an authorized bandwidth not to exceed 6 kHz.

(b) [Reserved]

(c) Base or control stations shall be located within 48 km (30 miles) of the center of Buffalo or 80 km (50 miles) of the center of Detroit. In Cleveland, base or control stations will be allowed at locations north of line A that are within 48 km (30 miles) of the city center. In addition, low power (2 watts or less) base stations may locate within 80 km (50 miles) of the center of Buffalo. The following coordinates shall be used for the centers of these areas (coordinates are referenced to North American Datum 1983 (NAD83)):

| | |
|------------|-----------------------------|
| Buffalo, | 42°52'52.2" North latitude. |
| NY, | 78°52'20.1" West longitude. |
| Cleveland, | 41°29'51.2" North latitude. |
| OH, | 81°41'49.5" West longitude. |
| Detroit, | 42°19'48.1" North latitude. |
| MI, | 83°02'56.7" West longitude. |

(d) Mobile operation shall be confined to within 80 km (50 miles) of the centers of Detroit, Cleveland, or Buffalo.

[52 FR 6156, Mar. 2, 1987, as amended at 54 FR 38681, Sept. 20, 1989; 58 FR 31476, June 3, 1993; 58 FR 44957, Aug. 25, 1993; 60 FR 37269, July 19, 1995; 61 FR 6576, Feb. 21, 1996; 62 FR 18929, Apr. 17, 1997; 63 FR 68965, Dec. 14, 1998]

§ 90.275 Selection and assignment of frequencies in the 421-430 MHz band.

Applicants must specify the frequencies in which the proposed system will operate pursuant to a recommendation by a frequency coordinator certified for the pool in which the requested frequency is assigned.

[62 FR 18932, Apr. 17, 1997]

§ 90.279 Power limitations applicable to the 421-430 MHz band.

(a) Base station authorizations in the 421-430 MHz band will be subject to Effective Radiated Power (ERP) and Effective Antenna Height (EAH) limitations as shown in the table below. ERP is defined as the product of the power supplied to the antenna and its gain relative to a half-wave dipole in a given direction. EAH is calculated by subtracting the Assumed Average Terrain Elevation (AATE) as listed in table 7 of § 90.619 from the antenna height above mean sea level.

LIMITS OF EFFECTIVE RADIATED POWER (ERP) CORRESPONDING TO EFFECTIVE ANTENNA HEIGHTS (EAH) OF BASE STATIONS IN THE 421-430 MHz BAND

| Effective antenna height (EAH) in meters (feet) | Maximum effective radiated power (ERP) (watts) |
|---|--|
| 0-152 (0-500) | 250 |
| Above 152-305 (above 500-1000) | 150 |
| Above 305-457 (above 1000-1500) | 75 |
| Above 457-610 (above 1500-2000) | 40 |
| Above 610-762 (above 2000-2500) | 20 |
| Above 762-914 (above 2500-3000) | 15 |
| Above 914-1219 (above 3000-4000) | 10 |
| Above 1219 (above 4000) | 5 |

(b) The maximum transmitter power output that will be authorized for control stations is 20 watts.

[52 FR 6157, Mar. 2, 1987, as amended at 58 FR 44957, Aug. 25, 1993]