

§ 355.15

§ 355.15 Inedible material operating and storage rooms; outer premises, docks, driveways, etc.; fly-breeding material; nuisances.

All operating and storage rooms and departments of inspected plants used for inedible material shall be maintained in clean condition, and shall be separate and apart from rooms and departments where certified products are prepared, handled, or stored. Docks and areas where cars and vehicles are loaded, and driveways, approaches and alleyways shall be properly paved and drained and the outer premises of every inspected plant shall be kept in clean and orderly condition. All catchbasins on the premises shall be of such construction and location and shall be given such attention as will insure their being kept in acceptable condition as regards odors and cleanliness. The accumulation on the premises of any material in which flies may breed, or the maintenance of any nuisance on the premises shall not be allowed.

§ 355.16 Control of flies, rats, mice, etc.

Flies, rats, mice, and other vermin shall be excluded from inspected plants and premises.

§ 355.17 Tagging equipment "U.S. rejected."

When necessary, inspectors shall attach a "U.S. rejected" tag to any equipment or utensil which is unclean or the use of which would be in conflict with the provisions of this part. No equipment or utensil so tagged shall again be used until made acceptable under this part and until removal of the tag. Such tag shall not be removed from the equipment or utensil by anyone other than an inspector.

§ 355.18 Drawings and specifications to be furnished.

Triplicate copies of complete drawings and specifications for remodeling inspected plants or for new structures at such plants shall be submitted to the Administrator and approval obtained for the plans in advance of construction.

9 CFR Ch. III (1-1-05 Edition)

INSPECTION PROCEDURE

§ 355.19 Inspector to be informed when plant operates.

The management of an inspected plant shall inform the inspector or the circuit supervisor when work in each department has been concluded for the day, and the day and hour when work will be resumed therein. There shall be no preparation of certified products at an inspected plant except under the supervision of an inspector.

§ 355.20 Inspector to have access to plant at all times.

For the purpose of examination or inspection necessary to enforce any of the provisions of this part, inspectors shall have access at all times by day or night, whether the plant is being operated or not, to every part of an inspected plant.

§ 355.21 Products entering inspected plants.

All products of a kind certified under this part or materials to be used in the preparation of such products when brought into an inspected plant shall be identified and inspected at the time of receipt and be subject to further inspection in such manner and at such time as may be deemed necessary. If, upon inspection, any such article is found to be unsound or otherwise unfit, it shall be handled as provided in § 355.28.

§ 355.22 Designation of place of receipt of returned products.

Certified products returned to an inspected plant shall be received at a dock or place specifically designated for the purpose by the plant management with the approval of the circuit supervisor. Such returned products shall be inspected there by the inspector before further entering the plant.

§ 355.23 Tagging products "U.S. retained."

A "U.S. Retained" tag shall be placed by an inspector at the time of inspection on all certified products, materials to be used in the preparation of certified products, or containers thereof, whenever such certified products, materials, or containers are suspected

of being unsound or otherwise unfit or not in conformity with the requirements contained in this part. Such tags so placed shall not be removed by anyone other than an inspector.

§ 355.24 Processes to be supervised.

All processes used in the preparation of the certified products shall be supervised by an inspector. All steps in the process of manufacture shall be conducted carefully and with strict cleanliness. Inspected plants shall not prepare products of a kind certified under this part unless they conform with the regulations contained in this part.

§ 355.25 Canning with heat processing and hermetically sealed containers; closures; code marking; heat processing; incubation.

(a) Containers shall be cleaned thoroughly immediately before filling, and precaution must be taken to avoid soiling the inner surfaces subsequently.

(b) The inside surfaces of containers of metal, glass, or other material shall be washed by spraying in an inverted position with running water at a temperature of at least 180 °F. The container washing equipment shall be provided with a thermometer to register the temperature of the water used for cleaning the containers.

(c) Perfect closure is required for hermetically sealed containers. Heat processing shall follow promptly after closing.

(d) Careful inspection shall be made of the containers by competent plant employees immediately after closing, and containers which are defectively filled or defectively closed, or which show inadequate vacuum, shall not be further processed until the defect has been corrected. The containers shall again be inspected by plant employees when they have cooled sufficiently for handling after processing by heating. The contents of defective containers shall be condemned unless correction of the defect is accomplished within six hours following the sealing of the containers or completion of the heat processing, as the case may be, except that (1) if the defective condition is discovered during an afternoon run the cans of product may be held in coolers at a temperature not exceeding 38 °F. under

conditions that will promptly and effectively chill them until the following day when the defect may be corrected; and (2) short vacuum or overstuffed cans of products which have not been handled in accordance with the above may be incubated as provided in paragraph (i) of this section in the inspected plant under Program supervision, after which the cans shall be opened and the sound products passed.

(e) Canned products shall not be passed unless, after cooling to atmospheric temperature, they show the external characteristic of sound cans; that is, the cans shall not be overfilled, the ends of the cans shall be concave, there shall be no bulging of the cans, the sides and ends of the cans shall conform to the products, and there shall be no slack or loose tin in the cans.

(f) All canned products shall be plainly and permanently marked on the containers by code or otherwise with the identity of the contents and date of canning. The code used and its meaning shall be on record in the office of the circuit supervisor before use.

(g) The canned products must be processed at such temperature and for such period of time as will assure keeping without refrigeration under usual conditions of storage and transportation as evidenced by the incubation test.

(h) Lots of canned products shall be identified during their handling preparatory to and during heat processing by tagging the baskets or cages in which the cans are being conveyed, with a tag which will change color on going through the heat processing or by other effective means so as to insure the proper channeling of the products for effective heat processing after closing the cans.

(i) Facilities shall be provided to incubate at least representative samples of the fully processed canned products. The incubation shall consist of holding the canned products for at least 10 days at about 98 °F. The extent to which incubation tests shall be required by inspectors depends on conditions such as the record of the inspected plant in conducting canning operations, the extent to which the plant furnishes competent supervision and inspection in