

of communicating with support vessels, shore side, etc.

§149.145 What are the requirements for curbs, gutters, drains, and reservoirs?

Each pumping platform complex must have enough curbs, gutters, drains, and reservoirs to collect, in the reservoirs, all oil and contaminants not authorized for discharge into the ocean according to the port's National Pollution Discharge Elimination System (NPDES) permit.

Subpart C—Lifesaving Equipment

§149.300 What does this subpart do?

This subpart provides requirements for lifesaving equipment on deepwater ports.

MANNED DEEPWATER PORT
REQUIREMENTS

§149.301 What are the requirements for lifesaving equipment?

(a) Each deepwater port on which at least one person occupies an accommodation space for more than 30 consecutive days, in any successive 12-month period, must comply with the requirements for lifesaving equipment in this subpart.

(b) Each deepwater port, not under paragraph (a) of this section, must comply with the requirements for lifesaving equipment for unmanned deepwater ports in this subpart.

§149.302 What are the requirements when lifesaving equipment is repaired or replaced?

When lifesaving equipment is replaced or when the deepwater port undergoes a repair, alteration, or modification that involves replacing or adding to the lifesaving equipment complement, the new lifesaving equipment must meet the requirements of this subpart.

§149.303 What survival craft and rescue boats may be used on a manned deepwater port?

(a) Each survival craft on a manned deepwater port must be one of the following:

(1) A lifeboat meeting the requirements of 149.306 to this subpart; or

(2) A liferaft meeting the requirements of 149.308 to this subpart.

(b) Each rescue boat on a manned deepwater port must be a rescue boat meeting the requirements of §149.314 to this part.

§149.304 What type and how many survival craft and rescue boats must a manned deepwater port have?

(a) Except as specified under §149.305 to this subpart, each manned deepwater port must have at least the type and number of survival craft and the number of rescue boats indicated for the deepwater port in paragraphs (a)(1) through (a)(5) of this section.

(1) For a deepwater port with 30 or fewer persons onboard:

(i) One or more lifeboats with a total capacity of 100 percent of the personnel onboard;

(ii) One or more liferafts with a total capacity of 100 percent of the personnel onboard; and

(iii) One rescue boat, except that the rescue boat is not required for deepwater ports with 8 or fewer persons onboard.

(2) For a deepwater port with 31 or more persons onboard:

(i) At least two lifeboats with a total capacity of 100 percent of the personnel onboard;

(ii) One or more liferafts with a total capacity so that, if the survival craft at any one location are rendered unusable, there will be craft remaining with 100 percent capacity; and

(iii) One rescue boat.

(3) Lifeboats may be substituted for liferafts.

(4) Capacity refers to the total number of persons on the deepwater port at any one time, not including temporary personnel. Temporary personnel include: contract workers, official visitors, and any other persons who are not permanent employees. See §149.305 in this subpart for additional survival craft requirements when temporary personnel are onboard.

(5) The required lifeboats may be used as rescue boats if the lifeboats also meet the requirements for rescue boats in §149.314 to this subpart.