

**§ 149.318**

(c) The operator must mark each lifejacket container, or lifejacket stowage location, with the words "LIFE-JACKETS" in block letters and the quantity, identity, and size of the lifejackets stowed inside the containers or stowed at the location.

**§ 149.318 Must every person on the port have a lifejacket?**

The operator must provide a lifejacket that complies with 149.316 to this subpart, for each person on a manned deepwater port.

**§ 149.319 What additional lifejackets must I have?**

For each person on duty in a location where the lifejacket required by 149.317 of this subpart is not readily accessible, an additional lifejacket must be stowed so as to be readily accessible to that location.

**§ 149.320 What are the requirements for ring lifebuoys?**

(a) Ring lifebuoys must be approved under approval series 46 CFR 160.050 or 160.150 (for SOLAS-approved equipment).

(b) Each ring lifebuoy must have a floating, electric water light—approved under approval series 46 CFR 161.010. The operator must ensure that the light to the ring lifebuoy is attached by a lanyard of 12-thread manila, or a synthetic rope of equivalent strength, not less than 3 feet nor more than 6 feet in length. The light must be mounted on a bracket near the ring lifebuoy so that, when the ring lifebuoy is cast loose, the light will be pulled free of the bracket.

(c) To each ring lifebuoy, there must be attached a buoyant line of 100 feet in length, with a breaking strength of at least 5 KiloNewtons force. The end of the line must not be secured to the deepwater port.

(d) Each ring lifebuoy must be marked with Type II retro-reflective material—approved under approval series 46 CFR 164.018.

**§ 149.321 How many ring lifebuoys must be on each deepwater port?**

There must be at least four approved ring lifebuoys on each manned deepwater port.

**33 CFR Ch. I (7–1–05 Edition)**

**§ 149.322 Where must ring lifebuoys be located and how must they be stowed?**

(a) The operator must locate one ring lifebuoy on each side of the port and one near each external stairway leading to the water. One buoy may be used to satisfy both these requirements.

(b) Each ring lifebuoy must be stowed on or in a rack that is readily accessible in an emergency. The ring lifebuoy must not be permanently secured in any way to the rack or the deepwater port.

**§ 149.323 What are the requirements for first aid kits?**

(a) Each manned deepwater port must have an industrial first aid kit approved by an appropriate organization (e.g., American Red Cross) for the maximum number of persons on the deepwater port.

(b) The first aid kit must be maintained in a space designated as a medical treatment room or, if there is no medical treatment room, under the custody of the person in charge.

(c) The operator must ensure that each first aid kit is accompanied by a copy of DHHS Publication No. (PHS) 84-2024: "The Ship's Medicine Chest and Medical Aid at Sea"—available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402, or the "American Red Cross First Aid and Safety Handbook"—available from Little Brown and Company, 3 Center Plaza, Boston, MA 02018.

**§ 149.324 What are the requirements for litters?**

Each manned deepwater port must have at least one Stokes litter, or other suitable litter, capable of being safely hoisted with an injured person. The litter must be readily accessible in an emergency.

**§ 149.325 What emergency communications equipment must be on a manned deepwater port?**

Each manned deepwater port must have a radio, telephone, or other means of emergency communication with the shore, vessels, and facilities in the vicinity in the event the primary communications system outlined in