

§149.140 fails. This communication equipment must have an emergency power source.

§ 149.326 What are the immersion suit requirements?

Each manned deepwater port, located North of 32 degrees North latitude, must comply with the immersion suit requirements in 46 CFR part 108.

§ 149.327 What are the approval requirements for work vests and anti-exposure suits?

All work vests and anti-exposure (deck) suits, on a manned deepwater port, must be of a buoyant type approved under:

- (a) Approval series 46 CFR 160.053 as a work vest;
- (b) Approval series 46 CFR 160.053 or 160.153 as an anti-exposure suit; or
- (c) Approval series 46 CFR 160.077 as a commercial hybrid personal flotation device.

§ 149.328 How must work vests and anti-exposure (deck) suits be stowed?

All work vests and deck suits must be stowed separately from lifejackets and in a location that is not easily confused with a storage area for lifejackets.

§ 149.329 How must work vests and deck suits be marked?

All work vests and deck suits must be marked with Type II retro-reflective material—approved under approval series 46 CFR 164.018.

§ 149.330 When may a work vest or deck suit be substituted for a lifejacket?

(a) A work vest or deck suit meeting § 149.326 of this subpart may be used instead of a lifejacket, when personnel are working near or over water.

(b) Work vests or deck suits may not be substituted for any portion of the number of approved lifejackets required to be on the deepwater port or an attending vessel for use during drills and emergencies.

§ 149.331 What are the requirements for hybrid personal flotation devices?

(a) The operator must ensure use and stowage of all commercial hybrid personal flotation devices (PFDs) used as work vests under:

(1) The procedures in the manual required for these devices in 46 CFR 160.077-29; and

(2) All limitations, if any, marked on them.

(b) All commercial hybrid PFDs on the deepwater port must be of the same or similar design and must have the same method of operation.

§ 149.332 What are the requirements for inflatable lifejackets?

(a) Each inflatable lifejacket must be approved under approval series 46 CFR 160.176.

(b) All inflatable lifejackets on a deepwater port must:

(1) Be used and stowed under the procedures in the manual required for these lifejackets under 46 CFR 160.176-21;

(2) Be marked with all limitations, if any; and

(3) Be of the same or similar design and must have the same method of operation.

§ 149.333 What are the marking requirements for lifesaving equipment?

(a) Each lifeboat, rigid liferaft, and survival capsule must be marked on two opposite outboard sides with the name, number, or other inscription identifying the deepwater port on which placed and the number of persons permitted on the craft. Each paddle or oar for these crafts must be marked with an inscription identifying the deepwater port. The letters and numbers must be at least 100 millimeters (3.94 inches) high on a contrasting background.

(b) Each inflatable liferaft must be marked to meet 46 CFR 160.151-33, and after each servicing, 46 CFR 160.151-57(m).

(c) All lifejackets and ring lifebuoys must be conspicuously marked with the name, number, or other inscription identifying the deepwater port on which placed. The letters and numbers