

## Coast Guard, DHS

## § 149.680

flux levels and provide the A-60 standard defined in 46 CFR 108.131(b)(2).

### SINGLE POINT MOORINGS

#### **§ 149.650 What are the requirements for single point moorings and their attached hoses?**

Each SPM and its attached hose must be designed appropriately for the protection of the environment and for durability under combined wind, wave, and current forces of the most severe storm that can be expected to occur at the port in any 100-year period. The appropriateness of a design may be shown by its compliance with standards generally used within the offshore industry that are at least equivalent, in protecting the environment, to the standards in use on January 1, 2003, by the American Bureau of Shipping or another recognized classification society.

### HELICOPTER FUELING FACILITIES

#### **§ 149.655 What are the requirements for helicopter fueling facilities?**

Helicopter fueling facilities must comply with 46 CFR 108.489 or an equivalent standard.

### EMERGENCY POWER

#### **§ 149.660 What are the requirements for emergency power?**

(a) Each pumping platform complex must have emergency power equipment to provide power to operate simultaneously all of the following for a continuous period of 18 hours:

- (1) Emergency lighting circuits;
- (2) Aids to navigation equipment;
- (3) Communications equipment;
- (4) Radar equipment;
- (5) Alarm systems;
- (6) Electrically operated fire pumps; and
- (7) Other electrical equipment identified as emergency equipment in the operations manual for the deepwater port.

(b) No emergency power generating equipment may be located in any enclosed space on a platform that contains oil or natural gas transfer pumping equipment or other power generating equipment.

### GENERAL ALARM SYSTEM

#### **§ 149.665 What are the requirements for a general alarm system?**

Each pumping platform complex must have a general alarm system that meets the following:

- (a) Is capable of being activated manually by the use of alarm boxes;
- (b) Is audible in all parts of the pumping platform complex, except in areas of high ambient noise levels where hearing protection is required under § 150.613 of this chapter; and
- (c) Has a high intensity flashing light in areas where hearing protection is used.

#### **§ 149.670 What are the requirements for marking a general alarm system?**

Each of the following must be marked with the words "GENERAL ALARM" in yellow letters at least 1-inch high on a red background:

- (a) Each general alarm box; and
- (b) Each audio or visual device under § 149.665 for signaling the general alarm.

### PUBLIC ADDRESS SYSTEM

#### **§ 149.675 What are the requirements for the public address system?**

Each pumping platform complex must have a public address system operable from two locations on the complex.

### MEDICAL TREATMENT ROOMS

#### **§ 149.680 What are the requirements for medical treatment rooms?**

Each deepwater port with sleeping spaces for 12 or more persons, including persons in accommodation modules, must have a medical treatment room that has:

- (a) A sign at the entrance designating it as a medical treatment room;
- (b) An entrance that is wide enough and arranged to readily admit a person on a stretcher;
- (c) A single berth or examination table that is accessible from both sides; and
- (d) A washbasin located in the room.