TABLE 150.380(a)—REGULATED ACTIVITIES OF VESSELS AT DEEPWATER PORTS

Regulated Activities	Area to be avoided		
	Safety Zone around each platform pumping complex and SPM ¹	Anchorage areas	No anchorage areas within safety zone and area to be avoided
Tankers calling at port	С	C	С
Support vessel movements	C	С	С
Transit by vessels other than tankers or support vessels	N	P	P
Mooring to SPM by vessels other than tankers or support vessels	F		
Anchoring by vessels other than tankers or support vessels	N	F	N
Fishing, including bottom trawl (shrimping)	N	P	N
Mobile drilling operations or erection of structures ²	N	N	N
Lightering/transshipment ³	N	N	N

Notes--

Key to regulated activities: F--Only in an emergency. N--Not permitted. C--Movement of the vessel is permitted when cleared by the port's person in charge, vessel operations. P--Transit is permitted when the vessel is not in the immediate area of a tanker and when cleared by the person in charge, vessel operations. Communication with the port's person in charge, vessel operations is required. For transiting foreign-flag vessels, the requirement for clearance to navigate in the area to be avoided is mandatory.

(b) If the activity is not listed in table 150.380(a) of this section, or is not otherwise provided for in this subpart, the COTP's permission is required first.

§ 150.385 What is required in an emergency?

In an emergency, for the protection of life or property, a vessel may deviate from a vessel movement requirement in this subpart without clearance from a manned deepwater port's person in charge of vessel operations if the master advises the port PIC of the reasons for the deviation at the earliest possible moment.

Subpart E—Cargo Transfer Operations

§150.400 What does this subpart do?

This subpart prescribes rules that apply to the transfer of oil or natural gas at a deepwater port.

§ 150.405 How must a Cargo Transfer System (CTS) be tested and inspected?

- (a) No person may transfer oil or natural gas through a CTS at a deepwater port unless it has been inspected and tested according to this section.
- (b) The SPM-CTS must be maintained as required by the design standards used to comply with §149.650 of this chapter.
- (c) If the manufacturer's maximum pressure rating for any cargo transfer hose in a SPM-CTS has been exceeded

¹Areas to be avoided are in subpart J of this part.

²Not part of Port Installation.

³Exception, 33 CFR 150.440(e).