

Coast Guard, DHS

§ 150.622

LOCKOUT/TAGOUT

**§ 150.616 What are the requirements for lockout?**

The deepwater port operator must ensure that, if equipment (electrical, hydraulic, mechanical, and pneumatic) does not need to be powered during the work described in § 150.615(a), and has a lockout or other device to prevent the equipment from being turned on unintentionally, that lockout or other device is activated.

**§ 150.617 What are the requirements for tagout?**

(a) The deepwater port operator must ensure that, before work takes place on equipment that is disconnected from the power source, a tag complying with this section is placed at the location where the power is disconnected. The operator must ensure that, if there is a control panel for the equipment in line between the equipment and the location where the power is disconnected, a tag complying with this section is also placed on the control panel.

(b) Each tag or sign must have words stating:

- (1) That equipment is being worked on;
- (2) That power must not be restored or the equipment activated; and
- (3) The name of the person who placed the tag.

(c) Only the person who placed the tag, that person's immediate supervisor, or the relief person of either, is authorized to remove the tag.

RESPIRATORY PROTECTION

**§ 150.618 What are the requirements for respiratory protection?**

(a) The deepwater port operator must ensure that respiratory protection measures are taken in compliance with 29 CFR 1910.134 including establishment of a formal respiratory protection program.

(b) The deepwater port operator must ensure that measures for protection from exposure to asbestos are taken in compliance with 29 CFR 1910.1001.

(c) The deepwater port operator must ensure that measures for protection from exposure to inorganic lead are

taken in compliance with 29 CFR 1910.1025.

FALL ARREST

**§ 150.619 What are the fall arrest system requirements?**

The deepwater port operator must ensure that all personnel who are exposed to the risk of falling more than 6 feet, or who are at risk of falling any distance onto equipment with irregular surfaces, exposed moving components, electrically energized cables or connectors, or water, are protected against such a fall either by guardrails or other measures that comply with 29 CFR 1910.23 or 1910.28, or by the use of suitable lifesaving equipment that complies with 46 CFR part 160. In addition, the operator must take measures to control the risk of falling, tripping, or slipping in work areas and walkways due to the presence of loose material or wet conditions including spills.

MACHINE GUARDS

**§ 150.620 What are the requirements for protecting personnel from machinery?**

The deepwater port operator must ensure that all personnel are protected from the risks created by operating machinery through the use of guard devices or other measures that comply with 29 CFR 1910.212, or through the use of conspicuously posted warning signs that comply with 150.626 of this part.

SLINGS

**§ 150.621 What are the requirements for slings?**

The use of slings for material handling must comply with the requirements of 29 CFR 1910.184.

WARNING SIGNS

**§ 150.622 What are the warning sign requirements?**

The construction and use of warning signs must be in compliance with 29 CFR 1910.144 and 1910.145.

§ 150.623

33 CFR Ch. I (7-1-05 Edition)

CONFINED SPACE SAFETY

**§ 150.623 What are the requirements for protecting personnel from hazards associated with confined spaces?**

(a) All personnel must be protected by suitable measures from inadvertently entering a confined space containing a hazardous atmosphere that can cause death or serious injury.

(b) Each deepwater port operator shall evaluate the port-specific hazards associated with confined space entry and develop a confined space safe entry program that complies with:

(1) 29 CFR 1910.146 for permit-required confined spaces, where applicable; and

(2) A national consensus standard, as that term is defined in 29 CFR 1910.2, or that is set by a nationally recognized testing laboratory as defined in 29 CFR 1910.7 and that provides levels of personnel protection at least equivalent to those provided for shipyard personnel by 29 CFR part 1915, subpart B.

(c) To implement the confined space safe entry program, the deepwater port operator must determine the education, training and experience needed by the designated competent persons to safely conduct their duties, including:

(1) Identification, testing, and certification of confined spaces; and

(2) Training of personnel regarding dangers, etc.

(d) These measures must be specified in the port operations manual, along with a list of all confined spaces on the port, describing the specific hazards associated with each such space.

BLOOD-BORNE PATHOGENS

**§ 150.624 What are the requirements for protecting personnel from blood-borne pathogens?**

Measures for protection from the dangers of blood-borne pathogens must be taken in compliance with 29 CFR 1910.1030.

HAZARD COMMUNICATION PROGRAM

**§ 150.625 What must the hazard communication program contain?**

(a) Each deepwater port must have a hazard communication program (HCP) available for the training of, and re-

view by, all personnel on the deepwater port.

(b) The program must be in writing and describe or include:

(1) An inventory of each hazardous material on the deepwater port;

(2) The potential hazards of the material;

(3) The material's intended use on the deepwater port;

(4) The methods for handling and storing the material;

(5) The protective measures and equipment to be used to avoid hazardous exposure;

(6) The labeling, marking, or tagging of the material;

(7) The special precautions, such as lockout and tagout under §§ 150.616-150.617, that should be emphasized when working around the material;

(8) Information and training required for personnel onboard the deepwater port; and

(9) A material safety data sheet (MSDS) for the material.

(c) The information on a material safety data sheet on the material may be used as a substitute for items in paragraph (b) of this section that are addressed in the sheet.

(d) The program must be supplemented as necessary to address each hazardous material newly introduced on the deepwater port.

**§ 150.626 What is the hazard communication program used for?**

(a) The hazard communication program must ensure that all deepwater port employees, when required by their duties, work safely and responsibly with hazardous materials.

(b) The person in charge for safety must ensure that, before a person is allowed to work at the deepwater port:

(1) A copy of the hazard communication program is made available to the person; and

(2) The person is trained in the information contained in the program.

(c) The training must be supplemented to address each hazardous material newly introduced on the deepwater port.