

**Environmental Protection Agency**

**§ 467.34**

**SUBPART C**

*Cleaning or Etching Bath*

Pollutant or pollutant property	BAT effluent limitations	
	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched	
Chromium .....	0.079	0.032
Cyanide .....	0.052	0.022
Zinc .....	0.262	0.109
Aluminum .....	1.15	0.58

**SUBPART C**

*Cleaning or Etching Rinse*

Pollutant or pollutant property	BAT effluent limitations	
	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched	
Chromium .....	1.7	0.7
Cyanide .....	1.2	0.5
Zinc .....	5.7	2.4
Aluminum .....	25	13

**SUBPART C**

*Cleaning or Etching Scrubber Liquor*

Pollutant or pollutant property	BAT effluent limitations	
	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched	
Chromium .....	0.85	0.35
Cyanide .....	0.56	0.23
Zinc .....	2.82	1.18
Aluminum .....	12.43	6.19

[48 FR 49149, Oct. 24, 1983; 49 FR 11631, 11633, and 11634, Mar. 27, 1984, as amended at 53 FR 52370, Dec. 27, 1988]

**§ 467.34 New source performance standards.**

Any new source subject to this subpart must achieve the following performance standards.

(a) There shall be no discharge allowance for wastewater pollutants from the degassing operation.

(b) The discharge of wastewater pollutants from the core and ancillary operations except those listed in para-

graph (a) shall not exceed the values set forth below:

**SUBPART C**

*Core*

Pollutant or pollutant property	NSPS	
	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum extruded	
Chromium .....	0.13	0.051
Cyanide .....	0.068	0.027
Zinc .....	0.35	0.14
Aluminum .....	2.07	0.92
Oil and grease .....	3.39	3.39
Suspended solids .....	5.10	4.07
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.0 to 10.0 at all times.

**SUBPART C**

*Extrusion Press Leakage*

Pollutant or pollutant property	NSPS	
	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum extruded	
Chromium .....	0.11	0.045
Cyanide .....	0.060	0.024
Zinc .....	0.31	0.126
Aluminum .....	1.82	0.81
Oil and grease .....	2.98	2.98
Suspended solids .....	4.47	3.58
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.0 to 10.0 at all times.

**SUBPART C**

*Direct Chill Casting Contact Cooling Water*

Pollutant or pollutant property	NSPS	
	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum cast by semicontinuous methods	
Chromium .....	0.49	0.20
Cyanide .....	0.27	0.11
Zinc .....	1.36	0.56
Aluminum .....	8.12	3.60
Oil and grease .....	13.29	13.29
Suspended solids .....	19.94	15.95
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> The pH shall be maintained within the range of 7.0 to 10.0 at all times except for those situations when this waste stream is discharged separately and without commingling with any other wastewater in which case the pH shall be within the range of 6.0 to 10.0 at all times.

§ 467.35

40 CFR Ch. I (7-1-05 Edition)

SUBPART C

*Press Heat Treatment Contact Cooling Water*

Pollutant or pollutant property	NSPS	
	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum quenched	
Chromium .....	0.76	0.31
Cyanide .....	0.41	0.17
Zinc .....	2.08	0.86
Aluminum .....	12.45	5.52
Oil and grease .....	20.37	20.37
Suspended solids .....	30.56	24.45
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.0 to 10.0 at all times.

SUBPART C

*Solution Heat Treatment Contact Cooling Water*

Pollutant or pollutant property	NSPS	
	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum quenched	
Chromium .....	0.76	0.31
Cyanide .....	0.41	0.17
Zinc .....	2.08	0.86
Aluminum .....	12.45	5.52
Oil and grease .....	20.37	20.37
Suspended solids .....	30.56	24.45
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.0 to 10.0 at all times.

SUBPART C

*Cleaning or Etching Bath*

Pollutant or pollutant property	NSPS	
	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched	
Chromium .....	0.067	0.027
Cyanide .....	0.036	0.015
Zinc .....	0.183	0.075
Aluminum .....	1.094	0.485
Oil and grease .....	1.79	1.79
Suspended solids .....	2.69	2.15
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.0 to 10.0 at all times.

SUBPART C

*Cleaning or Etching Rinse*

Pollutant or pollutant property	NSPS	
	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched	
Chromium .....	0.52	0.21
Cyanide .....	0.28	0.11
Zinc .....	1.42	0.59
Aluminum .....	8.50	3.77
Oil and grease .....	13.91	13.91
Suspended solids .....	20.87	16.70
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.0 to 10.0 at all times.

SUBPART C

*Cleaning or Etching Scrubber Liquor*

Pollutant or pollutant property	NSPS	
	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched	
Chromium .....	0.72	0.29
Cyanide .....	0.39	0.16
Zinc .....	1.97	0.81
Aluminum .....	11.81	5.24
Oil and grease .....	19.33	19.33
Suspended solids .....	29.00	23.20
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.0 to 10.0 at all times.

[48 FR 49149, Oct. 24, 1983; 49 FR 11633 and 11634, Mar. 27, 1984, as amended at 53 FR 52370, Dec. 27, 1988]

**§ 467.35 Pretreatment standards for existing sources.**

(a) Except as provided in 40 CFR 403.7 and 403.13, any existing source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for existing sources.

(b) There shall be no discharge allowance for wastewater pollutants from the degassing operation.

(c) The mass of wastewater pollutants from the core and ancillary operations except those identified in paragraph (b), introduced into a POTW shall not exceed the following values: