

## § 65.65

## 40 CFR Ch. I (7–1–05 Edition)

standard cubic foot) flow rate or the applicable concentration value in table 1 to this subpart, engineering assessment may be used to determine the flow rate or concentration for the representative operating condition expected to yield the highest flow rate or concentration.

(1) If the TRE index value calculated using such engineering assessment and the TRE index value equation in paragraph (h) of this section is greater than 4.0, then the owner or operator is not required to perform the measurements specified in paragraphs (c) through (g) of this section.

(2) If the TRE index value calculated using such engineering assessment and the TRE index value equation in paragraph (h) of this section is less than or equal to 4.0, then the owner or operator is required either to perform the measurements specified in paragraphs (c) through (g) of this section for group determination or to consider the process vent a Group 1 process vent and comply with the requirement (or standard) specified in § 65.63(a) and, if applicable, § 65.63(b).

(3) Engineering assessment includes, but is not limited to, the examples specified in paragraphs (i)(3)(i) through (iv) of this section.

(i) Previous test results provided the tests are representative of current operating practices at the process unit.

(ii) Bench-scale or pilot-scale test data representative of the process under representative operating conditions.

(iii) Maximum flow rate, TOC emission rate, organic HAP emission rate, organic HAP or TOC concentration, or net heating value limit specified or implied within a permit limit applicable to the process vent.

(iv) Design analysis based on accepted chemical engineering principles, measurable process parameters, or physical or chemical laws or properties. Examples of analytical methods include, but are not limited to, the following examples:

(A) Use of material balances based on process stoichiometry to estimate maximum TOC or organic HAP concentrations;

(B) Estimation of maximum flow rate based on physical equipment design such as pump or blower capacities;

(C) Estimation of TOC or organic HAP concentrations based on saturation conditions; and

(D) Estimation of maximum expected net heating value based on the stream concentration of each organic compound or, alternatively, as if all TOC in the stream were the compound with the highest heating value.

(4) All data, assumptions, and procedures used in the engineering assessment shall be documented. The owner or operator shall maintain the records specified in § 65.66(a), (b), (c), or (d), as applicable.

### § 65.65 Monitoring.

(a) An owner or operator of a Group 2A process vent maintaining a TRE index value greater than 1.0 without a recovery device shall monitor based on the approved plan as specified in § 65.63(d).

(b) As required in § 65.63(a) and (c), an owner or operator of a Group 2A process vent maintaining a TRE index value greater than 1.0 with a recovery device or a Group 1 process vent shall comply with § 65.142(b).

### § 65.66 Recordkeeping provisions.

(a) *TRE index value records.* The owner or operator shall maintain records of measurements, engineering assessments, and calculations performed to determine the TRE index value of the process vent according to the procedures of § 65.64(h), including those records associated with halogen vent stream determination. Documentation of engineering assessments shall include all data, assumptions, and procedures used for the engineering assessments, as specified in § 65.64(i). As specified in § 65.67(a), the owner or operator shall include this information in the Initial Compliance Status Report.

(b) *Flow rate records.* Each owner or operator who elects to demonstrate that a process vent is Group 2B based on a flow rate less than 0.011 standard cubic meter per minute (0.40 standard cubic foot per minute) shall record the flow rate as measured using the sampling site and flow rate determination procedures specified in § 65.64(b) and (d)

## Environmental Protection Agency

## § 65.67

or determined through engineering assessment as specified in § 65.64(i). As specified in § 65.67(a), the owner or operator shall include this information in the Initial Compliance Status Report.

(c) *Concentration records.* Each owner or operator who elects to demonstrate that a process vent is Group 2B based on a concentration less than the applicable criteria in table 1 to this subpart shall record the organic HAP or TOC concentration as measurement using the sampling site and HAP or TOC concentration determination procedures specified in § 65.64(b) and (c) or determined through engineering assessment as specified in § 65.64(i). As specified in § 65.67(a), the owner or operator shall include this information in the Initial Compliance Status Report.

(d) *Process change records.* The owner or operator shall keep up-to-date, readily accessible records as specified in the following and shall report this information as specified in § 65.67(b):

(1) If the process vent is Group 2B on the basis of flow rate being less than 0.011 scmm (0.40 standard cubic foot), then the owner or operator shall keep records of any process changes as defined in § 65.63(f) that increase the process vent flow rate and any recalculation or measurement of the flow rate pursuant to § 65.63(f).

(2) If the process vent is Group 2B on the basis of organic HAP or TOC concentration being less than the applicable value in table 1 to this subpart, then the owner or operator shall keep records of any process changes as defined in § 65.63(f) that increase the organic HAP or TOC concentration of the process vent and any recalculation or measurement of the concentration pursuant to § 65.63(f).

(3) If the process vent is Group 2A or Group 2B on the basis of the TRE index value being greater than 1.0, then the owner or operator shall keep records of any process changes as defined in § 65.63(f) and any recalculation of the TRE index value pursuant to § 65.63(f).

(4) As a result of a process change, if a process vent that was Group 2B on any basis becomes a Group 2B process vent only on the basis of having a TRE greater than 4.0, then the owner or operator shall keep records of the TRE index value determination performed

according to the sample site and TRE index value determination procedures of § 65.64(b)(1) and (h) or determined through engineering assessment as specified in § 65.64(i).

(e) *Other Group 2A records.* An owner or operator of a Group 2A process vent maintaining a TRE index value greater than 1.0 without a recovery device shall record the parameters monitored based on the approved plan as specified in § 65.63(d).

### § 65.67 Reporting provisions.

(a) *Initial compliance status report.* The owner or operator shall submit as part of the Initial Compliance Status Report specified in § 65.5(d) the information recorded in § 65.66(a), (b), and (c), as applicable.

(b) *Process change.* (1) Whenever a process change, as described in § 65.63(f), is made that causes a Group 2A or 2B process vent to become a Group 1 process vent or a Group 2B process vent to become a Group 2A process vent, the owner or operator shall either submit a report within 60 days after the performance test or group determination or submit a report included as part of the next periodic report. The report shall include the following information:

(i) A description of the process change;

(ii) The results of the recalculation of the flow rate, organic HAP or TOC concentration, and/or TRE index value required under § 65.63(f) and recorded under § 65.66(d); and

(iii) A statement that the owner or operator will comply with the provisions of § 65.63 by the schedules specified in § 65.63(f)(4) through (6).

(2) For process vents that become Group 1 process vents after a process change requiring a performance test to be conducted for the control device being used as specified in subpart G of this part, the owner or operator shall specify that the performance test has become necessary due to a process change. This specification shall be made in the notification to the Administrator of the intent to conduct a performance test as provided in § 65.164(b)(1).

(3) Whenever a process change as described in § 65.63(f) is made that